

October 15, 2021

Ms. Andrea Vasquez
Delicato Vineyards
12001 S Highway 99
Manteca, CA 95336

Re: Notice of Preliminary Decision – Title V Permit Renewal
Facility Number: N-266
Project Number: N-1201563

Dear Ms. Vasquez:

Enclosed for your review and comment is the District's analysis of the application to renew the Federally Mandated Operating Permit for Delicato Vineyards at 12001 S Highway 99, Manteca, California.

The notice of preliminary decision for this project has been posted on the District's website (www.valleyair.org). After addressing all comments made during the 30-day public notice and the 45-day EPA comment periods, the District intends to issue the renewed Federally Mandated Operating Permit. Please submit your written comments on this project within the 30-day public comment period, as specified in the enclosed public notice.

Thank you for your cooperation in this matter. If you have any questions, please contact Mr. Errol Villegas, Permit Services Manager, at (559) 230-5900.

Sincerely,



Brian Clements
Director of Permit Services

Enclosures

cc: Courtney Graham, CARB (w/enclosure) via email
cc: Laura Yannayon, EPA (w/enclosure) via EPS

Samir Sheikh
Executive Director/Air Pollution Control Officer

Northern Region
4800 Enterprise Way
Modesto, CA 95356-8718
Tel: (209) 557-6400 FAX: (209) 557-6475

Central Region (Main Office)
1990 E. Gettysburg Avenue
Fresno, CA 93726-0244
Tel: (559) 230-6000 FAX: (559) 230-6061

Southern Region
34946 Flyover Court
Bakersfield, CA 93308-9725
Tel: (661) 392-5500 FAX: (661) 392-5585

**SAN JOAQUIN VALLEY
AIR POLLUTION CONTROL DISTRICT**

**Proposed Title V Permit Renewal Evaluation
Delicato Vineyards
N-266**

TABLE OF CONTENTS

I.	PROPOSAL.....	2
II.	FACILITY LOCATION	2
III.	EQUIPMENT LISTING	3
IV.	GENERAL PERMIT TEMPLATE USAGE	3
V.	SCOPE OF EPA AND PUBLIC REVIEW	3
VI.	FEDERALLY ENFORCEABLE REQUIREMENTS	4
VII.	REQUIREMENTS NOT FEDERALLY ENFORCEABLE.....	7
VIII.	PERMIT REQUIREMENTS	10
IX.	PERMIT SHIELD	57
X.	CALIFORNIA ENVIRONMENTAL QUALITY ACT	57
XI.	PERMIT CONDITIONS	58
ATTACHMENTS		58
A.	DRAFT RENEWED TITLE V OPERATING PERMIT	
B.	PREVIOUS TITLE V OPERATING PERMIT	
C.	DETAILED SUMMARY LIST OF FACILITY PERMITS	

TITLE V PERMIT RENEWAL EVALUATION

Winery

Engineer: Ramon Norman
Date: October 15, 2021

Facility Number: N-266
Facility Name: Delicato Vineyards
Mailing Address: 12001 S Highway 99
Manteca, CA 95336

Contact Name: Andrea Vasquez
Phone: (209) 824-3675
Email: Andrea.Vasquez@Delicato.com

Responsible Official: John Yarborough
Title: VP of Winery Operations

Project # : N-1201563
Deemed Complete: April 29, 2020

I. PROPOSAL

Delicato Vineyards was issued a Title V permit on October 4, 2010 and the facility's Title V permit was last renewed on June 16, 2016. As required by District Rule 2520, the applicant is requesting a permit renewal. The existing Title V permit shall be reviewed and modified to reflect all applicable District and federal rules updated, removed, or added since the last renewal of the Title V permit.

The purpose of this evaluation is to provide the legal and factual basis for all updated applicable requirements and to determine if the facility will comply with these updated requirements. It also specifically identifies all additions, deletions, and/or changes made to permit conditions or equipment descriptions.

II. FACILITY LOCATION

Delicato Vineyards is located at 12001 S Highway 99, Manteca, CA.

III. EQUIPMENT LISTING

A detailed facility printout listing all permitted equipment at the facility is included as Attachment C.

IV. GENERAL PERMIT TEMPLATE USAGE

The applicant is requesting to use the following model general permit Templates:

A. Template SJV-UM-0-3 Facility Wide Umbrella

The applicant has requested to utilize template No. SJV-UM-0-3, Facility Wide Umbrella. Based on the information submitted in the Template Qualification Form, the applicant qualifies for the use of this template.

V. SCOPE OF EPA AND PUBLIC REVIEW

Certain segments of the proposed Renewed Operating Permit are based on model general permit templates that have been previously subject to EPA and public review. The terms and conditions from the model general permit templates are included in the proposed permit and are not subject to further EPA and public review.

For permit applications utilizing model general permit templates, public and agency comments on the District's proposed actions are limited to the applicant's eligibility for model general permit template, applicable requirements not covered by the model general permit template, and the applicable procedural requirements for issuance of Title V Operating Permits.

The following permit conditions, including their underlying applicable requirements, originate from model general permit templates and are not subject to further EPA or public review.

Permit Unit #	Permit Description	Condition #s
N-266-0-2	Facility-Wide Permit	1 through 22 and 26 through 40

VI. FEDERALLY ENFORCEABLE REQUIREMENTS

A. Rules Updated or Evaluated

- District Rule 2201 - New and Modified Stationary Source Review Rule (amended April 21, 2011 (SIP version of the Rule) ⇒ amended August 15, 2019)
- District Rule 2520 - Federally Mandated Operating Permits (amended June 21, 2001 (Approved Title V Rule) ⇒ amended August 15, 2019)
- District Rule 4306 - Boilers, Steam Generators, and Process Heaters – Phase 3 (amended October 16, 2008 (SIP version of the Rule) ⇒ amended December 17, 2020)
- District Rule 4320 - Advanced Emission Reduction Options for Boilers, Steam Generators, and Process Heaters Greater than 5.0 MMBtu/hr (adopted October 16, 2008 (SIP version of the Rule) ⇒ amended December 17, 2020)
- District Rule 4601 - Architectural Coatings (amended December 17, 2009 (SIP version of the Rule) ⇒ amended April 16, 2020)
- District Rule 4702 - Internal Combustion Engines (amended November 14, 2013 (SIP version of the Rule) ⇒ amended August 19, 2021)
- 40 CFR Part 60, Subpart IIII - Standards of Performance for Stationary Compression Ignition Internal Combustion Engines (last updated June 29, 2021)
- 40 CFR Part 60, Subpart JJJJ - Standards of Performance for Stationary Spark Ignition Internal Combustion Engines (last updated June 29, 2021)
- 40 CFR Part 63, Subpart ZZZZ - National Emissions Standards for Hazardous Air Pollutants for Stationary Reciprocating Internal Combustion Engines (Sections amended November 19, 2020 and December 4, 2020)
- 40 CFR Part 64 - Compliance Assurance Monitoring (adopted October 22, 1997)
- 40 CFR Part 82, Subpart B - Servicing of Motor Vehicle Air Conditioners (amended May 6, 2021)
- 40 CFR Part 82, Subpart F - Recycling and Emissions Reduction (amended May 6, 2021)

B. Rules Removed

There are no applicable rules that were removed since the last Title V renewal.

C. Rules Added

There are no applicable rules that were added since the last Title V renewal.

D. Rules Not Updated

- District Rule 1070 - Inspections (amended December 17, 1992)
- District Rule 1081 - Source Sampling (amended December 16, 1993)
- District Rule 1100 - Equipment Breakdown (amended December 17, 1992) (Non SIP replacement for San Joaquin County Rule 110)
- District Rule 1160 - Emission Statements (adopted November 18, 1992)
- District Rule 2010 - Permits Required (amended December 17, 1992)
- District Rule 2020 - Exemptions (amended August 18, 2011 (SIP version of the Rule), amended December 18, 2014)
- District Rule 2031 - Transfer of Permits (amended December 17, 1992)
- District Rule 2070 - Standards for Granting Applications (amended December 17, 1992)
- District Rule 2080 - Conditional Approval (amended December 17, 1992)
- District Rule 2410 - Prevention of Significant Deterioration (adopted June 16, 2011 and became effective November 26, 2012)
- District Rule 4101 - Visible Emissions (amended February 17, 2005)
- District Rule 4201 - Particulate Matter Concentration (amended December 17, 1992)
- District Rule 4301 - Fuel Burning Equipment (amended December 17, 1992)
- District Rule 4304 - Equipment Tuning Procedure for Boilers, Steam Generators, and Process Heaters (adopted October 19, 1995)

- District Rule 4305 - Boilers, Steam Generators, and Process Heaters – Phase 2 (amended August 21, 2003)
- District Rule 4566, Organic Material Composting Operation (adopted August 18, 2011)
- District Rule 4621, Gasoline Transfer into Stationary Storage Containers, Delivery Vessels and Bulk Plants (amended December 19, 2013)
- District Rule 4622, Gasoline Transfer into Motor Vehicle Fuel Tanks (amended December 19, 2013)
- District Rule 4694, Wine Fermentation and Storage Tanks (adopted December 15, 2005) (Only Wine Storage Tank Requirements)¹
- District Rule 4701 - Internal Combustion Engines – Phase 1 (amended August 21, 2003)
- District Rule 4801 - Sulfur Compounds (amended December 17, 1992) (Non SIP replacement for San Joaquin County Rule 407)
- District Rule 8011 - Fugitive PM10 Control: General Requirements (amended August 19, 2004)
- District Rule 8021 - Fugitive PM10 Control: Construction, Demolition, Excavation, and Extraction Activities (amended August 19, 2004)
- District Rule 8031 - Fugitive PM10 Control: Handling and Storage of Bulk Materials (amended August 19, 2004)
- District Rule 8041 - Fugitive PM10 Control: Carryout and Trackout (amended August 19, 2004)
- District Rule 8051 - Fugitive PM10 Control: Open Areas (amended August 19, 2004)
- District Rule 8061 - Fugitive PM10 Control: Paved and Unpaved Roads (amended August 19, 2004)

¹The SIP submittal for District Rule 4694 was amended on August 18, 2011 to exclude the fermentation requirements. The wine storage requirements were approved for inclusion in the SIP without the fermentation requirements on November 29, 2012; therefore, only the wine storage requirements federally enforceable.

- District Rule 8071 - Fugitive PM10 Control: Unpaved Vehicle/Equipment Areas (amended September 16, 2004)
- 40 CFR Part 61 Subpart M - National Emission Standard for Asbestos (last amended July 20, 2004)

VII. REQUIREMENTS NOT FEDERALLY ENFORCEABLE

For each Title V source, the District issues a single permit that contains the Federally Enforceable requirements, as well as the District-only requirements. The District-only requirements are not a part of the Title V Operating Permits. The terms and conditions that are part of the facility's Title V permit are designated as "Federally Enforceable Through Title V Permit".

For this facility, the following are not federally enforceable and will not be discussed in further detail:

A. Rules Added/Updated

None

B. Rules Not Updated

- **District Rule 2040 - Applications** (amended December 17, 1992 ⇒ removed from SIP December 16, 2004, 69 FR 67062)

The purpose of this rule is to explain the procedures for filing, denying, and appealing the denial of applications for a District Authority to Construct (ATC) or Permit to Operate.

The following condition is based solely on this rule and is therefore not federally enforceable through Title V.

Permit Unit #	Permit Description	Condition #
N-266-0-2	Facility-Wide Permit	7

- **District Rule 4102 - Nuisance** (amended December 17, 1992)

The purpose of this rule is to protect the health and safety of the public. This rule stipulates that a person shall not discharge from any source whatsoever such quantities of air contaminants or other materials which cause injury, detriment, nuisance or annoyance to any considerable number of persons or to the public or which endanger the comfort, repose, health or safety of any

such person or the public or which cause or have a natural tendency to cause injury or damage to business or property.

The following conditions are based solely on this rule and are therefore not federally enforceable through Title V.

Permit Unit #	Permit Description	Condition #s
N-266-0-2	Facility-Wide Permit	42
N-266-1-7	Gasoline Dispensing Operation	1
N-266-3-3	106 bhp Diesel Emergency Engine Powering a Firewater Pump	2
N-266-953-1	302 bhp Natural Gas Emergency Engine Powering an Electrical Generator	2

The following conditions are based on this rule and other federally enforceable requirements. Therefore, the conditions are federally enforceable, but are not federally enforceable through this rule:

Permit Unit #	Permit Description	Condition #s
N-266-952-1	250 bhp Diesel Emergency Engine Powering a Firewater Pump	5 & 7

- **District Rule 4694, Wine Fermentation and Storage Tanks** (adopted December 15, 2005) (Wine Fermentation Requirements)

The purpose of this rule is to reduce emissions of volatile organic compounds (VOC) from the fermentation and bulk storage of wine, or achieve equivalent reductions from alternative emission sources. This rule applies to any winery fermenting wine and/or storing wine in bulk containers.

This rule was adopted on December 15, 2005 and submitted to EPA for inclusion in the State Implementation Plan (SIP). On August 18, 2011, the District amended the SIP submittal for District Rule 4694 to exclude the fermentation requirements of the rule while maintaining the storage requirements. The wine storage requirements were approved for inclusion in the SIP on November 29, 2012 without the fermentation requirements; therefore, the wine fermentation requirements are not federally enforceable.

The following conditions are based solely on the wine fermentation requirements of this rule and are therefore not federally enforceable through Title V.

Permit Unit #	Permit Description	Condition #s
N-266-0-2	Facility-Wide Permit	43 through 48

Permit Unit #	Permit Description	Condition #s
N-266-9-4 through -10-4; N-266-20-4 through -33-4; N-266-38-4 through -39-4; N-266-48-4 through -49-4; N-266-56-4 through -106-4; N-266-113-4 through -320-4; N-266-322-4 through -335-4; N-266-338-4 through -502-4; N-266-569-2 through -597-2; N-266-599-2 through -639-2; N-266-643-2 through -676-2	Wine Fermentation and Storage Tanks	8
N-266-678-2 through -775-2	Wine Fermentation and Storage Tanks	9

- **California Code of Regulations (CCR) Title 17, Section 93115 – Airborne Toxic Control Measure for Stationary Compression Ignition Engines** (amended May 19, 2011)

The purpose of this California regulation is to reduce diesel PM and criteria pollutant emissions from stationary diesel-fueled compression-ignition (CI) engines. This regulation applies to any person who either sells a stationary compression-ignition engine, offers a stationary compression-ignition engine for sale, leases a stationary compression-ignition engine, or purchases a stationary compression-ignition engine for use in California, unless such engine is: a portable compression-ignition engine, a compression-ignition engine used to provide motive power, an auxiliary compression-ignition engine used on a marine vessel, or an agricultural wind machine. This regulation also applies to any person who owns or operates a stationary CI engine in California with a rated brake horsepower greater than 50 (> 50 bhp) except as specified in the regulation.

The following condition is based solely on this rule and is therefore not federally enforceable through Title V.

Permit Unit #	Permit Description	Condition #s
N-266-3-3	106 bhp Diesel Emergency Engine Powering a Firewater Pump	19

The following conditions are based on this rule and other federally enforceable requirements. Therefore, the conditions are federally enforceable, but are not federally enforceable through this rule.

Permit Unit #	Permit Description	Condition #s
N-266-3-3	106 bhp Diesel Emergency Engine Powering a Firewater Pump	2, 5, 8, & 18, & 20

Permit Unit #	Permit Description	Condition #s
N-266-952-1	250 bhp Diesel Emergency Engine Powering a Firewater Pump	2-5, 7, & 9-11

VIII. PERMIT REQUIREMENTS

The purpose of this evaluation is to review changes to federally enforceable requirements; therefore, this compliance section will only address rules that have been amended or added since the issuance of the initial Title V permit or most recent renewal of the Title V permit.

A. District Rule 2201 - New and Modified Stationary Source Review Rule (NSR)

District Rule 2201 has been amended since this facility's Title V permit was last renewed. However, the requirements of this rule are only triggered at the time the source undergoes a modification. All applicable requirements from any NSR permit actions have already been incorporated into the current Title V permit.

B. District Rule 2520 - Federally Mandated Operating Permits

The purpose of this rule is to provide an administrative mechanism for the following: issuing operating permits for new and modified sources of air contaminants in accordance with requirements of 40 CFR Part 70; issuing renewed operating permits for sources of air contaminants in accordance with requirements of 40 CFR Part 70; revising, reopening, revoking, and terminating operating permits for sources of air contaminants in accordance with requirements of 40 CFR Part 70; incorporating requirements authorized by preconstruction permits issued under District Rule 2201 (New and Modified Stationary Source Review) in a Part 70 permit as administrative amendments, provided that such permits meet the necessary procedural and compliance requirements.

District Rule 2520 was last amended on August 15, 2019 and the California Air Resources Board (ARB) submitted the amended rule to the US EPA on behalf of the District as a revision to the District's Title V program on November 12, 2019. The only purpose of the August 2019 amendments to District Rule 2520 was to allow the noticing required by the rule to be performed electronically rather than by publication in a newspaper, as allowed by Federal regulations. The amendments have no effect on the applicable requirements for the permit units that are subject to the rule.

C. District Rule 4306 - Boilers, Steam Generators, and Process Heaters – Phase 3

The purpose of this rule is to limit emissions of oxides of nitrogen (NO_x) and carbon monoxide (CO) from boilers, steam generators, and process heaters. This rule applies to any gaseous fuel or liquid fuel fired boiler, steam generator, or process heater with a total rated heat input greater than 5 million Btu per hour.

The October 16, 2008 version of District Rule 4306 was approved into the SIP on January 13, 2010. The rule was amended on December 17, 2020 and the California Air Resources Board (ARB) sent the amendments to EPA for inclusion in the SIP on March 12, 2021. The December 17, 2020 amendments to District Rule 4306 added definitions to improve clarity and to reflect the changes in requirements, removed the definition of a load following unit and the specific emission limits for load following units and required these units to comply with the same emission limits as other units of the same size, added additional categories of units and required lower Tier 2 NO_x emission limits for various categories, and established dates for the submission of emission control plans and ATC applications and compliance with the lower Tier 2 emission limits.

Delicato Vineyards has one 5.978 MMBtu/hr natural gas-fired boiler (Unit N-266-503-6) at the facility that is subject to the requirements of District Rule 4306. The only potential effect of the December 17, 2020 amendments to District Rule 4306 is to lower the required NO_x emission limit or reduce the maximum annual fuel input allowed for this unit.

N-266-503-6: 5.978 MMBTU/HR FULTON NATURAL GAS-FIRED BOILER WITH A FULTON MODEL 102347 LOW NOX BURNER

Permit Unit N-266-503-6 is currently subject to the applicable emission limits of District Rule 4306, Section 5.1 – NO_x and CO Emission Limits, Table 1 - Tier 1 NO_x and CO Limits as shown in the table below. The existing unit will become subject to the applicable Tier 2 NO_x and CO limits in accordance with the compliance schedule of the rule.

Section 5.1 - NO_x and CO Emissions Limits

Section 5.1.1 requires that, except for units subject to Section 5.2, on and after the compliance deadline specified in Section 7 units subject to Section 5.0 shall not be operated in a manner which exceeds the applicable NO_x and CO emissions limits specified in Table 1 - Tier 1 NO_x and CO Limits and Table 2 - Tier 2 NO_x and CO Limits (with all ppmv emission limits referenced at dry stack gas conditions and 3.00 percent by volume stack gas oxygen (O₂)).

Rule 4306, Table 1: Tier 1 NO _x and CO Limits					
Category	Operated on Gaseous Fuel			Operated on Liquid Fuel	
	NO _x Limit		CO Limit (ppmv)	NO _x Limit	CO Limit (ppmv)
	Standard Option	Enhanced Option			
A. Units with a rated heat input equal to or less than 20.0 MMBtu/hour, except for Categories C, D, E, F, G, H, and I units	15 ppmv or 0.018 lb/MMBtu	9 ppmv or 0.011 lb/MMBtu	400	40 ppmv or 0.052 lb/MMBtu	400

The current permit requirements for this unit limit NO_x emissions to no more than 9 ppmv @ 3% O₂ and the unit complies with all current applicable requirements of District Rule 4306. The information previously provided by the applicant and included in District files indicates that this unit is a fire tube boiler; therefore, District Rule 4306 will require submittal of an emission control plan and ATC application to comply with the applicable requirements of District Rule 4306 by the deadlines specified in the rule.

Pursuant to Section 7.0 – Compliance Schedule, an ATC application and Emission Control Plan must be submitted for this unit to comply with the applicable Tier 2 NO_x and CO limits by May 1, 2028 and the unit must comply with the applicable Tier 2 NO_x and CO limits by December 31, 2029. Compliance with the applicable Tier 2 NO_x and CO limits will be addressed later through the submittal of an ATC application and an appropriate Title V permit modification process, in accordance with the compliance schedule specified in the rule.

The following conditions of the proposed requirements for renewed Title V permit ensure compliance with this rule.

Permit Unit #	Permit Description	Condition #s
N-266-503-6	5.978 MMBtu/hr Natural Gas Boiler	6-7, 11, 13-18, 20, 22-25, and 28-29

D. District Rule 4320 - Advanced Emission Reduction Options for Boilers, Steam Generators, and Process Heaters Greater than 5.0 MMBtu/hr

The purpose of this rule is to limit emissions of oxides of nitrogen (NO_x), carbon monoxide (CO), oxides of sulfur (SO₂), and particulate matter 10 microns or less (PM₁₀) from boilers, steam generators, and process heaters. This rule applies to any gaseous fuel or liquid fuel fired boiler, steam generator, or process heater with a total rated heat input greater than 5 million Btu per hour.

The October 16, 2008 version of District Rule 4320 was approved into the SIP on March 25, 2011. The rule was amended on December 17, 2020 and ARB sent the amendments to EPA for inclusion in the SIP on March 12, 2021. The December 17, 2020 amendments to District Rule 4320 added definitions to improve clarity and to reflect the changes in requirements, added additional categories of units and required lower Tier 2 NO_x emission limits for various categories, and established dates for the submission of emission control plans and ATC applications and compliance with the lower Tier 2 emission limits.

Delicato Vineyards has one 5.978 MMBtu/hr natural gas-fired boiler (Unit N-266-503-6) at the facility that is subject to the requirements of District Rule 4320. The only potential effect of the December 17, 2020 amendments to District Rule 4320 is to lower the required NO_x emission limit or reduce the maximum annual fuel input allowed for this unit.

N-266-503-6: 5.978 MMBTU/HR FULTON NATURAL GAS-FIRED BOILER WITH A FULTON MODEL 102347 LOW NOX BURNER

Permit Unit N-266-503-6 is currently subject to the applicable NO_x emission limit specified in District Rule 4320, Section 5.2 – NO_x and CO Emission Limits, Table 1 - Tier 1 NO_x Emission Limits, as shown in the table below. Permit Unit N-266-503-6 is also subject to the CO limit of 400 ppmv @ 3% O₂ specified in District Rule 4320, Section 5.2 – NO_x and CO Emission Limits. The existing unit will become subject to the applicable Tier 2 NO_x limits in accordance with the compliance schedule of the rule.

Section 5.2 - NO_x and CO Emissions Limits

Section 5.2 requires that units subject to this section shall not be operated in a manner which exceeds the applicable NO_x emissions limit specified in Table 1 - Tier 1 NO_x Emissions Limits (until December 31, 2023) and Table 2 - Tier 2 NO_x Emissions Limits (on and after December 31, 2023). Section 5.2 also requires that units subject to this section shall not be operated in a manner to which exceeds a carbon monoxide (CO) emissions limit of 400 ppmv. All ppmv emission limits specified in Section 5.2 are referenced at dry stack gas conditions and 3.00 percent by volume stack gas oxygen (O₂). Emission concentrations shall be corrected to 3.00 percent oxygen in accordance with Section 8.1.

Rule 4320, Table 1: Tier 1 NO_x Emission Limits			
Category	NO_x Limit	Authority to Construct	Compliance Deadline
A. Units with a total rated heat input > 5.0 MMBtu/hr to ≤ 20.0 MMBtu/hr, except for Categories C through G units	a) Standard Schedule 9 ppmv or 0.011 lb/MMBtu; or	July 1, 2011	July 1, 2012
	b) Enhanced Schedule 6 ppmv or 0.007 lb/MMBtu	January 1, 2013	January 1, 2014

Section 5.4 - Particulate Matter Control Requirements

Section 5.4.1 of this rule requires the operator of a unit to comply with one of the following requirements for control of particulate matter (PM):

- 1) Operators shall fire units exclusively on PUC-quality natural gas, commercial propane, butane, or liquefied petroleum gas, or a combination of such gases;
- 2) Operators shall limit fuel sulfur content to no more than five (5) grains of total sulfur per one hundred (100) standard cubic feet; or
- 3) operators shall install and properly operate an emission control system that reduces SO₂ emissions by at least 95% by weight; or limit exhaust SO₂ to less than or equal to 9 ppmv corrected to 3.0% O₂

The current permit requirements for this unit require that the unit only be fired on PUC-quality natural gas and limit NO_x emissions to no more than 9 ppmv @ 3% O₂. The unit complies with all current applicable requirements of District Rule 4320. The information previously provided by the applicant and included in District files indicates that this unit is a fire tube boiler; therefore, District Rule 4320 will require submittal of an emission control plan and ATC application to comply with the applicable requirements of District Rule 4320 by the deadlines specified in the rule.

Pursuant to Section 5.2, Table 2- Tier 2 NO_x Emission Limits and Section 7.0 – Compliance Schedule, an ATC application and Emission Control Plan must be submitted for this unit to comply with the applicable Tier 2 NO_x limits by May 1, 2022 and the unit must comply with the applicable Tier 2 NO_x limits by December 31, 2023. Compliance with the applicable Tier 2 NO_x limits will be addressed later through the submittal of an ATC application and an appropriate Title V permit modification process, in accordance with the compliance schedule specified in the rule.

The following conditions of the proposed requirements for renewed Title V permit ensure compliance with this rule.

Permit Unit #	Permit Description	Condition #s
N-266-503-6	5.978 MMBtu/hr Natural Gas Boiler	3, 6-7, 11, 13-20, 22-26, and 28-29

E. District Rule 4601 – Architectural Coatings

The purpose of this rule is to limit VOC emissions from architectural coatings. This rule specifies architectural coatings storage, cleanup, and labeling requirements. This rule is applicable to any person who supplies, sells, offers for sale, applies, or solicits the application of any architectural coating, or who manufactures, blends or repackages any architectural coating. This rule is applicable to any person who supplies, markets, sells, offers for sale, applies, or solicits the application of any architectural coating, or who manufactures, blends or repackages any architectural coating for use within the San Joaquin Valley Air Pollution Control District.

EPA approved District Rule 4601 as amended in December 17, 2009 for inclusion in the SIP on November 8, 2011. District Rule 4601 was last amended on April 16, 2020 and ARB sent District Rule 4601 as amended in April 16, 2020 to EPA for inclusion in the SIP on April 24, 2020; however, the latest amendments have not yet been included in the SIP.

As required by a September 2016 decision by the U.S. Court of Appeals for the Ninth Circuit in *Bahr v. U.S. Environmental Protection Agency*,² the April 16, 2020 amendments to District Rule 4601 added a contingency measure for the District's 2016 Ozone Plan that would remove the exemption for specific categories of coatings sold in small containers with a volume of one liter or less if EPA issues a finding that the San Joaquin Valley Air Basin has failed to attain, or to make reasonable further progress towards attainment of, the 2008 National Ambient Air Quality Standard (NAAQS) for ozone. The April 16, 2020 amendments to District Rule 4601 implemented provisions of the 2019 California Air Resources Board (ARB) Suggested Control Measure for Architectural Coatings,³ including lowering VOC limits for several categories of architectural coatings, setting VOC limits for three new categories of architectural coatings, and adding new requirements for colorants.

² United States Court of Appeals for the Ninth Circuit (September 12, 2016) *Bahr v. U.S. Environmental Protection Agency*. <https://cdn.ca9.uscourts.gov/datastore/opinions/2016/09/12/14-72327.pdf>

³ California Air Resources Board (May 2019) California Air Resources Board (CARB) Suggested Control Measure for Architectural Coatings. https://ww2.arb.ca.gov/sites/default/files/2020-05/10602_scm_final.pdf

The primary effect of the April 16, 2020 amendments to District Rule 4601 will be reducing VOC content limits required for specific categories of coatings and adding VOC content limits for specific categories of colorants. The current VOC content limits of District Rule 4601 and the VOC content limits of coatings and colorants that will be effective on and after January 1, 2022 are summarized below.

Section 5.1 - VOC Content Limits:

Except as provided in Sections 5.2 and 5.3, no person shall: manufacture, blend, or repackage for use within the District; or supply, sell, market or offer for sale within the District; or solicit for application or apply within the District any architectural coating or colorant with a VOC content in excess of the corresponding limit specified in Table 1 or Table 2, after the specified effective date in Table 1 or Table 2. Limits are expressed as VOC Regulatory, thinned to the manufacturer’s maximum thinning recommendation, excluding any colorant added to tint bases.

Rule 4601, Table 1 - VOC Content Limits for Coatings¹		
COATING CATEGORY	Current VOC Limit (g/l)	VOC Limit (g/l) Effective on and after 1/1/2022
Flat Coatings	50	50
Nonflat Coatings	100	50
Specialty Coatings	-	-
Aluminum Roof Coatings	400	100
Basement Specialty Coatings	400	400
Bituminous Roof Coatings	50	50
Bituminous Roof Primers	350	350
Bond Breakers	350	350
Building Envelope Coatings	-	50
Concrete Curing Compounds	350	350
Concrete/Masonry Sealers	100	100
Driveway Sealers	50	50
Dry Fog Coatings	150	50
Faux Finishing Coatings	350	350
Fire Resistive Coatings	350	150
Floor Coatings	100	50
Form-Release Compounds	250	100
Graphic Arts Coatings (Sign Paints)	500	500
High Temperature Coatings	420	420
Industrial Maintenance Coatings	250	250
Low Solids Coatings ²	120	120
Magnesite Cement Coatings	450	450

Rule 4601, Table 1 - VOC Content Limits for Coatings¹		
COATING CATEGORY	Current VOC Limit (g/l)	VOC Limit (g/l) Effective on and after 1/1/2022
Mastic Texture Coatings	100	100
Metallic Pigmented Coatings	500	500
Multi-Color Coatings	250	250
Pre-Treatment Wash Primers	420	420
Primers, Sealers, and Undercoaters	100	100
Reactive Penetrating Sealers	350	350
Recycled Coatings	250	250
Roof Coatings	50	50
Rust Preventative Coatings	250	250
Shellacs:		
Clear	730	730
Opaque	550	550
Specialty Primers, Sealers, and Undercoaters	100	100
Stains	250	100
Interior Stains		250
Stone Consolidants	450	450
Swimming Pool Coatings	340	340
Tile and Stone Sealers		100
Traffic Marking Coatings	100	100
Tub and Tile Refinish Coatings	420	420
Waterproofing Membranes	250	100
Wood Coatings	275	275
Wood Preservatives	350	350
Zinc-Rich Primers	340	340

1 Limits are expressed as VOC Regulatory (except where noted otherwise), thinned to the manufacturer's maximum thinning recommendation, excluding any colorant added to tint bases.

2 Units are grams of VOC per liter of coating, including water and exempt compounds, in accordance with Section 3.72.

Rule 4601, Table 2 VOC Content Limits for Colorants¹	
Colorants Added To	VOC Limit (g/l) Effective on and after 1/1/2022
Architectural Coatings, excluding Industrial Maintenance Coatings	50
Solvent Based Industrial Maintenance Coatings	600
Waterborne Industrial Maintenance Coatings	50
Wood Coatings	600

1 Limits are expressed as VOC Regulatory.

The following conditions of the proposed requirements of the facility-wide permit ensure compliance with this rule.

Permit Unit #	Permit Description	Condition #s
N-266-0-2	Facility-Wide Permit	23-25

F. District Rule 4702 - Internal Combustion Engines

The purpose of this rule is to limit the emissions of nitrogen oxides (NO_x), carbon monoxide (CO), volatile organic compounds (VOC), particulate matter (PM), and sulfur oxides (SO_x) from internal combustion engines. This rule applies to any internal combustion engine with a rated at 25 brake horsepower or greater.

The requirements of District Rule 4702 as amended November 14, 2013 were incorporated into the SIP on April 25, 2016. District Rule 4702 was subsequently amended on August 19, 2021; however, ARB has not yet submitted the August 19, 2021 amendments for inclusion into the SIP. The August 19, 2021 amendments to District Rule 4702 established more stringent NO_x limits various categories of non-emergency engines, including waste gas-fueled IC engines; cyclic loaded, field gas-fueled IC engines; limited-use IC engines, lean-burn engines used for gas compression; and spark-ignited agricultural IC engines. The amendments will also remove the specific emission requirements for lean-burn, two-stroke, gaseous-fueled engines rated greater than 50 bhp and less than 100 bhp because the District does not currently have any permitted engines in this category. Any new two-stroke, gaseous-fueled engines in this category will be required to comply with the more stringent emission limits for other types of lean burn IC engines. The August 19, 2021 amendments to District Rule 4702 also reduced the VOC emission limits required for all spark-ignited IC engines that are subject to the emission requirements of the rule, made agricultural engines subject to the SO_x requirements of the rule, and added particulate matter requirements for IC engines. The amendments also will remove the current option to pay fees rather than complying with certain emission limits in the rule. The August 19, 2021 amendments did not have any effect on the requirements for low-use engines limited to no more than 200 hours per calendar year or emergency IC engines. These amendments also did not result in any substantive changes to the requirements for compression-ignition IC engines.

The only IC engines that Delicato Vineyards has permitted at this facility that are subject to the requirements of District Rule 4702 are two emergency IC engines powering firewater pumps (Units N-266-3-3 and -952-1) and one emergency standby IC engine powering an electrical generator (Unit N-266-953-1). The August 19, 2021 amendments to District Rule 4702 have no effect on the requirements for these units. The requirements of District Rule 4702 that apply to emergency IC engines are shown below.

Section 3.0 - Definitions

Section 3.15 provides the following definition for an Emergency Standby Engine:

Emergency Standby Engine: an internal combustion engine which operates as a temporary replacement for primary mechanical or electrical power during an unscheduled outage caused by sudden and reasonably unforeseen natural disasters or sudden and reasonably unforeseen events beyond the control of the operator. An engine shall be considered to be an emergency standby engine if it is used only for the following purposes: (1) periodic maintenance, periodic readiness testing, or readiness testing during and after repair work; (2) unscheduled outages, or to supply power while maintenance is performed or repairs are made to the primary power supply; and (3) if it is limited to operate 100 hours or less per calendar year for non-emergency purposes. An engine shall not be considered to be an emergency standby engine if it is used: (1) to reduce the demand for electrical power when normal electrical power line service has not failed, or (2) to produce power for the utility electrical distribution system, or (3) in conjunction with a voluntary utility demand reduction program or interruptible power contract.

Section 4.0 - Exemptions

Pursuant to Section 4.2, except for the requirements of Sections 5.10 and 6.2.3, the requirements of Rule 4702 shall not apply to an emergency standby engine or a low-use engine, provided that the engine is operated with a functional nonresettable elapsed time meter or an alternative device, method, or technique to determine operating time, provided that the alternative is approved by the APCO and EPA and is allowed by the Permit-to-Operate or Permit-Exempt Equipment Registration. The operator shall properly maintain and operate the nonresettable elapsed time meter or alternative device in accordance with the manufacturer's instructions.

Pursuant to Section 4.3.1, except for the administrative requirements of Section 6.2.3, the requirements of this rule shall not apply to an internal combustion engine that is operated exclusively to preserve or protect property, human life, or public health during a disaster or state of emergency, such as a fire or flood and except for these operations is limited to operate no more than 100 hours per calendar year for periodic maintenance, periodic readiness testing, and readiness testing during and after repair work of the engine as determined by an operational nonresettable elapsed time meter or an alternative device, method, or technique to determine operating time that is approved by the APCO and EPA. The operator of the engine shall properly maintain and operate the nonresettable elapsed time meter or alternative device in accordance with the manufacturer's instructions.

Section 5.10 - Monitoring Requirements: All Other Engines

Pursuant to Section 5.10.1, the operator of any of the following engines shall comply with the requirements specified in Section 5.10.2 through Section 5.10.5 below:

- 1) An AO spark-ignited engine subject to the requirements of Section 5.2;
- 2) A compression-ignited engine subject to the requirements of Section 5.2;
- or
- 3) An engine subject to Section 4.2.

Section 5.10.2 requires operators of engines to subject to Section 5.10 to properly operate and maintain each engine as recommended by the engine manufacturer or emission control system supplier.

Section 5.10.3 requires operators of engines to subject to Section 5.10 to monitor the operational characteristics of each engine as recommended by the engine manufacturer or emission control system supplier.

Section 5.10.4 requires the installation of a functional nonresettable elapsed time meter or use of an alternative device, method, or technique to determine operating time provided that the alternative is approved by the APCO and EPA and is allowed by a Permit-to-Operate or Permit-Exempt Equipment Registration condition. The operator shall properly maintain and operate the nonresettable elapsed time meter or alternative device in accordance with the manufacturer's instructions.

Section 5.10.5 requires all agricultural spark-ignited engines and compression-ignited engines that have been retro-fitted with a NO_x exhaust control, except certified spark-ignited engines, engines certified per Section 9.0, and certified compression-ignited engines to use a portable analyzer to take NO_x and CO emission readings and oxygen (O₂) concentration readings to demonstrate compliance with the emission requirements of Section 5.2. Section 5.10.5 does not apply to emergency standby engines or a low-use engines because they are not subject to the requirements of Section 5.2.

Section 6.2 - Recordkeeping

Section 6.2.3 requires an operator claiming an exemption under Section 4.2 or Section 4.3 shall maintain annual operating records. This information shall be retained for at least five years, shall be readily available, and provided to the APCO upon request. The records shall include, but are not limited to, the following:

- 1) Total hours of operation,
- 2) The type of fuel used,

- 3) The purpose for operating the engine,
- 4) For emergency standby engines, all hours of non-emergency and emergency operation shall be reported, and
- 5) Other support documentation necessary to demonstrate claim to the exemption.

The following conditions of the proposed requirements for the draft renewed Title V permit ensure compliance with this rule.

Permit Unit #	Permit Description	Condition #s
N-266-3-3	106 bhp Diesel Emergency Engine Powering a Firewater Pump	3, 8, and 17-19
N-266-952-1	250 bhp Diesel Emergency Engine Powering a Firewater Pump	2 and 7-10
N-266-953-1	302 bhp Natural Gas Emergency Engine Powering an Electrical Generator	3 and 8-15

G. 40 CFR Part 60 Subpart IIII - Standards of Performance for Stationary Compression Ignition Internal Combustion Engines

The purpose of 40 CFR 60 Subpart IIII is to establish New Source Performance Standards (NSPS) to reduce emissions of NO_x, SO_x, PM, CO, and VOC from new stationary compression ignition (CI) internal combustion (IC) engines.

This regulation has been amended three times since the facility's Title V permit was last amended on June 16, 2016 – on July 7, 2016 (81 FR 44219), December 4, 2020 (85 FR 78463), and June 29, 2021 (86 FR 34357).

The July 7, 2016 amendments allowed manufacturers of certified non-road engines to give operators the means to temporarily override emission control inducements during qualified emergency situations, such as those where operation of the engine is needed to protect human life. Most Tier 4 Final certified IC engines are equipped with selective catalytic reduction (SCR) systems that typically require the use of a solution of urea in water known as diesel exhaust fluid (DEF) as a reactant to reduce NO_x. These engines generally include controls that limit the function of the engines if they are operated without DEF, or if the engine's electronic control module cannot confirm that the SCR system is properly operating. The amendments aligned the NSPS with the provisions of 40 CFR 1039.665 that allow engine manufacturers to include a dormant feature in the engine's control software that could be activated to override emission control inducements for up to 120 hours per use during a qualified emergency situation. After 120 hours of cumulative operation without emission control inducements, the permission of the manufacturer and specific procedures are required to allow another 120 hours of operation with emission control inducements overridden. These

amendments did not affect the requirements for emergency IC engines in 40 CFR 60 Subpart IIII since the regulation does not require emergency engines to utilize SCR or other add-on controls. The July 7, 2016 amendments also aligned the definition of remote areas of Alaska in this NSPS with the definition used in 40 CFR part 63 Subpart ZZZZ - National Emission Standards for Hazardous Air Pollutants (NESHAP) for Stationary Reciprocating Internal Combustion Engines. The change to the definition of remote areas in Alaska had no effect on the requirements for engines outside Alaska.

EPA indicated that the purpose of the EPA action that resulted in the December 4, 2020 amendments to this NSPS was to update many of EPA's existing gasoline, diesel, and other fuel quality programs to improve overall compliance assurance and maintain environmental performance, while reducing compliance costs for industry and EPA. The EPA action removed expired provisions, eliminated redundant compliance provisions, removed unnecessary and out-of-date requirements and replaced them with a single set of provisions and definitions that applies to all gasoline, diesel, and other fuel quality programs. EPA's action and the associated amendments did not change the stringency of the fuel quality standards. The amendments to 40 CFR 60 Subpart IIII removed an outdated reference to 40 CFR 80.510 for diesel fuel requirements and replaced it with the current reference to 40 CFR 1090.305 and updated the language limiting the maximum sulfur content of diesel fuel used in compression ignition IC engines subject to this subpart with a displacement of greater than or equal to 30 liters per cylinder without changing the requirement. The December 4, 2020 amendments did not change any requirements of 40 CFR 60 Subpart IIII.

The June 29, 2021 amendments to this subpart were the result of EPA's action to remove references to outdated legacy parts for engine certification and replace them with the new regulatory parts in subchapter U (e.g. replacing reference to 40 CFR part 89 with 40 CFR part 1039), or to copy referenced text directly into 40 CFR part 60. EPA stated "*most of the changes for stationary engines in 40 CFR part 60 are intended to update references without changing standards or other provisions.*" The June 29, 2021 amendments included three more substantive changes. The first change allowed all manufacturers of emergency stationary IC engines to certify the engines using assigned deterioration factors. The second change is allow manufacturers of stationary spark-ignition IC engines to certify engines using the procedures in 40 CFR part 1054. The third change is to allow manufactures to use any of the VOC measurement methods that are specified for highway or nonroad engines in 40 CFR part 1065, subpart C. The June 29, 2021 amendments to this subpart did not affect the requirements for operators of IC engines that are subject to this regulation.

Delicato Vineyards has two compression-ignition IC engines that are permitted at this facility, Units N-266-3-3 and -952-1. However, only Unit N-266-952-1 (250 bhp firewater pump IC engine) is subject to this subpart since the N-266-3-3 was manufactured and installed before the applicable date of this subpart and has not been reconstructed. The requirements of 40 CFR 60 Subpart IIII that apply to Unit N-266-952-1 are summarized below.

§ 60.4200 Am I subject to this subpart?

Pursuant to Section 60.4200(a), the provisions of this subpart are applicable to manufacturers, owners, and operators of stationary compression ignition (CI) internal combustion engines (ICE) and other persons as specified in paragraphs (a)(1) through (4) of this section. For the purposes of this subpart, the date that construction commences is the date the engine is ordered by the owner or operator.

- 1) Manufacturers of stationary CI ICE with a displacement of less than 30 liters per cylinder where the model year is:
 - (i) 2007 or later, for engines that are not fire pump engines;
 - (ii) The model year listed in Table 3 to this subpart or later model year, for fire pump engines.
- 2) Owners and operators of stationary CI ICE that commence construction after July 11, 2005, where the stationary CI ICE are:
 - (i) Manufactured after April 1, 2006, and are not fire pump engines, or
 - (ii) Manufactured as a certified National Fire Protection Association (NFPA) fire pump engine after July 1, 2006.
- 3) Owners and operators of any stationary CI ICE that are modified or reconstructed after July 11, 2005 and any person that modifies or reconstructs any stationary CI ICE after July 11, 2005.
- 4) The provisions of Section 60.4208 of this subpart are applicable to all owners and operators of stationary CI ICE that commence construction after July 11, 2005.

§ 60.4205 What emission standards must I meet for emergency engines if I am an owner or operator of a stationary CI internal combustion engine?

(a) Owners and operators of pre-2007 model year emergency stationary CI ICE with a displacement of less than 10 liters per cylinder that are not fire pump engines must comply with the emission standards in Table 1 to this subpart. Owners and operators of pre-2007 model year emergency stationary CI ICE with a displacement of greater than or equal to 10 liters per cylinder and less

than 30 liters per cylinder that are not fire pump engines must comply with the Tier 1 emission standards in 40 CFR part 1042, appendix I.

- (b) Owners and operators of 2007 model year and later emergency stationary CI ICE with a displacement of less than 30 liters per cylinder that are not fire pump engines must comply with the emission standards for new nonroad CI engines in § 60.4202, for all pollutants, for the same model year and maximum engine power for their 2007 model year and later emergency stationary CI ICE.
- (c) Owners and operators of fire pump engines with a displacement of less than 30 liters per cylinder must comply with the emission standards in table 4 to this subpart, for all pollutants.
- (e) Owners and operators of emergency stationary CI ICE with a displacement of less than 30 liters per cylinder who conduct performance tests in-use must meet the NTE standards as indicated in § 60.4212.
- (f) Owners and operators of any modified or reconstructed emergency stationary CI ICE subject to this subpart must meet the emission standards applicable to the model year, maximum engine power, and displacement of the modified or reconstructed CI ICE that are specified in paragraphs (a) through (e) of this section.

Table 4 to Subpart IIII of Part 60 - Emission Standards for Stationary Fire Pump Engines				
[As stated in §§ 60.4202(d) and 60.4205(c), you must comply with the following emission standards for stationary fire pump engines]				
Maximum Engine Power	Model year(s)	NMHC + NO_x	CO	PM
KW<8 (HP<11)	2010 and earlier	10.5 (7.8)	8.0 (6.0)	1.0 (0.75)
	2011 +	7.5 (5.6)		0.40 (0.30)
8≤KW<19 (11≤HP<25)	2010 and earlier	9.5 (7.1)	6.6 (4.9)	0.80 (0.60)
	2011 +	7.5 (5.6)		0.40 (0.30)
19≤KW<37 (25≤HP<50)	2010 and earlier	9.5 (7.1)	5.5 (4.1)	0.80 (0.60)
	2011 +	7.5 (5.6)		0.30 (0.22)
37≤KW<56 (50≤HP<75)	2010 and earlier	10.5 (7.8)	5.0 (3.7)	0.80 (0.60)
	2011 + ¹	4.7 (3.5)		0.40 (0.30)
56≤KW<75 (75≤HP<100)	2010 and earlier	10.5 (7.8)	5.0 (3.7)	0.80 (0.60)
	2011 + ¹	4.7 (3.5)		0.40 (0.30)
75≤KW<130 (100≤HP<175)	2009 and earlier	10.5 (7.8)	5.0 (3.7)	0.80 (0.60)
	2010 + ²	4.0 (3.0)		0.30 (0.22)
130≤KW<225 (175≤HP<300)	2008 and earlier	10.5 (7.8)	3.5 (2.6)	0.54 (0.40)
	2009 + ³	4.0 (3.0)		0.20 (0.15)
225≤KW<450 (300≤HP<600)	2008 and earlier	10.5 (7.8)	3.5 (2.6)	0.54 (0.40)
	2009 + ³	4.0 (3.0)		0.20 (0.15)
450≤KW≤560 (600≤HP≤750)	2008 and earlier	10.5 (7.8)	3.5 (2.6)	0.54 (0.40)
	2009 +	4.0 (3.0)		0.20 (0.15)

Table 4 to Subpart IIII of Part 60 - Emission Standards for Stationary Fire Pump Engines				
[As stated in §§ 60.4202(d) and 60.4205(c), you must comply with the following emission standards for stationary fire pump engines]				
Maximum Engine Power	Model year(s)	NMHC + NO_x	CO	PM
KW>560 (HP>750)	2007 and earlier	10.5 (7.8)	3.5 (2.6)	0.54 (0.40)
	2008 +	6.4 (4.8)		0.20 (0.15)

- ¹ For model years 2011-2013, manufacturers, owners and operators of fire pump stationary CI ICE in this engine power category with a rated speed of greater than 2,650 revolutions per minute (rpm) may comply with the emission limitations for 2010 model year engines.
- ² For model years 2010-2012, manufacturers, owners and operators of fire pump stationary CI ICE in this engine power category with a rated speed of greater than 2,650 rpm may comply with the emission limitations for 2009 model year engines.
- ³ In model years 2009-2011, manufacturers of fire pump stationary CI ICE in this engine power category with a rated speed of greater than 2,650 rpm may comply with the emission limitations for 2008 model year engines.

§ 60.4206 How long must I meet the emission standards if I am an owner or operator of a stationary CI internal combustion engine?

Owners and operators of stationary CI ICE must operate and maintain stationary CI ICE that achieve the emission standards as required in Sections 60.4204 and 60.4205 over the entire life of the engine.

§ 60.4207 What fuel requirements must I meet if I am an owner or operator of a stationary CI internal combustion engine subject to this subpart?

- (a) [Reserved]
- (b) Beginning October 1, 2010, owners and operators of stationary CI ICE subject to this subpart with a displacement of less than 30 liters per cylinder that use diesel fuel must use diesel fuel that meets the requirements of 40 CFR 1090.305 for nonroad diesel fuel, except that any existing diesel fuel purchased (or otherwise obtained) prior to October 1, 2010, may be used until depleted.
- (c) [Reserved]
- (d) Beginning June 1, 2012, owners and operators of stationary CI ICE subject to this subpart with a displacement of greater than or equal to 30 liters per cylinder must use diesel fuel that meets a maximum per-gallon sulfur content of 1,000 parts per million (ppm).
- (e) Stationary CI ICE that have a national security exemption under § 60.4200(d) are also exempt from the fuel requirements in this section.

§ 60.4209 What are the monitoring requirements if I am an owner or operator of a stationary CI internal combustion engine?

If you are an owner or operator, you must meet the monitoring requirements of this section. In addition, you must also meet the monitoring requirements specified in § 60.4211.

- (a) If you are an owner or operator of an emergency stationary CI internal combustion engine that does not meet the standards applicable to non-emergency engines, you must install a non-resettable hour meter prior to startup of the engine.

§ 60.4211 What are my compliance requirements if I am an owner or operator of a stationary CI internal combustion engine?

- (a) If you are an owner or operator and must comply with the emission standards specified in this subpart, you must do all of the following, except as permitted under paragraph (g) of this section:
 - (1) Operate and maintain the stationary CI internal combustion engine and control device according to the manufacturer's emission-related written instructions;
 - (2) Change only those emission-related settings that are permitted by the manufacturer; and
 - (3) Meet the requirements of 40 CFR part 1068, as they apply to you.
- (c) If you are an owner or operator of a 2007 model year and later stationary CI internal combustion engine and must comply with the emission standards specified in § 60.4204(b) or § 60.4205(b), or if you are an owner or operator of a CI fire pump engine that is manufactured during or after the model year that applies to your fire pump engine power rating in table 3 to this subpart and must comply with the emission standards specified in § 60.4205(c), you must comply by purchasing an engine certified to the emission standards in § 60.4204(b), or § 60.4205(b) or (c), as applicable, for the same model year and maximum (or in the case of fire pumps, NFPA nameplate) engine power. The engine must be installed and configured according to the manufacturer's emission-related specifications, except as permitted in paragraph (g) of this section.
- (f) If you own or operate an emergency stationary ICE, you must operate the emergency stationary ICE according to the requirements in paragraphs (f)(1) through (3) of this section. In order for the engine to be considered an emergency stationary ICE under this subpart, any operation other than emergency operation, maintenance and testing, emergency demand response, and operation in non-emergency situations for 50 hours per year, as described in paragraphs (f)(1) through (3) of this section, is prohibited. If

you do not operate the engine according to the requirements in paragraphs (f)(1) through (3) of this section, the engine will not be considered an emergency engine under this subpart and must meet all requirements for non-emergency engines.

- (1) There is no time limit on the use of emergency stationary ICE in emergency situations.
- (2) You may operate your emergency stationary ICE for any combination of the purposes specified in paragraphs (f)(2)(i) through (iii) of this section for a maximum of 100 hours per calendar year. Any operation for non-emergency situations as allowed by paragraph (f)(3) of this section counts as part of the 100 hours per calendar year allowed by this paragraph (f)(2).
 - (i) Emergency stationary ICE may be operated for maintenance checks and readiness testing, provided that the tests are recommended by federal, state or local government, the manufacturer, the vendor, the regional transmission organization or equivalent balancing authority and transmission operator, or the insurance company associated with the engine. The owner or operator may petition the Administrator for approval of additional hours to be used for maintenance checks and readiness testing, but a petition is not required if the owner or operator maintains records indicating that federal, state, or local standards require maintenance and testing of emergency ICE beyond 100 hours per calendar year.
 - (ii) Emergency stationary ICE may be operated for emergency demand response for periods in which the Reliability Coordinator under the North American Electric Reliability Corporation (NERC) Reliability Standard EOP-002-3, Capacity and Energy Emergencies (incorporated by reference, see § 60.17), or other authorized entity as determined by the Reliability Coordinator, has declared an Energy Emergency Alert Level 2 as defined in the NERC Reliability Standard EOP-002-3.
 - (iii) Emergency stationary ICE may be operated for periods where there is a deviation of voltage or frequency of 5 percent or greater below standard voltage or frequency.
- (3) Emergency stationary ICE may be operated for up to 50 hours per calendar year in non-emergency situations. The 50 hours of operation in non-emergency situations are counted as part of the 100 hours per calendar year for maintenance and testing and emergency demand response provided in paragraph (f)(2) of this section. Except as provided in paragraph (f)(3)(i) of this section, the 50 hours per calendar year for non-emergency situations cannot be used for peak shaving or non-emergency demand response, or to generate income for a facility to an

electric grid or otherwise supply power as part of a financial arrangement with another entity.

- (g) If you do not install, configure, operate, and maintain your engine and control device according to the manufacturer's emission-related written instructions, or you change emission-related settings in a way that is not permitted by the manufacturer, you must demonstrate compliance as follows:
- (1) If you are an owner or operator of a stationary CI internal combustion engine with maximum engine power less than 100 HP, you must keep a maintenance plan and records of conducted maintenance to demonstrate compliance and must, to the extent practicable, maintain and operate the engine in a manner consistent with good air pollution control practice for minimizing emissions. In addition, if you do not install and configure the engine and control device according to the manufacturer's emission-related written instructions, or you change the emission-related settings in a way that is not permitted by the manufacturer, you must conduct an initial performance test to demonstrate compliance with the applicable emission standards within 1 year of such action.
 - (2) If you are an owner or operator of a stationary CI internal combustion engine greater than or equal to 100 HP and less than or equal to 500 HP, you must keep a maintenance plan and records of conducted maintenance and must, to the extent practicable, maintain and operate the engine in a manner consistent with good air pollution control practice for minimizing emissions. In addition, you must conduct an initial performance test to demonstrate compliance with the applicable emission standards within 1 year of startup, or within 1 year after an engine and control device is no longer installed, configured, operated, and maintained in accordance with the manufacturer's emission-related written instructions, or within 1 year after you change emission-related settings in a way that is not permitted by the manufacturer.
 - (3) If you are an owner or operator of a stationary CI internal combustion engine greater than 500 HP, you must keep a maintenance plan and records of conducted maintenance and must, to the extent practicable, maintain and operate the engine in a manner consistent with good air pollution control practice for minimizing emissions. In addition, you must conduct an initial performance test to demonstrate compliance with the applicable emission standards within 1 year of startup, or within 1 year after an engine and control device is no longer installed, configured, operated, and maintained in accordance with the manufacturer's emission-related written instructions, or within 1 year after you change

emission-related settings in a way that is not permitted by the manufacturer. You must conduct subsequent performance testing every 8,760 hours of engine operation or 3 years, whichever comes first, thereafter to demonstrate compliance with the applicable emission standards.

- (h) The requirements for operators and prohibited acts specified in 40 CFR 1039.665 apply to owners or operators of stationary CI ICE equipped with AECDs for qualified emergency situations as allowed by 40 CFR 1039.665.

§ 60.4214 What are my notification, reporting, and recordkeeping requirements if I am an owner or operator of a stationary CI internal combustion engine?

- (b) If the stationary CI internal combustion engine is an emergency stationary internal combustion engine, the owner or operator is not required to submit an initial notification. Starting with the model years in table 5 to this subpart, if the emergency engine does not meet the standards applicable to non-emergency engines in the applicable model year, the owner or operator must keep records of the operation of the engine in emergency and non-emergency service that are recorded through the non-resettable hour meter. The owner must record the time of operation of the engine and the reason the engine was in operation during that time.

- a. N-266-3-3: 106 BHP DEUTZ MODEL NDC-BF4 M1013ES DIESEL-FIRED EMERGENCY IC ENGINE POWERING A FIREWATER PUMP

As discussed above, this unit is not subject to the requirements of 40 CFR 60 Subpart since it was manufactured and installed before the applicable date of this subpart and has not been reconstructed.

- b. N-266-952-1: 250 BHP (INTERMITTENT) JOHN DEERE MODEL 6068HFC48 TIER 3 CERTIFIED DIESEL-FIRED EMERGENCY IC ENGINE POWERING A FIREWATER PUMP

The following conditions of the proposed requirements of the draft renewed Title V permit ensure compliance with this regulation.

Permit Unit #	Permit Description	Condition #s
N-266-952-1	250 bhp Diesel Emergency Engine Powering a Firewater Pump	2-10

H. 40 CFR Part 60 Subpart JJJJ - Standards of Performance for Stationary Spark Ignition Internal Combustion Engines

The purpose of 40 CFR 60 Subpart JJJJ is to establish New Source Performance Standards (NSPS) to reduce emissions of NO_x, CO, and VOC from new stationary spark ignition (SI) IC engines.

This regulation has been amended three times since the facility's Title V permit was last amended on June 16, 2016 – on August 30, 2016 (81 FR 59809), December 4, 2020 (85 FR 78463), and June 29, 2021 (86 FR 34360).

EPA stated that the August 30, 2016 amendments incorporated technical and editorial corrections and revisions to regulations related to source testing of emissions, made corrections and updates to testing provisions, and added approved alternatives to existing testing regulations. The amendments did not impose any new substantive requirements on source owners or operators. The amendments to 40 CFR 60 Subpart JJJJ added language requiring the reporting of specific QA/QC data when approved Fourier Transform Infrared Spectroscopy (FTIR) VOC test methods are used and replaced the term “methane cutter” with “hydrocarbon cutter”. The August 30, 2016 amendments did not change any requirements of 40 CFR 60 Subpart JJJJ except adding the requirement to report specific QA/QC data for FTIR VOC test methods.

EPA indicated that the purpose of the EPA action that resulted in the December 4, 2020 amendments to this NSPS was to update many of EPA's existing gasoline, diesel, and other fuel quality programs to improve overall compliance assurance and maintain environmental performance, while reducing compliance costs for industry and EPA. The EPA action removed expired provisions, eliminated redundant compliance provisions, removed unnecessary and out-of-date requirements and replaced them with a single set of provisions and definitions that applies to all gasoline, diesel, and other fuel quality programs. EPA's action and the associated amendments did not change the stringency of the fuel quality standards. The amendments to 40 CFR 60 Subpart JJJJ removed an outdated reference to 40 CFR 80.195 for gasoline fuel requirements and replaced it with the current reference to 40 CFR 1090.205. The December 4, 2020 amendments did not change any requirements of 40 CFR 60 Subpart JJJJ.

The June 29, 2021 amendments to this subpart were the result of EPA's action to remove references to outdated legacy parts for engine certification and replace them with the new regulatory parts in subchapter U (e.g. replacing reference to 40 CFR part 90 with 40 CFR part 1054), or to copy referenced text directly into 40 CFR part 60. EPA stated “*most of the changes for stationary engines in 40 CFR part 60 are intended to update references without changing standards or other provisions.*” The June 29, 2021 amendments included three

more substantive changes. The first change allowed all manufacturers of emergency stationary IC engines to certify the engines using assigned deterioration factors. The second change is allow manufacturers of stationary spark-ignition IC engines to certify engines using the procedures in 40 CFR part 1054. The third change is to allow manufactures to use any of the VOC measurement methods that are specified for highway or nonroad engines in 40 CFR part 1065, subpart C. The June 29, 2021 amendments to this subpart did not affect the requirements for operators of IC engines that are subject to this regulation.

Delicato Vineyards has one natural gas-fired spark-ignition IC engine that is permitted at this facility, Unit N-266-953-1. The requirements of 40 CFR 60 Subpart JJJJ that apply to Unit N-266-953-1 are summarized below.

§ 60.4230 Am I subject to this subpart?

- (a) The provisions of this subpart are applicable to manufacturers, owners, and operators of stationary spark ignition (SI) internal combustion engines (ICE) as specified in paragraphs (a)(1) through (6) of this section. For the purposes of this subpart, the date that construction commences is the date the engine is ordered by the owner or operator.
- (1) Manufacturers of stationary SI ICE with a maximum engine power less than or equal to 19 kilowatt (KW) (25 horsepower (HP)) that are manufactured on or after July 1, 2008.
- (2) Manufacturers of stationary SI ICE with a maximum engine power greater than 19 KW (25 HP) that are gasoline fueled or that are rich burn engines fueled by liquefied petroleum gas (LPG), where the date of manufacture is:
- (i) On or after July 1, 2008; or
- (ii) On or after January 1, 2009, for emergency engines.
- (3) Manufacturers of stationary SI ICE with a maximum engine power greater than 19 KW (25 HP) that are not gasoline fueled and are not rich burn engines fueled by LPG, where the manufacturer participates in the voluntary manufacturer certification program described in this subpart and where the date of manufacture is:
- (i) On or after July 1, 2007, for engines with a maximum engine power greater than or equal to 500 HP (except lean burn engines with a maximum engine power greater than or equal to 500 HP and less than 1,350 HP);
- (ii) On or after January 1, 2008, for lean burn engines with a maximum engine power greater than or equal to 500 HP and less than 1,350 HP;

- (iii) On or after July 1, 2008, for engines with a maximum engine power less than 500 HP; or
 - (iv) On or after January 1, 2009, for emergency engines.
- (4) Owners and operators of stationary SI ICE that commence construction after June 12, 2006, where the stationary SI ICE are manufactured:
- (i) On or after July 1, 2007, for engines with a maximum engine power greater than or equal to 500 HP (except lean burn engines with a maximum engine power greater than or equal to 500 HP and less than 1,350 HP);
 - (ii) on or after January 1, 2008, for lean burn engines with a maximum engine power greater than or equal to 500 HP and less than 1,350 HP;
 - (iii) on or after July 1, 2008, for engines with a maximum engine power less than 500 HP; or
 - (iv) on or after January 1, 2009, for emergency engines with a maximum engine power greater than 19 KW (25 HP).
- (5) Owners and operators of stationary SI ICE that are modified or reconstructed after June 12, 2006, and any person that modifies or reconstructs any stationary SI ICE after June 12, 2006.
- (6) The provisions of § 60.4236 of this subpart are applicable to all owners and operators of stationary SI ICE that commence construction after June 12, 2006.

§ 60.4233 What emission standards must I meet if I am an owner or operator of a stationary SI internal combustion engine?

- (e) Owners and operators of stationary SI ICE with a maximum engine power greater than or equal to 75 KW (100 HP) (except gasoline and rich burn engines that use LPG) must comply with the emission standards in Table 1 to this subpart for their stationary SI ICE. For owners and operators of stationary SI ICE with a maximum engine power greater than or equal to 100 HP (except gasoline and rich burn engines that use LPG) manufactured prior to January 1, 2011 that were certified to the certification emission standards in 40 CFR part 1048 applicable to engines that are not severe duty engines, if such stationary SI ICE was certified to a carbon monoxide (CO) standard above the standard in Table 1 to this subpart, then the owners and operators may meet the CO certification (not field testing) standard for which the engine was certified.

Table 1 to Subpart JJJJ of Part 60 - NO_x, CO, and VOC Emission Standards for Stationary Non-Emergency SI Engines ≥100 HP (Except Gasoline and Rich Burn LPG), Stationary SI Landfill/Digester Gas Engines, and Stationary Emergency Engines >25 HP								
Engine type and fuel	Maximum engine power	Manufacture date	Emission standards ^a					
			g/HP-hr			ppmvd at 15% O ₂		
			NO _x	CO	VOC ^d	NO _x	CO	VOC ^d
Non-Emergency SI Natural Gas ^b and Non-Emergency SI Lean Burn LPG ^b	100≤HP<500	7/1/2008	2.0	4.0	1.0	160	540	86
		1/1/2011	1.0	2.0	0.7	82	270	60
Non-Emergency SI Lean Burn Natural Gas and LPG	500≤HP<1,350	1/1/2008	2.0	4.0	1.0	160	540	86
		7/1/2010	1.0	2.0	0.7	82	270	60
Non-Emergency SI Natural Gas and Non-Emergency SI Lean Burn LPG (except lean burn 500≤HP<1,350)	HP≥500	7/1/2007	2.0	4.0	1.0	160	540	86
	HP≥500	7/1/2010	1.0	2.0	0.7	82	270	60
Landfill/Digester Gas (except lean burn 500≤HP<1,350)	HP<500	7/1/2008	3.0	5.0	1.0	220	610	80
		1/1/2011	2.0	5.0	1.0	150	610	80
	HP≥500	7/1/2007	3.0	5.0	1.0	220	610	80
		7/1/2010	2.0	5.0	1.0	150	610	80
Landfill/Digester Gas Lean Burn Emergency	500≤HP<1,350	1/1/2008	3.0	5.0	1.0	220	610	80
		7/1/2010	2.0	5.0	1.0	150	610	80
	25<HP<130	1/1/2009	^c 10	387	N/A	N/A	N/A	N/A
			HP≥130	2.0	4.0	1.0	160	540

^a Owners and operators of stationary non-certified SI engines may choose to comply with the emission standards in units of either g/HP-hr or ppmvd at 15 percent O₂.

^b Owners and operators of new or reconstructed non-emergency lean burn SI stationary engines with a site rating of greater than or equal to 250 brake HP located at a major source that are meeting the requirements of 40 CFR part 63, subpart ZZZZ, Table 2a do not have to comply with the CO emission standards of Table 1 of this subpart.

^c The emission standards applicable to emergency engines between 25 HP and 130 HP are in terms of NO_x + HC.

^d For purposes of this subpart, when calculating emissions of volatile organic compounds, emissions of formaldehyde should not be included.

§ 60.4234 How long must I meet the emission standards if I am an owner or operator of a stationary SI internal combustion engine?

Owners and operators of stationary SI ICE must operate and maintain stationary SI ICE that achieve the emission standards as required in § 60.4233 over the entire life of the engine.

§ 60.4237 What are the monitoring requirements if I am an owner or operator of an emergency stationary SI internal combustion engine?

(a) Starting on July 1, 2010, if the emergency stationary SI internal combustion engine that is greater than or equal to 500 HP that was built on or after July 1, 2010, does not meet the standards applicable to non-emergency engines, the owner or operator must install a non-resettable hour meter.

(b) Starting on January 1, 2011, if the emergency stationary SI internal combustion engine that is greater than or equal to 130 HP and less than

500 HP that was built on or after January 1, 2011, does not meet the standards applicable to non-emergency engines, the owner or operator must install a non-resettable hour meter.

- (c) If you are an owner or operator of an emergency stationary SI internal combustion engine that is less than 130 HP, was built on or after July 1, 2008, and does not meet the standards applicable to non-emergency engines, you must install a non-resettable hour meter upon startup of your emergency engine.

§ 60.4243 What are my compliance requirements if I am an owner or operator of a stationary SI internal combustion engine?

- (a) If you are an owner or operator of a stationary SI internal combustion engine that is manufactured after July 1, 2008, and must comply with the emission standards specified in § 60.4233(a) through (c), you must comply by purchasing an engine certified to the emission standards in § 60.4231(a) through (c), as applicable, for the same engine class and maximum engine power. In addition, you must meet one of the requirements specified in (a)(1) and (2) of this section.

- (1) If you operate and maintain the certified stationary SI internal combustion engine and control device according to the manufacturer's emission-related written instructions, you must keep records of conducted maintenance to demonstrate compliance, but no performance testing is required if you are an owner or operator. You must also meet the requirements as specified in 40 CFR part 1068, subparts A through D, as they apply to you. If you adjust engine settings according to and consistent with the manufacturer's instructions, your stationary SI internal combustion engine will not be considered out of compliance.

- (2) If you do not operate and maintain the certified stationary SI internal combustion engine and control device according to the manufacturer's emission-related written instructions, your engine will be considered a non-certified engine, and you must demonstrate compliance according to (a)(2)(i) through (iii) of this section, as appropriate.

- (i) If you are an owner or operator of a stationary SI internal combustion engine less than 100 HP, you must keep a maintenance plan and records of conducted maintenance to demonstrate compliance and must, to the extent practicable, maintain and operate the engine in a manner consistent with good air pollution control practice for minimizing emissions, but no performance testing is required if you are an owner or operator.

- (ii) If you are an owner or operator of a stationary SI internal combustion engine greater than or equal to 100 HP and less than or equal to 500 HP, you must keep a maintenance plan and records of conducted maintenance and must, to the extent practicable, maintain and operate the engine in a manner consistent with good air pollution control practice for minimizing emissions. In addition, you must conduct an initial performance test within 1 year of engine startup to demonstrate compliance.
 - (iii) If you are an owner or operator of a stationary SI internal combustion engine greater than 500 HP, you must keep a maintenance plan and records of conducted maintenance and must, to the extent practicable, maintain and operate the engine in a manner consistent with good air pollution control practice for minimizing emissions. In addition, you must conduct an initial performance test within 1 year of engine startup and conduct subsequent performance testing every 8,760 hours or 3 years, whichever comes first, thereafter to demonstrate compliance.
- (b) If you are an owner or operator of a stationary SI internal combustion engine and must comply with the emission standards specified in § 60.4233(d) or (e), you must demonstrate compliance according to one of the methods specified in paragraphs (b)(1) and (2) of this section.
 - (1) Purchasing an engine certified according to procedures specified in this subpart, for the same model year and demonstrating compliance according to one of the methods specified in paragraph (a) of this section.
 - (2) Purchasing a non-certified engine and demonstrating compliance with the emission standards specified in § 60.4233(d) or (e) and according to the requirements specified in § 60.4244, as applicable, and according to paragraphs (b)(2)(i) and (ii) of this section.
- (d) If you own or operate an emergency stationary ICE, you must operate the emergency stationary ICE according to the requirements in paragraphs (d)(1) through (3) of this section. In order for the engine to be considered an emergency stationary ICE under this subpart, any operation other than emergency operation, maintenance and testing, emergency demand response, and operation in non-emergency situations for 50 hours per year, as described in paragraphs (d)(1) through (3) of this section, is prohibited. If you do not operate the engine according to the requirements in paragraphs (d)(1) through (3) of this section, the engine will not be considered an emergency engine under this subpart and must meet all requirements for non-emergency engines.

- (1) There is no time limit on the use of emergency stationary ICE in emergency situations.
- (2) You may operate your emergency stationary ICE for any combination of the purposes specified in paragraphs (d)(2)(i) through (iii) of this section for a maximum of 100 hours per calendar year. Any operation for non-emergency situations as allowed by paragraph (d)(3) of this section counts as part of the 100 hours per calendar year allowed by this paragraph (d)(2).
 - (i) Emergency stationary ICE may be operated for maintenance checks and readiness testing, provided that the tests are recommended by federal, state or local government, the manufacturer, the vendor, the regional transmission organization or equivalent balancing authority and transmission operator, or the insurance company associated with the engine. The owner or operator may petition the Administrator for approval of additional hours to be used for maintenance checks and readiness testing, but a petition is not required if the owner or operator maintains records indicating that federal, state, or local standards require maintenance and testing of emergency ICE beyond 100 hours per calendar year.
 - (ii) Emergency stationary ICE may be operated for emergency demand response for periods in which the Reliability Coordinator under the North American Electric Reliability Corporation (NERC) Reliability Standard EOP-002-3, Capacity and Energy Emergencies (incorporated by reference, see § 60.17), or other authorized entity as determined by the Reliability Coordinator, has declared an Energy Emergency Alert Level 2 as defined in the NERC Reliability Standard EOP-002-3.
 - (iii) Emergency stationary ICE may be operated for periods where there is a deviation of voltage or frequency of 5 percent or greater below standard voltage or frequency.
- (3) Emergency stationary ICE may be operated for up to 50 hours per calendar year in non-emergency situations. The 50 hours of operation in non-emergency situations are counted as part of the 100 hours per calendar year for maintenance and testing and emergency demand response provided in paragraph (d)(2) of this section. Except as provided in paragraph (d)(3)(i) of this section, the 50 hours per year for non-emergency situations cannot be used for peak shaving or non-emergency demand response, or to generate income for a facility to an electric grid or otherwise supply power as part of a financial arrangement with another entity.
- (e) Owners and operators of stationary SI natural gas fired engines may operate their engines using propane for a maximum of 100 hours per year

as an alternative fuel solely during emergency operations, but must keep records of such use. If propane is used for more than 100 hours per year in an engine that is not certified to the emission standards when using propane, the owners and operators are required to conduct a performance test to demonstrate compliance with the emission standards of § 60.4233.

- (f) If you are an owner or operator of a stationary SI internal combustion engine that is less than or equal to 500 HP and you purchase a non-certified engine or you do not operate and maintain your certified stationary SI internal combustion engine and control device according to the manufacturer's written emission-related instructions, you are required to perform initial performance testing as indicated in this section, but you are not required to conduct subsequent performance testing unless the stationary engine undergoes rebuild, major repair or maintenance. Engine rebuilding means to overhaul an engine or to otherwise perform extensive service on the engine (or on a portion of the engine or engine system). For the purpose of this paragraph (f), perform extensive service means to disassemble the engine (or portion of the engine or engine system), inspect and/or replace many of the parts, and reassemble the engine (or portion of the engine or engine system) in such a manner that significantly increases the service life of the resultant engine.
- (g) It is expected that air-to-fuel ratio controllers will be used with the operation of three-way catalysts/non-selective catalytic reduction. The AFR controller must be maintained and operated appropriately in order to ensure proper operation of the engine and control device to minimize emissions at all times.

§ 60.4245 What are my notification, reporting, and recordkeeping requirements if I am an owner or operator of a stationary SI internal combustion engine?

Owners or operators of stationary SI ICE must meet the following notification, reporting and recordkeeping requirements.

- (a) Owners and operators of all stationary SI ICE must keep records of the information in paragraphs (a)(1) through (4) of this section.
 - (1) All notifications submitted to comply with this subpart and all documentation supporting any notification.
 - (2) Maintenance conducted on the engine.
 - (3) If the stationary SI internal combustion engine is a certified engine, documentation from the manufacturer that the engine is certified to meet

the emission standards and information as required in 40 CFR parts 1048, 1054, and 1060, as applicable.

- (4) If the stationary SI internal combustion engine is not a certified engine or is a certified engine operating in a non-certified manner and subject to § 60.4243(a)(2), documentation that the engine meets the emission standards.

- (b) For all stationary SI emergency ICE greater than or equal to 500 HP manufactured on or after July 1, 2010, that do not meet the standards applicable to non-emergency engines, the owner or operator of must keep records of the hours of operation of the engine that is recorded through the non-resettable hour meter. For all stationary SI emergency ICE greater than or equal to 130 HP and less than 500 HP manufactured on or after July 1, 2011 that do not meet the standards applicable to non-emergency engines, the owner or operator of must keep records of the hours of operation of the engine that is recorded through the non-resettable hour meter. For all stationary SI emergency ICE greater than 25 HP and less than 130 HP manufactured on or after July 1, 2008, that do not meet the standards applicable to non-emergency engines, the owner or operator of must keep records of the hours of operation of the engine that is recorded through the non-resettable hour meter. The owner or operator must document how many hours are spent for emergency operation, including what classified the operation as emergency and how many hours are spent for non-emergency operation.

The following conditions of the proposed requirements for the draft renewed Title V permit for Unit N-266-953-1 ensure compliance with these requirements.

Permit Unit #	Permit Description	Condition #s
N-266-953-1	302 bhp Natural Gas Emergency Engine Powering an Electrical Generator	3-5, 8, 10, 13 and 15

I. 40 CFR 63, Subpart ZZZZ – National Emissions Standards for Hazardous Air Pollutants for Stationary Reciprocating Internal Combustion Engines

40 CFR 63 Subpart ZZZZ establishes national emission limitations and operating limitations for hazardous air pollutants (HAP) emitted from stationary reciprocating internal combustion engines (RICE) located at major and area sources of HAP emissions.

This regulation has been amended twice since the facility’s Title V permit was last amended on June 16, 2016 – on November 19, 2020 (85 FR 73912) and December 4, 2020 (85 FR 78463).

EPA stated that the November 19, 2020 amendments implemented the plain language reading of the “major source” and “area source” definitions of section 112 of the Clean Air Act (CAA) and allowed that a major source can be reclassified to area source status at any time upon reducing its potential to emit (PTE) hazardous air pollutants (HAP) to below the major source thresholds (MST) of 10 tons per year (tpy) of any single HAP and 25 tpy of any combination of HAPs. The amendments also clarified the compliance dates, notification, and recordkeeping requirements that apply to sources choosing to reclassify to area source status and to sources that revert back to major source status, including a requirement for electronic notification and reporting.

EPA indicated that the purpose of the EPA action that resulted in the December 4, 2020 amendments to this NESHAP was to update many of EPA's existing gasoline, diesel, and other fuel quality programs to improve overall compliance assurance and maintain environmental performance, while reducing compliance costs for industry and EPA. The EPA action removed expired provisions, eliminated redundant compliance provisions, removed unnecessary and out-of-date requirements and replaced them with a single set of provisions and definitions that applies to all gasoline, diesel, and other fuel quality programs. EPA's action and the associated amendments did not change the stringency of the fuel quality standards. The amendments to 40 CFR 63 Subpart ZZZZ removed an outdated reference to 40 CFR 80.510 for diesel fuel requirements and replaced it with the current reference to 40 CFR 1090.305. The December 4, 2020 amendments did not change any requirements of 40 CFR 63 Subpart ZZZZ.

Delicato Vineyards has two emergency IC engines powering firewater pumps, Units N-266-3-3 and -952-1, and one emergency standby IC engine powering an electrical generator, Unit N-266-953-1, permitted at this facility. As discussed above, Units N-266-952-1 and -953-1 are subject to 40 CFR 60 subpart IIII and 40 CFR 60 subpart JJJJ, respectively. Pursuant to Section 63.6590 (c), these IC engines satisfy the requirements of this subpart by meeting the requirements of 40 CFR part 60 subpart IIII, for compression ignition engines or 40 CFR part 60 subpart JJJJ, for spark ignition engines and no further requirements apply for to the engines under this part. Therefore, only Unit N-266-3-3 is subject to the requirements of this regulation. The November 19, 2020 and December 4, 2020 amendments to 40 CFR 63 Subpart ZZZZ did not result in any changes in requirements for Unit N-266-3-3. The requirements of 40 CFR 63 Subpart ZZZZ that apply to Unit N-266-3-3 are summarized below.

Section 63.6580 Purpose

40 CFR 63 Subpart ZZZZ establishes national emission limitations and operating limitations for hazardous air pollutants (HAP) emitted from stationary

reciprocating internal combustion engines (RICE) located at major and area sources of HAP emissions. This subpart also establishes requirements to demonstrate initial and continuous compliance with the emission limitations and operating limitations.

Section 63.6585 Am I subject to this subpart?

This subpart applies to owners and operators of stationary RICE at a major or area source of HAP emissions, except if the stationary RICE is being tested at a stationary RICE test cell/stand.

Pursuant to Section 63.6585(f), the emergency stationary RICE listed in paragraphs (f)(1) through (3) of this section are not subject to this subpart. The stationary RICE must meet the definition of an emergency stationary RICE in Section 63.6675, which includes operating according to the provisions specified in Section 63.6640(f).

- (1) Existing residential emergency stationary RICE located at an area source of HAP emissions that do not operate or are not contractually obligated to be available for more than 15 hours per calendar year for the purposes specified in Section 63.6640(f)(2)(ii) and (iii) and that do not operate for the purpose specified in Section 63.6640(f)(4)(ii).
- (2) Existing commercial emergency stationary RICE located at an area source of HAP emissions that do not operate or are not contractually obligated to be available for more than 15 hours per calendar year for the purposes specified in Section 63.6640(f)(2)(ii) and (iii) and that do not operate for the purpose specified in Section 63.6640(f)(4)(ii).
- (3) Existing institutional emergency stationary RICE located at an area source of HAP emissions that do not operate or are not contractually obligated to be available for more than 15 hours per calendar year for the purposes specified in Section 63.6640(f)(2)(ii) and (iii) and that do not operate for the purpose specified in Section 63.6640(f)(4)(ii).

§ 63.6590 What parts of my plant does this subpart cover?

This subpart applies to each affected source.

- (a) **Affected source.** An affected source is any existing, new, or reconstructed stationary RICE located at a major or area source of HAP emissions, excluding stationary RICE being tested at a stationary RICE test cell/stand.

(1) **Existing stationary RICE.**

- (i) For stationary RICE with a site rating of more than 500 brake horsepower (HP) located at a major source of HAP emissions, a stationary RICE is existing if you commenced construction or reconstruction of the stationary RICE before December 19, 2002.
- (ii) For stationary RICE with a site rating of less than or equal to 500 brake HP located at a major source of HAP emissions, a stationary RICE is existing if you commenced construction or reconstruction of the stationary RICE before June 12, 2006.
- (iii) For stationary RICE located at an area source of HAP emissions, a stationary RICE is existing if you commenced construction or reconstruction of the stationary RICE before June 12, 2006.
- (iv) A change in ownership of an existing stationary RICE does not make that stationary RICE a new or reconstructed stationary RICE.

(2) **New stationary RICE.**

- (i) A stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions is new if you commenced construction of the stationary RICE on or after December 19, 2002.
- (ii) A stationary RICE with a site rating of equal to or less than 500 brake HP located at a major source of HAP emissions is new if you commenced construction of the stationary RICE on or after June 12, 2006.
- (iii) A stationary RICE located at an area source of HAP emissions is new if you commenced construction of the stationary RICE on or after June 12, 2006.

This facility is an area source of HAP emissions because nearly all VOC emissions from the winery are ethanol, which is not a HAP.

Unit N-266-3-3 is an existing stationary RICE as defined in this subpart because construction or reconstruction commenced for the engine before June 12, 2006.

Units N-266-952-1 and -953-1 are new stationary RICEs as defined in this subpart because construction or reconstruction commenced for the engine on or after June 12, 2006.

(c) **Stationary RICE subject to Regulations under 40 CFR Part 60.**

An affected source that meets any of the criteria in paragraphs (c)(1) through (7) of this section must meet the requirements of this part by meeting the requirements of 40 CFR part 60 subpart IIII, for compression ignition engines

or 40 CFR part 60 subpart JJJJ, for spark ignition engines. No further requirements apply for such engines under this part.

- (1) A new or reconstructed stationary RICE located at an area source;
- (2) A new or reconstructed 2SLB stationary RICE with a site rating of less than or equal to 500 brake HP located at a major source of HAP emissions;
- (3) A new or reconstructed 4SLB stationary RICE with a site rating of less than 250 brake HP located at a major source of HAP emissions;
- (4) A new or reconstructed spark ignition 4 stroke rich burn (4SRB) stationary RICE with a site rating of less than or equal to 500 brake HP located at a major source of HAP emissions;
- (5) A new or reconstructed stationary RICE with a site rating of less than or equal to 500 brake HP located at a major source of HAP emissions which combusts landfill or digester gas equivalent to 10 percent or more of the gross heat input on an annual basis;
- (6) A new or reconstructed emergency or limited use stationary RICE with a site rating of less than or equal to 500 brake HP located at a major source of HAP emissions;
- (7) A new or reconstructed compression ignition (CI) stationary RICE with a site rating of less than or equal to 500 brake HP located at a major source of HAP emissions.

As explained above, Units N-266-952-1 and -953-1 are subject to 40 CFR 60 subpart IIII and 40 CFR 60 subpart JJJJ, respectively and are therefore not required to meet the requirements of this subpart.

§ 63.6595 When do I have to comply with this subpart?

(a) ***Affected sources.***

- (1) If you have an existing stationary RICE, excluding existing non-emergency CI stationary RICE, with a site rating of more than 500 brake HP located at a major source of HAP emissions, you must comply with the applicable emission limitations, operating limitations and other requirements no later than June 15, 2007. If you have an existing non-emergency CI stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions, an existing stationary CI RICE with a site rating of less than or equal to 500 brake HP located

at a major source of HAP emissions, or an existing stationary CI RICE located at an area source of HAP emissions, you must comply with the applicable emission limitations, operating limitations, and other requirements no later than May 3, 2013. If you have an existing stationary SI RICE with a site rating of less than or equal to 500 brake HP located at a major source of HAP emissions, or an existing stationary SI RICE located at an area source of HAP emissions, you must comply with the applicable emission limitations, operating limitations, and other requirements no later than October 19, 2013.

§ 63.6603 What emission limitations, operating limitations, and other requirements must I meet if I own or operate an existing stationary RICE located at an area source of HAP emissions?

Compliance with the numerical emission limitations established in this subpart is based on the results of testing the average of three 1-hour runs using the testing requirements and procedures in § 63.6620 and Table 4 to this subpart.

- (a) If you own or operate an existing stationary RICE located at an area source of HAP emissions, you must comply with the requirements in Table 2d to this subpart and the operating limitations in Table 2b to this subpart that apply to you.

Table 2d to Subpart ZZZZ of Part 63 - Requirements for Existing Stationary RICE Located at Area Sources of HAP Emissions

The following table includes requirements that apply to the existing emergency stationary CI RICE at the facility:

Requirements for Existing Stationary RICE Located at Area Sources of HAP Emissions		
For each . . .	You must meet the following requirement, except during periods of startup . . .	During periods of startup you must . . .
4. Emergency stationary CI RICE and black start stationary CI RICE. ²	a. Change oil and filter every 500 hours of operation or annually, whichever comes first; ¹ b. Inspect air cleaner every 1,000 hours of operation or annually, whichever comes first, and replace as necessary; and c. Inspect all hoses and belts every 500 hours of operation or annually, whichever comes first, and replace as necessary.	Minimize the engine's time spent at idle and minimize the engine's startup time at startup to a period needed for appropriate and safe loading of the engine, not to exceed 30 minutes, after which time the non-startup emission limitations apply.

¹ Sources have the option to utilize an oil analysis program as described in Section 63.6625(i) or (j) in order to extend the specified oil change requirement in Table 2d of this subpart.

² If an emergency engine is operating during an emergency and it is not possible to shut down the engine in order to perform the management practice requirements on the schedule required in Table 2d of this subpart, or if performing the management practice on the required schedule would otherwise pose an unacceptable risk under federal, state, or local law, the management practice can be delayed until the emergency is over or the unacceptable risk under federal, state, or local law has abated. The management practice should be performed as soon as practicable after the emergency has ended or the unacceptable risk under federal, state, or local law has abated. Sources must report any failure to perform the management practice on the schedule required and the federal, state or local law under which the risk was deemed unacceptable.

§ 63.6604 What fuel requirements must I meet if I own or operate a stationary CI RICE?

(b) Beginning January 1, 2015, if you own or operate an existing emergency CI stationary RICE with a site rating of more than 100 brake HP and a displacement of less than 30 liters per cylinder that uses diesel fuel and operates or is contractually obligated to be available for more than 15 hours per calendar year for the purposes specified in § 63.6640(f)(2)(ii) and (iii) or that operates for the purpose specified in § 63.6640(f)(4)(ii), you must use diesel fuel that meets the requirements in 40 CFR 1090.305 for nonroad diesel fuel, except that any existing diesel fuel purchased (or otherwise obtained) prior to January 1, 2015, may be used until depleted.

§ 63.6605 What are my general requirements for complying with this subpart?

(a) You must be in compliance with the emission limitations, operating limitations, and other requirements in this subpart that apply to you at all times.

- (b) At all times you must operate and maintain any affected source, including associated air pollution control equipment and monitoring equipment, in a manner consistent with safety and good air pollution control practices for minimizing emissions. The general duty to minimize emissions does not require you to make any further efforts to reduce emissions if levels required by this standard have been achieved. Determination of whether such operation and maintenance procedures are being used will be based on information available to the Administrator which may include, but is not limited to, monitoring results, review of operation and maintenance procedures, review of operation and maintenance records, and inspection of the source.

§ 63.6625 What are my monitoring, installation, collection, operation, and maintenance requirements?

- (e) If you own or operate any of the following stationary RICE, you must operate and maintain the stationary RICE and after-treatment control device (if any) according to the manufacturer's emission-related written instructions or develop your own maintenance plan which must provide to the extent practicable for the maintenance and operation of the engine in a manner consistent with good air pollution control practice for minimizing emissions:
- (1) An existing stationary RICE with a site rating of less than 100 HP located at a major source of HAP emissions;
 - (2) An existing emergency or black start stationary RICE with a site rating of less than or equal to 500 HP located at a major source of HAP emissions;
 - (3) An existing emergency or black start stationary RICE located at an area source of HAP emissions;
- (f) If you own or operate an existing emergency stationary RICE with a site rating of less than or equal to 500 brake HP located at a major source of HAP emissions or an existing emergency stationary RICE located at an area source of HAP emissions, you must install a non-resettable hour meter if one is not already installed.
- (h) If you operate a new, reconstructed, or existing stationary engine, you must minimize the engine's time spent at idle during startup and minimize the engine's startup time to a period needed for appropriate and safe loading of the engine, not to exceed 30 minutes, after which time the emission standards applicable to all times other than startup in Tables 1a, 2a, 2c, and 2d to this subpart apply.

- (i) If you own or operate a stationary CI engine that is subject to the work, operation or management practices in items 1 or 2 of Table 2c to this subpart or in items 1 or 4 of Table 2d to this subpart, you have the option of utilizing an oil analysis program in order to extend the specified oil change requirement in Tables 2c and 2d to this subpart. The oil analysis must be performed at the same frequency specified for changing the oil in Table 2c or 2d to this subpart. The analysis program must at a minimum analyze the following three parameters: Total Base Number, viscosity, and percent water content. The condemning limits for these parameters are as follows: Total Base Number is less than 30 percent of the Total Base Number of the oil when new; viscosity of the oil has changed by more than 20 percent from the viscosity of the oil when new; or percent water content (by volume) is greater than 0.5. If all of these condemning limits are not exceeded, the engine owner or operator is not required to change the oil. If any of the limits are exceeded, the engine owner or operator must change the oil within 2 business days of receiving the results of the analysis; if the engine is not in operation when the results of the analysis are received, the engine owner or operator must change the oil within 2 business days or before commencing operation, whichever is later. The owner or operator must keep records of the parameters that are analyzed as part of the program, the results of the analysis, and the oil changes for the engine. The analysis program must be part of the maintenance plan for the engine.

§ 63.6635 How do I monitor and collect data to demonstrate continuous compliance?

- (a) If you must comply with emission and operating limitations, you must monitor and collect data according to this section.
- (b) Except for monitor malfunctions, associated repairs, required performance evaluations, and required quality assurance or control activities, you must monitor continuously at all times that the stationary RICE is operating. A monitoring malfunction is any sudden, infrequent, not reasonably preventable failure of the monitoring to provide valid data. Monitoring failures that are caused in part by poor maintenance or careless operation are not malfunctions.
- (c) You may not use data recorded during monitoring malfunctions, associated repairs, and required quality assurance or control activities in data averages and calculations used to report emission or operating levels. You must, however, use all the valid data collected during all other periods.

§ 63.6640 How do I demonstrate continuous compliance with the emission limitations, operating limitations, and other requirements?

- (a) You must demonstrate continuous compliance with each emission limitation, operating limitation, and other requirements in Tables 1a and 1b, Tables 2a and 2b, Table 2c, and Table 2d to this subpart that apply to you according to methods specified in Table 6 to this subpart.
- (b) You must report each instance in which you did not meet each emission limitation or operating limitation in Tables 1a and 1b, Tables 2a and 2b, Table 2c, and Table 2d to this subpart that apply to you. These instances are deviations from the emission and operating limitations in this subpart. These deviations must be reported according to the requirements in § 63.6650. If you change your catalyst, you must reestablish the values of the operating parameters measured during the initial performance test. When you reestablish the values of your operating parameters, you must also conduct a performance test to demonstrate that you are meeting the required emission limitation applicable to your stationary RICE.
- (f) If you own or operate an emergency stationary RICE, you must operate the emergency stationary RICE according to the requirements in paragraphs (f)(1) through (4) of this section. In order for the engine to be considered an emergency stationary RICE under this subpart, any operation other than emergency operation, maintenance and testing, emergency demand response, and operation in non-emergency situations for 50 hours per year, as described in paragraphs (f)(1) through (4) of this section, is prohibited. If you do not operate the engine according to the requirements in paragraphs (f)(1) through (4) of this section, the engine will not be considered an emergency engine under this subpart and must meet all requirements for non-emergency engines.
 - (1) There is no time limit on the use of emergency stationary RICE in emergency situations.
 - (2) You may operate your emergency stationary RICE for any combination of the purposes specified in paragraphs (f)(2)(i) through (iii) of this section for a maximum of 100 hours per calendar year. Any operation for non-emergency situations as allowed by paragraphs (f)(3) and (4) of this section counts as part of the 100 hours per calendar year allowed by this paragraph (f)(2).
 - (i) Emergency stationary RICE may be operated for maintenance checks and readiness testing, provided that the tests are recommended by federal, state or local government, the manufacturer, the vendor, the regional transmission organization or equivalent balancing authority and transmission operator, or the

insurance company associated with the engine. The owner or operator may petition the Administrator for approval of additional hours to be used for maintenance checks and readiness testing, but a petition is not required if the owner or operator maintains records indicating that federal, state, or local standards require maintenance and testing of emergency RICE beyond 100 hours per calendar year.

- (ii) Emergency stationary RICE may be operated for emergency demand response for periods in which the Reliability Coordinator under the North American Electric Reliability Corporation (NERC) Reliability Standard EOP-002-3, Capacity and Energy Emergencies (incorporated by reference, see § 63.14), or other authorized entity as determined by the Reliability Coordinator, has declared an Energy Emergency Alert Level 2 as defined in the NERC Reliability Standard EOP-002-3.
 - (iii) Emergency stationary RICE may be operated for periods where there is a deviation of voltage or frequency of 5 percent or greater below standard voltage or frequency.
- (4) Emergency stationary RICE located at area sources of HAP may be operated for up to 50 hours per calendar year in non-emergency situations. The 50 hours of operation in non-emergency situations are counted as part of the 100 hours per calendar year for maintenance and testing and emergency demand response provided in paragraph (f)(2) of this section. Except as provided in paragraphs (f)(4)(i) and (ii) of this section, the 50 hours per year for non-emergency situations cannot be used for peak shaving or non-emergency demand response, or to generate income for a facility to an electric grid or otherwise supply power as part of a financial arrangement with another entity.

Applicable Requirements from Table 6 to Subpart ZZZZ of Part 63 - Continuous Compliance With Emission Limitations, Operating Limitations, Work Practices, and Management Practices

Continuous Compliance with Emission Limitations, Operating Limitations, Work Practices, and Management Practices for Stationary RICE		
For each . . .	You must meet the following requirement, except during periods of startup . . .	During periods of startup you must . . .
<p>9. Existing emergency and black start stationary RICE ≤500 HP located at a major source of HAP, existing non-emergency stationary RICE <100 HP located at a major source of HAP, existing emergency and black start stationary RICE located at an area source of HAP, existing non-emergency stationary CI RICE ≤300 HP located at an area source of HAP, existing non-emergency 2SLB stationary RICE located at an area source of HAP, existing non-emergency stationary SI RICE located at an area source of HAP which combusts landfill or digester gas equivalent to 10 percent or more of the gross heat input on an annual basis, existing non-emergency 4SLB and 4SRB stationary RICE ≤500 HP located at an area source of HAP, existing non-emergency 4SLB and 4SRB stationary RICE >500 HP located at an area source of HAP that operate 24 hours or less per calendar year, and existing non-emergency 4SLB and 4SRB stationary RICE >500 HP located at an area source of HAP that are remote stationary RICE</p>	<p>a. Work or Management practices</p>	<p>i. Operating and maintaining the stationary RICE according to the manufacturer's emission-related operation and maintenance instructions; or</p> <p>ii. Develop and follow your own maintenance plan which must provide to the extent practicable for the maintenance and operation of the engine in a manner consistent with good air pollution control practice for minimizing emissions.</p>

§ 63.6655 What records must I keep?

(a) If you must comply with the emission and operating limitations, you must keep the records described in paragraphs (a)(1) through (a)(5), (b)(1) through (b)(3) and (c) of this section.

(1) A copy of each notification and report that you submitted to comply with this subpart, including all documentation supporting any Initial

Notification or Notification of Compliance Status that you submitted, according to the requirement in § 63.10(b)(2)(xiv).

- (2) Records of the occurrence and duration of each malfunction of operation (*i.e.*, process equipment) or the air pollution control and monitoring equipment.
 - (3) Records of performance tests and performance evaluations as required in § 63.10(b)(2)(viii).
 - (4) Records of all required maintenance performed on the air pollution control and monitoring equipment.
 - (5) Records of actions taken during periods of malfunction to minimize emissions in accordance with § 63.6605(b), including corrective actions to restore malfunctioning process and air pollution control and monitoring equipment to its normal or usual manner of operation.
- (d) You must keep the records required in Table 6 of this subpart to show continuous compliance with each emission or operating limitation that applies to you.
- (e) You must keep records of the maintenance conducted on the stationary RICE in order to demonstrate that you operated and maintained the stationary RICE and after-treatment control device (if any) according to your own maintenance plan if you own or operate any of the following stationary RICE;
- (1) An existing stationary RICE with a site rating of less than 100 brake HP located at a major source of HAP emissions.
 - (2) An existing stationary emergency RICE.
 - (3) An existing stationary RICE located at an area source of HAP emissions subject to management practices as shown in Table 2d to this subpart.
- (f) If you own or operate any of the stationary RICE in paragraphs (f)(1) through (2) of this section, you must keep records of the hours of operation of the engine that is recorded through the non-resettable hour meter. The owner or operator must document how many hours are spent for emergency operation, including what classified the operation as emergency and how many hours are spent for non-emergency operation. If the engine is used for the purposes specified in § 63.6640(f)(2)(ii) or (iii) or § 63.6640(f)(4)(ii), the owner or operator must

keep records of the notification of the emergency situation, and the date, start time, and end time of engine operation for these purposes.

- (1) An existing emergency stationary RICE with a site rating of less than or equal to 500 brake HP located at a major source of HAP emissions that does not meet the standards applicable to non-emergency engines.
- (2) An existing emergency stationary RICE located at an area source of HAP emissions that does not meet the standards applicable to non-emergency engines.

§ 63.6660 In what form and how long must I keep my records?

- (a) Your records must be in a form suitable and readily available for expeditious review according to § 63.10(b)(1).
- (b) As specified in § 63.10(b)(1), you must keep each record for 5 years following the date of each occurrence, measurement, maintenance, corrective action, report, or record.
- (c) You must keep each record readily accessible in hard copy or electronic form for at least 5 years after the date of each occurrence, measurement, maintenance, corrective action, report, or record, according to § 63.10(b)(1).

a. N-266-3-3: 106 BHP DEUTZ MODEL NDC-BF4 M1013ES DIESEL-FIRED EMERGENCY IC ENGINE POWERING A FIREWATER PUMP

The following conditions of the proposed requirements of the draft renewed Title V permit ensure compliance with this regulation.

Permit Unit #	Permit Description	Condition #s
N-266-3-3	106 bhp Diesel Emergency Engine Powering a Firewater Pump	3, 8-17, and 19

b. N-266-952-1: 250 BHP (INTERMITTENT) JOHN DEERE MODEL 6068HFC48 TIER 3 CERTIFIED DIESEL-FIRED EMERGENCY IC ENGINE POWERING A FIREWATER PUMP

As discussed above, this engine is a new stationary engine as defined in Section 63.6590(a) of this regulation because construction of the engine commenced on or after June 12, 2006 and the engine is subject to the requirements of 40 CFR 60 Subpart IIII. Pursuant to Section 63.6590(c), this engine must meet the requirements of 40 CFR 63 Subpart ZZZZ by

meeting the requirements of 40 CFR part 60 Subpart IIII and no further requirements apply for the engine under this regulation.

- c. N-266-953-1: 302 BHP (INTERMITTENT) DOOSAN MODEL D111L RICH-BURN NATURAL GAS-FIRED EMERGENCY STANDBY IC ENGINE WITH NON-SELECTIVE CATALYTIC REDUCTION (NSCR) POWERING AN ELECTRICAL GENERATOR

As discussed above, this engine is a new stationary engine as defined in Section 63.6590(a) of this regulation because construction of the engine commenced on or after June 12, 2006 and the engine is subject to the requirements of 40 CFR 60 Subpart JJJJ. Pursuant to Section 63.6590(c), this engine must meet the requirements of 40 CFR 63 Subpart ZZZZ by meeting the requirements of 40 CFR part 60 Subpart JJJJ and no further requirements apply for the engine under this regulation.

F. 40 CFR Part 64 - Compliance Assurance Monitoring(CAM)

40 CFR Part 64 requires Compliance Assurance Monitoring for units that meet the following three criteria:

- 1) the unit must have an emission limit for the pollutant;
- 2) the unit must have add-on controls for the pollutant; these are devices such as flue gas recirculation (FGR), baghouses, and catalytic oxidizers; and
- 3) the unit must have a pre-control potential to emit of greater than the major source thresholds.

Pollutant	Major Source Threshold (lb/year)
NO _x	20,000
SO _x	140,000
PM ₁₀	140,000
CO	200,000
VOC	20,000

- a. N-266-1-7: GASOLINE DISPENSING OPERATION WITH ONE 4,000 GALLON (SPLIT 2,000 GALLON GASOLINE/2,000 GALLON DIESEL) CONVAULT ABOVEGROUND STORAGE TANK SERVED BY MORRISON BROTHERS PHASE I VAPOR RECOVERY SYSTEM (VR-402-B), STANDING LOSS CONTROL (VR-301-E), AND 1 FUELING

POINT WITH 1 GASOLINE DISPENSING NOZZLE SERVED BY
 BALANCE PHASE II VAPOR RECOVERY SYSTEM (G-70-116F)

This permit unit has an emissions limit for VOC and is equipped with vapor recovery, which may be considered an add-on control for VOC. Therefore, the unit may potentially be subject to CAM for VOC.

The annual pre-control potential to emit for VOC from this permit unit is calculated below using the VOC emission factor for aboveground tanks for gasoline dispensing without vapor recovery.

Uncontrolled VOC Emission Factor for Gasoline Dispensing Operations
 with Aboveground Storage Tanks

These emission factors were obtained from Appendix A - Emission Factors For Gasoline Stations published by CAPCOA Air Toxic "Hot Spots" Program in the Gasoline Service Station Industrywide Risk Assessment Guidelines dated December 1997.

VOC Emission Factors	
Emission Factor (EF1) (lb-VOC/1,000 gal)	Emission Source
8.4	Tank filling loss
2.1	Breathing Loss (A/G tank)
8.4	Vehicle fueling loss
0.61	Spillage
19.51	Total VOC Losses

The current permit limits the maximum Amount of Gasoline that can be dispensed annually to 657,000 gal/year

Pre-Control Potential to Emit for VOC:
 $19.51 \text{ lb-VOC/1,000 gal} \times 657,000 \text{ gal/yr} = 12,818 \text{ lb-VOC/yr} < 20,000 \text{ lb-VOC/yr}$

As shown above, the pre-control potential to emit for VOC from this permit unit does not unit exceed the applicable major source threshold for this pollutant. Therefore, this permit unit is not subject to CAM.

b. N-266-503-6: 5.978 MMBTU/HR FULTON NATURAL GAS-FIRED BOILER WITH A FULTON MODEL 102347 LOW NOX BURNER

This permit unit is not equipped with any add-on controls for any pollutant that would cause the unit to be subject to these requirements. Therefore, this permit unit is not subject to CAM.

c. N-266-952-1: 250 BHP (INTERMITTENT) JOHN DEERE MODEL 6068HFC48 TIER 3 CERTIFIED DIESEL-FIRED EMERGENCY IC ENGINE POWERING A FIREWATER PUMP

This permit unit is not equipped with any add-on controls for any pollutant that would cause the unit to be subject to these requirements. Therefore, this permit unit is not subject to CAM.

d. N-266-953-1: 302 BHP (INTERMITTENT) DOOSAN MODEL D111L RICH-BURN NATURAL GAS-FIRED EMERGENCY STANDBY IC ENGINE WITH NON-SELECTIVE CATALYTIC REDUCTION (NSCR) POWERING AN ELECTRICAL GENERATOR

This permit unit has emissions limits for NO_x, PM₁₀, CO, and VOC and is equipped with non-selective catalytic reduction (NSCR), which is considered an add-on control for NO_x, CO, and VOC. Therefore, the unit may potentially be subject to CAM for NO_x, CO, and VOC.

The annual pre-control potential to emit for NO_x, CO, and VOC from this permit unit are calculated below using the NO_x, CO, and VOC emission factors rich-burn IC engines from AP 42, Chapter 3.2 - Natural Gas-fired Reciprocating Engines.

Maximum Pre-Control Potential to Emit for NO_x

The pre-control potential to emit for NO_x from the engine is calculated as follows:

Engine bhp: 302 bhp
Annual Hours of Operation: 100 hr/yr (Current permit)
NO_x Emission Factor: 2.21 lb-NO_x/MMBtu (AP 42, Table 3.2-3 (July 2000))
Btu to bhp-hr Conversion: 2,545 Btu/bhp-hr
Engine mechanical efficiency: 30% (assumed)

Pre-Control Potential to Emit for NO_x from the engine:

$302 \text{ bhp} \times 100 \text{ hr/yr} \times 1 \text{ bhp}_{(in)}/0.3 \text{ bhp}_{(out)} \times 2,545 \text{ Btu/bhp-hr} \times 1 \text{ MMBtu}/10^6 \text{ Btu} \times 2.21 \text{ lb-NO}_x/\text{MMBtu} = 566 \text{ lb-NO}_x/\text{yr}$

As shown above, the pre-control potential to emit for NO_x from this permit unit does not unit exceed the applicable major source threshold for this pollutant. Therefore, this permit unit is not subject to CAM for NO_x.

Maximum Pre-Control Potential to Emit for CO

The pre-control potential to emit for CO from the engine is calculated as follows:

Engine bhp: 302 bhp
Annual Hours of Operation: 100 hr/yr (Current permit)
CO Emission Factor: 3.72 lb-CO/MMBtu (AP 42, Table 3.2-3 (July 2000))
Btu to bhp-hr Conversion: 2,545 Btu/bhp-hr
Engine mechanical efficiency: 30% (assumed)

Pre-Control Potential to Emit for CO from the engine:

$$302 \text{ bhp} \times 100 \text{ hr/yr} \times 1 \text{ bhp}_{(in)}/0.3 \text{ bhp}_{(out)} \times 2,545 \text{ Btu/bhp-hr} \times 1 \text{ MMBtu}/10^6 \text{ Btu} \times 3.72 \text{ lb-CO/MMBtu} = 953 \text{ lb-CO/yr}$$

As shown above, the pre-control potential to emit for CO from this permit unit does not unit exceed the applicable major source threshold for this pollutant. Therefore, this permit unit is not subject to CAM for CO.

Maximum Pre-Control Potential to Emit for VOC

The pre-control potential to emit for VOC from the engine is calculated as follows:

Engine bhp: 302 bhp
Annual Hours of Operation: 100 hr/yr (Current permit)
VOC Emission Factor: 0.0296 lb-VOC/MMBtu (AP 42, Table 3.2-3 (July 2000))
Btu to bhp-hr Conversion: 2,545 Btu/bhp-hr
Engine mechanical efficiency: 30% (assumed)

Pre-Control Potential to Emit for VOC from the engine:

$$302 \text{ bhp} \times 100 \text{ hr/yr} \times 1 \text{ bhp}_{(in)}/0.3 \text{ bhp}_{(out)} \times 2,545 \text{ Btu/bhp-hr} \times 1 \text{ MMBtu}/10^6 \text{ Btu} \times 0.0296 \text{ lb-VOC/MMBtu} = 8 \text{ lb-VOC/yr}$$

As shown above, the pre-control potential to emit for VOC from this permit unit does not unit exceed the applicable major source threshold for this pollutant. Therefore, this permit unit is not subject to CAM for VOC.

e. All Wine Fermentation and Storage Tanks at the Facility

These permit units are not equipped with any add-on controls for any pollutant that would cause the units to be subject to these requirements. Therefore, these permit units are not subject to CAM.

J. **40 CFR Part 82, Subpart B - Servicing of Motor Vehicle Air Conditioners**

The purpose of 40 CFR Part 82 Subpart B is to implement section 609 of the Clean Air Act, as amended regarding the servicing of motor vehicle air conditioners (MVACs), and to implement section 608 of the Clean Air Act regarding certain servicing, maintenance, repair and disposal of air conditioners in MVACs and MVAC-like appliances.

These regulations apply to any person performing service on a motor vehicle for consideration when this service involves the refrigerant in the motor vehicle air conditioner.

The amendments to this subpart did not have any effect on the current permit requirements and will therefore not be addressed further in this evaluation.

The following condition of the proposed requirements of the facility-wide permit ensure compliance with this regulation.

Permit Unit #	Permit Description	Condition #
N-266-0-2	Facility-Wide Permit	28

K. **40 CFR Part 82, Subpart F - Recycling and Emissions Reduction**

The purpose of 40 CFR Part 82 Subpart F is to reduce emissions of class I and class II refrigerants and their substitutes to the lowest achievable level by maximizing the recapture and recycling of such refrigerants during the service, maintenance, repair, and disposal of appliances and restricting the sale of refrigerants consisting in whole or in part of a class I and class II ODS in accordance with Title VI of the Clean Air Act.

These regulations apply to any person servicing, maintaining, or repairing appliances. This subpart also applies to persons disposing of appliances, including small appliances and motor vehicle air conditioners. In addition, this subpart applies to refrigerant reclaimers, technician certifying programs, appliance owners and operators, manufacturers of appliances, manufacturer of recycling and recovery equipment, approved recycling and recovery equipment testing organizations, persons selling class I or class II refrigerants or offering class I or class II refrigerants for sale, and persons purchasing class I or class II refrigerants.

The amendments to this subpart do not have any effect on the current permit requirements and therefore will not be addressed further in this evaluation.

The following condition of the proposed requirements of the facility-wide permit ensure compliance with this regulation.

Permit Unit #	Permit Description	Condition #
N-266-0-2	Facility-Wide Permit	27

IX. PERMIT SHIELD

A permit shield legally protects a facility from enforcement of the shielded regulations when a source is in compliance with the terms and conditions of the Title V permit. Compliance with the terms and conditions of the Operating Permit is considered compliance with all applicable requirements upon which those conditions are based, including those that have been subsumed.

A. Requirements Addressed by Model General Permit Templates

1. Model General Permit Template SJV-UM-0-3

By submitting Model General Permit Template SJV-UM-0-3 qualification form, the applicant has requested that a permit shield be granted for all the applicable requirements identified by the template. Therefore, the permit shields as granted in Model General Permit Template is included as conditions 39 and 40 of the facility-wide requirements (N-266-0-2).

B. Requirements not Addressed by Model General Permit Templates

The applicant is not requesting any permit shields that are not addressed by general permit templates.

X. CALIFORNIA ENVIRONMENTAL QUALITY ACT

The purpose of the Title V permit renewal is to update the permit to ensure that any changes to regulations since the issuance of the initial Title V permit or most recent renewal of the Title V permit are incorporated as permit requirements.

Per the California Environmental Quality Act (CEQA) Statute §21080.24, and CEQA Guidelines §15281, the issuance, modification, amendment, or renewal of any permit by an air pollution control district or air quality management district pursuant to Title V is exempt from CEQA, unless the issuance, modification,

amendment, or renewal authorizes a physical or operational change to a source or facility. There will be no physical or operational change to the source or facility nor will the Title V permit renewal authorize a physical or operational change to the source or facility. Therefore, this project, a Title V permit renewal, is subject to a ministerial action that is exempt from CEQA.

XI. PERMIT CONDITIONS

See Attachment A - Draft Renewed Title V Operating Permit.

ATTACHMENTS

- A. Draft Renewed Title V Operating Permit
- B. Previous Title V Operating Permit
- C. Detailed Summary List of Facility Permits

ATTACHMENT A

Draft Renewed Title V Operating Permit

San Joaquin Valley Air Pollution Control District

FACILITY: N-266-0-2

EXPIRATION DATE: 10/31/2020

FACILITY-WIDE REQUIREMENTS

1. {4362} The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100, 6.1; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit
2. {4363} The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100, 7.0; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit
3. {4364} The owner or operator of any stationary source operation that emits more than 25 tons per year of nitrogen oxides or reactive organic compounds, shall provide the District annually with a written statement in such form and at such time as the District prescribes, showing actual emissions of nitrogen oxides and reactive organic compounds from that source. [District Rule 1160, 5.0] Federally Enforceable Through Title V Permit
4. Any person building, altering or replacing any operation, article, machine, equipment, or other contrivance, the use of which may cause the issuance of air contaminants or the use of which may eliminate, reduce, or control the issuance of air contaminants, shall first obtain an Authority to Construct (ATC) from the District unless exempted by District Rule 2020 (8/18/11). [District Rule 2010, 3.0 and 4.0; and 2020] Federally Enforceable Through Title V Permit
5. {4366} The permittee must comply with all conditions of the permit including permit revisions originated by the District. All terms and conditions of a permit that are required pursuant to the Clean Air Act (CAA), including provisions to limit potential to emit, are enforceable by the EPA and Citizens under the CAA. Any permit noncompliance constitutes a violation of the CAA and the District Rules and Regulations, and is grounds for enforcement action, for permit termination, revocation, reopening and reissuance, or modification; or for denial of a permit renewal application. [District Rules 2070, 7.0; 2080; and 2520, 9.8.1 and 9.13.1] Federally Enforceable Through Title V Permit
6. {4367} A Permit to Operate or an Authority to Construct shall not be transferred unless a new application is filed with and approved by the District. [District Rule 2031] Federally Enforceable Through Title V Permit
7. Every application for a permit required under Rule 2010 (12/17/92) shall be filed in a manner and form prescribed by the District. [District Rule 2040]
8. {4369} The operator shall maintain records of required monitoring that include: 1) the date, place, and time of sampling or measurement; 2) the date(s) analyses were performed; 3) the company or entity that performed the analysis; 4) the analytical techniques or methods used; 5) the results of such analysis; and 6) the operating conditions at the time of sampling or measurement. [District Rule 2520, 9.4.1] Federally Enforceable Through Title V Permit
9. {4370} The operator shall retain records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, or report. Support information includes copies of all reports required by the permit and, for continuous monitoring instrumentation, all calibration and maintenance records and all original strip-chart recordings. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate. Any amendments to these Facility-wide Requirements that affect specific Permit Units may constitute modification of those Permit Units.

Facility Name: DELICATO VINEYARDS
Location: 12001 S HIGHWAY 99, MANTECA, CA 95336
N-266-0-2 : Sep 27 2021 1:20PM -- NORMANR

10. {4371} The operator shall submit reports of any required monitoring at least every six months unless a different frequency is required by an applicable requirement. All instances of deviations from permit requirements must be clearly identified in such reports. [District Rule 2520, 9.5.1] Federally Enforceable Through Title V Permit
11. {4372} Deviations from permit conditions must be promptly reported, including deviations attributable to upset conditions, as defined in the permit. For the purpose of this condition, promptly means as soon as reasonably possible, but no later than 10 days after detection. The report shall include the probable cause of such deviations, and any corrective actions or preventive measures taken. All required reports must be certified by a responsible official consistent with section 10.0 of District Rule 2520 (6/21/01). [District Rules 2520, 9.5.2 and 1100, 7.0] Federally Enforceable Through Title V Permit
12. {4373} If for any reason a permit requirement or condition is being challenged for its constitutionality or validity by a court of competent jurisdiction, the outcome of such challenge shall not affect or invalidate the remainder of the conditions or requirements in that permit. [District Rule 2520, 9.7] Federally Enforceable Through Title V Permit
13. {4374} It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. [District Rule 2520, 9.8.2] Federally Enforceable Through Title V Permit
14. {4375} The permit may be modified, revoked, reopened and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition. [District Rule 2520, 9.8.3] Federally Enforceable Through Title V Permit
15. {4376} The permit does not convey any property rights of any sort, or any exclusive privilege. [District Rule 2520, 9.8.4] Federally Enforceable Through Title V Permit
16. {4377} The Permittee shall furnish to the District, within a reasonable time, any information that the District may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the District copies of records required to be kept by the permit or, for information claimed to be confidential, the permittee may furnish such records directly to EPA along with a claim of confidentiality. [District Rule 2520, 9.8.5] Federally Enforceable Through Title V Permit
17. {4378} The permittee shall pay annual permit fees and other applicable fees as prescribed in Regulation III of the District Rules and Regulations. [District Rule 2520, 9.9] Federally Enforceable Through Title V Permit
18. {4379} Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 2520, 9.13.2.1] Federally Enforceable Through Title V Permit
19. {4380} Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 2520, 9.13.2.2] Federally Enforceable Through Title V Permit
20. {4381} Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to inspect at reasonable times any facilities, equipment, practices, or operations regulated or required under the permit. [District Rule 2520, 9.13.2.3] Federally Enforceable Through Title V Permit
21. {4382} Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements. [District Rule 2520, 9.13.2.4] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

22. {4383} No air contaminants shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101 (02/17/05). If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101, and County Rules 401 (in all eight counties in the San Joaquin Valley)] Federally Enforceable Through Title V Permit
23. No person shall: manufacture, blend, or repackage for use within the District; or supply, sell, market or offer for sale within the District; or solicit for application or apply within the District any architectural coating or colorant with a VOC content in excess of the corresponding limit specified in Table 1 or Table 2 of District Rule 4601 (4/16/20), after the specified effective date in Table 1 or Table 2 of District Rule 4601. [District Rule 4601, 5.1] Federally Enforceable Through Title V Permit
24. All architectural coating containers and containers of any VOC-containing materials subject to Rule 4601 (4/16/20) shall be closed when not in use. [District Rule 4601, 5.4] Federally Enforceable Through Title V Permit
25. The permittee shall comply with all the Labeling and Test Methods requirements outlined in Rule 4601, sections 6.1 and 6.3 (4/16/20). [District Rule 4601, 6.1 and 6.3] Federally Enforceable Through Title V Permit
26. {4387} With each report or document submitted under a permit requirement or a request for information by the District or EPA, the permittee shall include a certification of truth, accuracy, and completeness by a responsible official. [District Rule 2520, 9.13.1 and 10.0] Federally Enforceable Through Title V Permit
27. {4388} If the permittee performs maintenance on, or services, repairs, or disposes of appliances, the permittee shall comply with the standards for Recycling and Emissions Reduction pursuant to 40 CFR Part 82, Subpart F. [40 CFR 82 Subpart F] Federally Enforceable Through Title V Permit
28. {4389} If the permittee performs service on motor vehicles when this service involves the ozone-depleting refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the standards for Servicing of Motor Vehicle Air Conditioners pursuant to all the applicable requirements as specified in 40 CFR Part 82, Subpart B. [40 CFR Part 82, Subpart B] Federally Enforceable Through Title V Permit
29. {4390} Disturbances of soil related to any construction, demolition, excavation, extraction, or other earthmoving activities shall comply with the requirements for fugitive dust control in District Rule 8021 unless specifically exempted under Section 4.0 of Rule 8021 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8021] Federally Enforceable Through Title V Permit
30. {4391} Outdoor handling, storage and transport of any bulk material which emits dust shall comply with the requirements of District Rule 8031, unless specifically exempted under Section 4.0 of Rule 8031 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8031] Federally Enforceable Through Title V Permit
31. {4392} An owner/operator shall prevent or cleanup any carryout or trackout in accordance with the requirements of District Rule 8041 Section 5.0, unless specifically exempted under Section 4.0 of Rule 8041 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8041] Federally Enforceable Through Title V Permit
32. {4393} Whenever open areas are disturbed, or vehicles are used in open areas, the facility shall comply with the requirements of Section 5.0 of District Rule 8051, unless specifically exempted under Section 4.0 of Rule 8051 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8051] Federally Enforceable Through Title V Permit
33. {4394} Any paved road or unpaved road shall comply with the requirements of District Rule 8061 unless specifically exempted under Section 4.0 of Rule 8061 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8061] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

34. {4395} Any unpaved vehicle/equipment area that anticipates more than 50 Average annual daily Trips (AADT) shall comply with the requirements of Section 5.1.1 of District Rule 8071. Any unpaved vehicle/equipment area that anticipates more than 150 vehicle trips per day (VDT) shall comply with the requirements of Section 5.1.2 of District Rule 8071. On each day that 25 or more VDT with 3 or more axles will occur on an unpaved vehicle/equipment traffic area, the owner/operator shall comply with the requirements of Section 5.1.3 of District Rule 8071. On each day when a special event will result in 1,000 or more vehicles that will travel/park on an unpaved area, the owner/operator shall comply with the requirements of Section 5.1.4 of District Rule 8071. All sources shall comply with the requirements of Section 5.0 of District Rule 8071 unless specifically exempted under Section 4.0 of Rule 8071 (9/16/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8071] Federally Enforceable Through Title V Permit
35. {4396} Any owner or operator of a demolition or renovation activity, as defined in 40 CFR 61.141, shall comply with the applicable inspection, notification, removal, and disposal procedures for asbestos containing materials as specified in 40 CFR 61.145 (Standard for Demolition and Renovation). [40 CFR 61 Subpart M] Federally Enforceable Through Title V Permit
36. {4397} The permittee shall submit certifications of compliance with the terms and standards contained in Title V permits, including emission limits, standards and work practices, to the District and the EPA annually (or more frequently as specified in an applicable requirement or as specified by the District). The certification shall include the identification of each permit term or condition, the compliance status, whether compliance was continuous or intermittent, the methods used for determining the compliance status, and any other facts required by the District to determine the compliance status of the source. [District Rule 2520, 9.16] Federally Enforceable Through Title V Permit
37. {4398} The permittee shall submit an application for Title V permit renewal to the District at least six months, but not greater than 18 months, prior to the permit expiration date. [District Rule 2520, 5.2] Federally Enforceable Through Title V Permit
38. {4399} When a term is not defined in a Title V permit condition, the definition in the rule cited as the origin and authority for the condition in a Title V permits shall apply. [District Rule 2520, 9.1.1] Federally Enforceable Through Title V Permit
39. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following outdated SIP requirements: San Joaquin County Rule 110, San Joaquin County Rule 202, and San Joaquin County Rule 401. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
40. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following applicable requirements: SJVUAPCD Rules 2010, Sections 3.0 and 4.0 (12/17/92); 2031 (12/17/92); 2070, section 7.0 (12/17/92); 2080 (12/17/92); 4101 (2/17/05); 8021 (8/19/2004); 8031 (8/19/2004); 8041 (8/19/2004); 8051 (8/19/2004); 8061 (8/19/2004); and 8071 (9/16/2004). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
41. The reporting periods for the Report of Required Monitoring and the Compliance Certification Report begin October 1 of every year, unless alternative dates are approved by the District Compliance Division. These reports are due within 30 days of the end of the reporting period. [District Rule 2520] Federally Enforceable Through Title V Permit
42. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
43. The winery operator shall achieve required annual emissions reductions (RAER) equal to at least 35% of the winery's baseline fermentation emissions (BFE) [District Rule 4694]
44. By December 1, 2006, and every three years thereafter, the winery operator subject to the requirements of Section 5.1 shall submit to the District a three-year compliance plan that demonstrates compliance with the applicable requirements of District Rule 4694 for each year of the applicable compliance period. The three-year compliance plan shall include all the information specified in sections 6.1.1 through 6.1.8 of the rule. [District Rule 4694, 6.1]

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

45. By July 1, 2007, and every three years thereafter, the winery operator shall submit to the District a three-year compliance plan verification that demonstrates that the three-year compliance plan elements are in effect. The compliance plan verification shall include all the information specified in sections 6.2.1 through 6.2.5 of District Rule 4694. [District Rule 4694, 6.2]
46. By March 1, 2008, and every year thereafter on or before March 1, the winery operator shall submit to the District an annual compliance plan demonstration that shows compliance with the applicable requirements of District Rule 4694. The compliance plan demonstration shall include all the information specified in sections 6.3.1 through 6.3.7 of the rule. All additional Required Annual Emissions Reductions (RAER) shall be obtained by April 1 of the year of the Annual Compliance Demonstration, per section 6.3.7.2 of the rule. [District Rule 4694, 6.3]
47. Operators using certified emission reductions (CER) to mitigate fermentation emissions shall perform all monitoring and recordkeeping, as established in their approved three-year compliance plan, and shall maintain all records necessary to demonstrate compliance. [District Rule 4694]
48. Payment of District Obtained Emissions Reductions (DOER) and administrative fees shall be made to the District no later than March 1, of the first year in the applicable compliance period. [District Rule 4694, 6.1.5.3.5]

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-1-7

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

GASOLINE DISPENSING OPERATION WITH ONE 4,000 GALLON (SPLIT 2,000 GALLON GASOLINE/2,000 GALLON DIESEL) CONVAULT ABOVEGROUND STORAGE TANK SERVED BY MORRISON BROTHERS PHASE I VAPOR RECOVERY SYSTEM (VR-402-B), STANDING LOSS CONTROL (VR-301-E), AND 1 FUELING POINT WITH 1 GASOLINE DISPENSING NOZZLE SERVED BY BALANCE PHASE II VAPOR RECOVERY SYSTEM (G-70-116F)

PERMIT UNIT REQUIREMENTS

1. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The Phase I, Phase II, and Standing Loss Control Vapor recovery systems shall be installed and maintained in accordance with the manufacturer specifications and the ARB Executive Orders specified in this permit, including applicable rules and regulations of the Division of Measurement Standards of the Department of Food and Agriculture, the Office of the State Fire Marshal of the Department of Forestry and Fire Protection, the Division of Occupational Safety and Health of the Department of Industrial Relations, and the Division of Water Quality of the State Water Resources Control Board that have been made conditions of the certification. [District Rules 4621 and 4622 and CH&SC 41950] Federally Enforceable Through Title V Permit
3. This gasoline storage and dispensing equipment shall not be used in retail sales, where gasoline dispensed by the unit is subject to payment of California sales tax on gasoline sales. [District Rule 4622] Federally Enforceable Through Title V Permit
4. The storage container(s) shall be installed, maintained, and operated such that they are leak-free. [District Rule 4621] Federally Enforceable Through Title V Permit
5. The Phase I and Phase II vapor recovery systems and gasoline dispensing equipment shall be maintained without leaks as determined in accordance with the test method specified in this permit. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
6. A leak is defined as the dripping of VOC-containing liquid at a rate of more than three (3) drops per minute, or the detection of any gaseous or vapor emissions with a concentration of total organic compound greater than 10,000 ppmv, as methane, above background when measured in accordance with EPA Test Method 21. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
7. No gasoline delivery vessel shall be operated or be allowed to operate unless valid State of California decals are displayed on the cargo container, which attest to the vapor integrity of the container. [District Rule 4621] Federally Enforceable Through Title V Permit
8. No person shall operate any ARB certified Phase II vapor recovery system or any portion thereof that has a major defect or an equipment defect that is identified in any applicable ARB Executive Order until the following conditions have been met: 1) the defect has been repaired, replaced, or adjusted as necessary to correct the defect; 2) the District has been notified, and the District has reinspected the system or authorized the system for use (such authorization shall not include the authority to operate the equipment prior to the correction of the defective components); and 3) all major defects, after repair, are duly entered into the Operations and Maintenance (O&M) manual. [District Rule 4622] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

9. Upon identification of any major defects, the permittee shall tag "Out-of-Order" all dispensing equipment for which vapor recovery has been impaired. Tagged equipment shall be rendered inoperable and the tag(s) shall not be removed until the defective equipment has been repaired, replaced, or adjusted, as necessary. In the case of defects identified by the District, tagged equipment shall be rendered inoperable, and the tag shall not be removed until the District has been notified of the repairs, and the District has either reinspected the system or authorized the tagged equipment for use. [District Rule 4622] Federally Enforceable Through Title V Permit
10. The permittee shall implement a periodic maintenance inspection program for the certified Phase II vapor recovery system consistent with the requirements of this permit. The program shall be documented in an operation and maintenance (O&M) manual and shall at a minimum contain the following information: 1) copies of all vapor recovery performance tests; 2) all applicable ARB Executive Orders, Approval Letters, and District Permits; 3) the manufacturer's specifications and instructions for installation, operation, repair, and maintenance required pursuant to ARB Certification Procedure CP-201, and any additional instruction provided by the manufacturer; 4) system and/or component testing requirements, including test schedules and passing criteria for each of the standard tests required by this permit (the owner/operator may include any non-ARB required diagnostic and other tests as part of the testing requirements), and 5) additional O&M instructions, if any, that are designed to ensure compliance with the applicable rules, regulations, ARB Executive Orders, and District permit conditions, including replacement schedules for failure or wear prone components. [District Rule 4622] Federally Enforceable Through Title V Permit
11. The permittee shall conduct periodic maintenance inspections based on the greatest monthly throughput of gasoline dispensed by the facility in the previous year as follows: A) less than 2,500 gallons - one day per month; B) 2,500 to less than 25,000 gallons - one day per week; or C) 25,000 gallons or greater - five days per week. All inspections shall be documented within the O & M Manual. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
12. Periodic maintenance inspections of the Phase I vapor recovery system shall include, at a minimum, verification that 1) the fill caps and vapor caps are not missing, damaged, or loose; 2) the fill cap gasket and vapor cap gaskets are not missing or damaged; 3) the fill adapter and vapor adapter are securely attached to the risers; 4) where applicable, the spring-loaded submerged fill tube seals properly against the coaxial tubing; 5) the dry break (poppet-valve) is not missing or damaged; and 6) the submerged fill tube is not missing or damaged. [District Rule 4621] Federally Enforceable Through Title V Permit
13. Periodic maintenance inspections of the Phase II vapor recovery system shall include, at a minimum, verification that 1) the following nozzle components are in place and in good condition as specified in ARB Executive Order as applicable: faceplate/facecone, bellows, latching device spring, vapor check valve, spout (proper diameter/vapor collection holes), insertion interlock mechanism, automatic shut-off mechanism, and hold open latch (unless prohibited by law or the local fire control authority); 2) the hoses are not torn, flattened or crimped; 3) the vapor path of the coaxial hoses associated with bellows equipped nozzles does not contain more than 100 ml of liquid if applicable; and 4) the vapor processing unit is functioning properly, for operations that are required to have or possess such a unit. [District Rule 4622] Federally Enforceable Through Title V Permit
14. In the event of a separation due to a drive off, the permittee shall, unless otherwise specified in the applicable ARB Executive Order, conduct a visual inspection of the affected equipment and either 1) perform qualified repairs on any damaged components and conduct applicable re-verification tests pursuant to the requirements of this permit, or 2) replace the affected nozzles, coaxial hoses, breakaway couplings, and any other damaged components with new or certified rebuilt components that are ARB certified. The activities shall be documented in accordance with the requirements of this permit before placing the affected equipment back in service. [District Rule 4622] Federally Enforceable Through Title V Permit
15. The gasoline throughput for this permit unit shall not exceed 657,000 gallons in any one calendar year. [District Rule 2201] Federally Enforceable Through Title V Permit
16. The permittee shall conduct all periodic vapor recovery system performance tests specified in this permit, no more than 30 days before or after the required compliance testing date, unless otherwise required under the applicable ARB Executive Order. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

17. The permittee shall perform and pass a Static Leak Test "Determination of Static Pressure Performance of Vapor Recovery Systems at Gasoline Dispensing Facilities with Aboveground Tanks" in accordance with the Executive Order specified in this permit for the Phase I Vapor Recovery System at least once every 12 months. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
18. For certified Phase II vapor recovery systems with liquid removal devices, the permittee shall perform and pass an ARB TP-201.6C Liquid Removal Test whenever the liquid in the vapor path exceeds 100 ml of liquid, or as required by the applicable ARB Executive Order. The amount of liquid in the vapor path shall be measured by lowering the gasoline dispensing nozzle into a container until such time that no more liquid drains from the nozzle. The amount of liquid drained into the container shall be measured using a graduated cylinder or graduated beaker. The vapor path shall be inspected according to the monitoring frequency as determined by monthly gasoline throughput. [District Rule 4622] Federally Enforceable Through Title V Permit
19. A person conducting testing of, or repairs to, a certified vapor recovery system shall be in compliance with District Rule 1177 (Gasoline Dispensing Facility Tester Certification). [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
20. A person performing installation of, or maintenance on, a certified Phase I or Phase II vapor recovery system shall be certified by the ICC for Vapor Recovery System Installation and Repair, or work under the direct and personal supervision of an individual physically present at the work site who is certified. The ICC certification shall be renewed every 24 months. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
21. Proof of the ICC certification and all other certifications required by the Executive Order and installation and operation manual shall be made available onsite. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
22. The permittee shall notify the District at least 7 days prior to each performance test. The test results shall be submitted to the District no later than 30 days after the completion of each test. [District Rule 4621] Federally Enforceable Through Title V Permit
23. The permittee shall maintain a copy of all test results. The test results shall be dated and shall contain the name, address, and telephone number of the company responsible for system installation and testing. [District Rule 4622] Federally Enforceable Through Title V Permit
24. The permittee shall maintain on the premises a log of any repairs made to the certified Phase I or Phase II vapor recovery system. The repair log shall include the following: 1) date and time of each repair; 2) the name and applicable certification numbers of the person(s) who performed the repair, and if applicable, the name, address and phone number of the person's employer; 3) description of service performed; 4) each component that was repaired, serviced, or removed; 5) each component that was installed as replacement, if applicable; and 6) receipts or other documents for parts used in the repair and, if applicable, work orders which shall include the name and signature of the person responsible for performing the repairs. [District Rule 4622] Federally Enforceable Through Title V Permit
25. The O&M manual shall be kept at the dispensing operation and made available to any person who operates, inspects, maintains, repairs, or tests the equipment at the operation as well as to District personnel upon request. [District Rule 4622] Federally Enforceable Through Title V Permit
26. The permittee shall maintain monthly and annual gasoline throughput records. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
27. All records required by this permit shall be retained on-site for a period of at least five years and shall be made available for District inspection upon request. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-3-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

106 BHP DEUTZ MODEL NDC-BF4 M1013ES DIESEL-FIRED EMERGENCY IC ENGINE POWERING A FIREWATER PUMP

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. {1898} The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102]
3. This engine shall be equipped with a non-resettable hour meter with a minimum display capability of 9,999 hours, unless the District determines that a non-resettable hour meter with a different minimum display capability is appropriate in consideration of the historical use of the engine and the owner or operator's compliance history. [District Rule 4702, 17 CCR 93115, and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
4. This engine shall be equipped with either a positive crankcase ventilation (PCV) system that recirculates crankcase emissions into the air intake system for combustion, or a crankcase emissions control device of at least 90% control efficiency. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Only CARB certified diesel fuel containing not more than 0.0015% sulfur by weight shall be used. [District Rules 2201 and 4801, San Joaquin County Rule 407, and 17 CCR 93115] Federally Enforceable Through Title V Permit
6. NOx emissions shall not exceed 5.9 g/hp-hr. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The PM10 emissions rate shall not exceed 0.1 g/hp-hr based on US EPA certification using ISO 8178 test procedure. [District Rule 2201] Federally Enforceable Through Title V Permit
8. This engine shall be operated only for testing and maintenance of the engine, required regulatory purposes, and to preserve or protect property, human life, or public health during a fire. For testing purposes, the engine shall only be operated the number of hours necessary to comply with the testing requirements of the National Fire Protection Association (NFPA) 25 - "Standard for the Inspection, Testing, and Maintenance of Water-Based Fire Protection Systems", 1998 edition. Total hours of operation for all maintenance, testing, and required regulatory purposes shall not exceed 50 hours per calendar year. [District Rules 2201, 4701, 4702, 17 CCR 93115, and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
9. This engine shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier in a manner consistent with good air pollution control practice for minimizing emissions. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
10. The permittee must minimize the engine's time spent at idle during startup and minimize the engine's startup time to a period needed for appropriate and safe loading of the engine, not to exceed 30 minutes. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
11. The engine's oil and filter shall be changed every 500 hours of operation or every 12 months, whichever comes first. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

12. The engine's air filter shall be inspected every 1,000 hours of operation or every 12 months, whichever comes first, and replaced as necessary. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
13. The engine's hoses and belts shall be inspected every 500 hours of operation or every 12 months, whichever comes first, and replaced as necessary. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
14. The permittee has the option of utilizing an oil analysis program in order to extend the specified oil change requirement in Tables 2c and 2d of Subpart ZZZZ. The oil analysis must be performed at the same frequency specified for changing the oil in Table 2c or 2d to this subpart. The analysis program must at a minimum analyze the following three parameters: Total Base Number, viscosity, and percent water content. The condemning limits for these parameters are as follows: Total Base Number is less than 30 percent of the Total Base Number of the oil when new; viscosity of the oil has changed by more than 20 percent from the viscosity of the oil when new; or percent water content (by volume) is greater than 0.5. If all of these condemning limits are not exceeded, the engine owner or operator is not required to change the oil. If any of the limits are exceeded, the engine owner or operator must change the oil within 2 days of receiving the results of the analysis; if the engine is not in operation when the results of the analysis are received, the engine owner or operator must change the oil within 2 days or before commencing operation, whichever is later. The owner or operator must keep records of the parameters that are analyzed as part of the program, the results of the analysis, and the oil changes for the engine. The analysis program must be part of the maintenance plan for the engine. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
15. The permittee must maintain records of all required maintenance performed on the air pollution control and monitoring equipment. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
16. The permittee shall maintain monthly records of the occurrence and duration of each malfunction of operation (i.e., process equipment) or the air pollution control and monitoring equipment. The permittee shall also maintain monthly records of action taken during periods of malfunction to minimize emissions, including corrective actions to restore malfunctioning process and air pollution control and monitoring equipment to its normal or usual manner of operation. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
17. The permittee shall maintain monthly records of emergency and non-emergency operation. Records shall include the number of hours of emergency operation, the date and number of hours of all testing and maintenance operations, and the purpose of the operation (for example: load testing, weekly testing, rolling blackout, general area power outage, etc.). For units with automated testing systems, the operator may, as an alternative to keeping records of actual operation for testing purposes, maintain a readily accessible written record of the automated testing schedule. [District Rules 4701 and 4702, 17 CCR 93115, and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
18. The permittee shall maintain monthly records of the type of fuel purchased, the amount of fuel purchased, date when the fuel was purchased, signature of the permittee who received the fuel, and signature of the fuel supplier indicating that the fuel was delivered. [District Rules 4701 and 4702, and 17 CCR 93115] Federally Enforceable Through Title V Permit
19. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 4701 and 4702, 17 CCR 93115, and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-9-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

14,579 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 34 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-10-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

14,707 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 35 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-20-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

7,184 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 45 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-21-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

7,192 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 46 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-22-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

7,180 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 47 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-23-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

7,168 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 48 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-24-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

7,151 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 49 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-25-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

7,188 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 50 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-26-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

7,192 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 51 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-27-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

7,201 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 52 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-28-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

7,188 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 53 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-29-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

7,180 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 54 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-30-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,663 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 55 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-31-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,728 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 56 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-32-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,663 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 57 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-33-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,696 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 58 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-38-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

8,590 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 63 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-39-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

8,563 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 64 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-48-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,720 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 73 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-49-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,735 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 74 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-56-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

51,486 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 108 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

***San Joaquin Valley
Air Pollution Control District***

PERMIT UNIT: N-266-57-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

51,460 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 109 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-58-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

51,446 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 110 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-59-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

51,406 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 111 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-60-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

51,446 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 112 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-61-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

51,460 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 113 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

***San Joaquin Valley
Air Pollution Control District***

PERMIT UNIT: N-266-62-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

51,433 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 114 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-63-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

51,420 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 115 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-64-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

51,446 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 116 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-65-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

51,433 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 117 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

***San Joaquin Valley
Air Pollution Control District***

PERMIT UNIT: N-266-66-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

51,460 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 118 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

***San Joaquin Valley
Air Pollution Control District***

PERMIT UNIT: N-266-67-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

51,500 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 119 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

***San Joaquin Valley
Air Pollution Control District***

PERMIT UNIT: N-266-68-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

51,700 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 120 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-69-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

51,500 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 121 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-70-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

51,500 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 122 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

***San Joaquin Valley
Air Pollution Control District***

PERMIT UNIT: N-266-71-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

51,687 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 123 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

***San Joaquin Valley
Air Pollution Control District***

PERMIT UNIT: N-266-72-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

51,741 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 124 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-73-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

51,674 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 125 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-74-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

51,741 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 126 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-75-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

51,687 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 127 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-76-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

51,714 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 128 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-77-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

44,309 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 151 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-78-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

44,327 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 152 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-79-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

44,327 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 153 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-80-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

44,370 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 154 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-81-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

44,361 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 155 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

***San Joaquin Valley
Air Pollution Control District***

PERMIT UNIT: N-266-82-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

44,309 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 156 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-83-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

44,309 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 157 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-84-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

44,327 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 158 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-85-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

44,378 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 161 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

***San Joaquin Valley
Air Pollution Control District***

PERMIT UNIT: N-266-86-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

44,356 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 162 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-87-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

44,206 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 163 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-88-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

44,361 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 164 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-89-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

44,155 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 165 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-90-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

44,206 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 166 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-91-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

44,327 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 167 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-92-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

44,344 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 168 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

***San Joaquin Valley
Air Pollution Control District***

PERMIT UNIT: N-266-93-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

44,176 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 171 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

***San Joaquin Valley
Air Pollution Control District***

PERMIT UNIT: N-266-94-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

44,335 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 172 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-95-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

44,172 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 173 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

***San Joaquin Valley
Air Pollution Control District***

PERMIT UNIT: N-266-96-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

44,361 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 174 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

***San Joaquin Valley
Air Pollution Control District***

PERMIT UNIT: N-266-97-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

44,206 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 175 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-98-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

44,155 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 176 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-99-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

44,172 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 177 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

***San Joaquin Valley
Air Pollution Control District***

PERMIT UNIT: N-266-100-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

44,206 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 178 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

***San Joaquin Valley
Air Pollution Control District***

PERMIT UNIT: N-266-101-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

73,375 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 187 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-102-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

73,373 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 188 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-103-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

72,048 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 189 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

***San Joaquin Valley
Air Pollution Control District***

PERMIT UNIT: N-266-104-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

73,336 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 197 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-105-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

73,355 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 198 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-106-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

72,031 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 199 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

***San Joaquin Valley
Air Pollution Control District***

PERMIT UNIT: N-266-113-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

60,339 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 207 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

***San Joaquin Valley
Air Pollution Control District***

PERMIT UNIT: N-266-114-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

60,158 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 208 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-115-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

60,094 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 209 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-116-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

60,090 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 210 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-117-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

60,109 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 211 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-118-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

60,076 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 212 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

***San Joaquin Valley
Air Pollution Control District***

PERMIT UNIT: N-266-119-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

60,076 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 219 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-120-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

60,010 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 220 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

***San Joaquin Valley
Air Pollution Control District***

PERMIT UNIT: N-266-121-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

60,066 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 221 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

***San Joaquin Valley
Air Pollution Control District***

PERMIT UNIT: N-266-122-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

60,109 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 222 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-123-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

60,058 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 229 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-124-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

127,903 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 250 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-125-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

127,709 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 251 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-126-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

128,223 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 252 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-127-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

128,327 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 253 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-128-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

127,566 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 254 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-129-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

128,256 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 255 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-130-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

128,493 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 256 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-131-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

127,579 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 260 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-132-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

128,016 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 261 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-133-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

127,129 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 262 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-134-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

128,290 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 263 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-135-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

128,467 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 264 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-136-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

127,768 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 265 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-137-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

128,324 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 266 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-138-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

128,511 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 270 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-139-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

127,507 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 271 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-140-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

128,647 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 272 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-141-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

128,425 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 273 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-142-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

128,639 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 274 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-143-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

128,915 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 275 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-144-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

128,290 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 276 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-145-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

128,425 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 280 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-146-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

129,372 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 281 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-147-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

128,155 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 282 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-148-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

128,425 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 283 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-149-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

128,695 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 284 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-150-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

128,670 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 285 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-151-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

128,636 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 286 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-152-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

127,738 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 290 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

***San Joaquin Valley
Air Pollution Control District***

PERMIT UNIT: N-266-153-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

129,435 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 291 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-154-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

127,535 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 292 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-155-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

23,100 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 293 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-156-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

23,100 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 294 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

***San Joaquin Valley
Air Pollution Control District***

PERMIT UNIT: N-266-157-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

23,100 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 295 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-158-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

23,100 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 296 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-159-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

23,100 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 297 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-160-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

352,002 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 301 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

***San Joaquin Valley
Air Pollution Control District***

PERMIT UNIT: N-266-161-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

350,790 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 302 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-162-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

351,769 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 303 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-163-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

351,655 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 304 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-164-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

352,067 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 305 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-165-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

351,022 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 306 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-166-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

351,141 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 307 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-167-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

351,079 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 311 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-168-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

351,724 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 312 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-169-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

351,039 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 313 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-170-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

350,496 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 314 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-171-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

351,219 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 315 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-172-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

351,521 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 316 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-173-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

351,051 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 317 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-174-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

350,760 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 321 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-175-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

350,946 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 322 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-176-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

351,267 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 323 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-177-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

351,930 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 324 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-178-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

352,374 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 325 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-179-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

351,625 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 326 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

***San Joaquin Valley
Air Pollution Control District***

PERMIT UNIT: N-266-180-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

351,374 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 327 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-181-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

351,125 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 331 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-182-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

351,178 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 332 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-183-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

349,827 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 333 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-184-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

352,011 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 334 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-185-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

350,672 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 335 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-266-186-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

352,014 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 336 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-187-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

351,229 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 337 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-188-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

351,941 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 341 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-189-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

352,833 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 342 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-190-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

351,917 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 343 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-191-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

351,965 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 344 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-192-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

351,845 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 345 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-193-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

352,592 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 346 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-194-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

353,300 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 347 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-195-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

352,592 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 401 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-196-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

351,868 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 402 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-197-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

352,116 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 403 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-198-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

351,381 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 404 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-199-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

352,556 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 405 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-200-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

352,028 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 406 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-201-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

352,291 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 411 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-202-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

350,900 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 412 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-203-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

351,876 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 413 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-204-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

351,019 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 414 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-205-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

352,127 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 415 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-206-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

352,381 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 416 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-207-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

351,750 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 421 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-208-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

351,575 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 422 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-209-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

351,991 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 423 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-210-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

351,503 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 424 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-211-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

351,404 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 425 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-212-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

352,189 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 426 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-213-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

184,614 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 501 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-214-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

184,476 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 502 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-215-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

184,682 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 503 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-216-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

185,169 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 504 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-217-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

251,301 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 505 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

***San Joaquin Valley
Air Pollution Control District***

PERMIT UNIT: N-266-218-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

251,909 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 506 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-219-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

185,400 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 511 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-220-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

185,273 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 512 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-221-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

184,262 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 513 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-222-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

185,453 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 514 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-223-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

250,885 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 515 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-224-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

250,230 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 516 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

***San Joaquin Valley
Air Pollution Control District***

PERMIT UNIT: N-266-225-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

212,399 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 521 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-226-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

211,951 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 522 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-227-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

211,775 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 523 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-228-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

212,847 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 524 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-229-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

249,902 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 525 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-230-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

251,435 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 526 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-231-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

211,653 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 531 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

***San Joaquin Valley
Air Pollution Control District***

PERMIT UNIT: N-266-232-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

211,496 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 532 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-233-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

211,198 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 533 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

***San Joaquin Valley
Air Pollution Control District***

PERMIT UNIT: N-266-234-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

212,367 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 534 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-235-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

251,482 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 535 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-236-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

250,731 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 536 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

***San Joaquin Valley
Air Pollution Control District***

PERMIT UNIT: N-266-237-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

56,046 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 601 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-238-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

55,572 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 602 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-239-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

55,824 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 603 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-240-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

55,815 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 604 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-241-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

55,778 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 611 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-242-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

55,572 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 612 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-243-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

55,825 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 613 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-244-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

55,592 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 614 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

***San Joaquin Valley
Air Pollution Control District***

PERMIT UNIT: N-266-245-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

49,395 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 621 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-246-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

49,771 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 622 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-247-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

49,226 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 623 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-248-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

49,379 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 624 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-249-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

49,755 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 631 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-250-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

49,793 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 632 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-251-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

49,208 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 633 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-252-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,054 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 634 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-253-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

49,692 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 635 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-254-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

49,397 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 636 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-255-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

49,413 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 637 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-256-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

49,535 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 638 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-257-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,734 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 641 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-258-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,638 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 642 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-259-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,321 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 643 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-260-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

3,269 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 644 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-261-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,324 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 645 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-262-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,311 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 646 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-263-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,324 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 647 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

***San Joaquin Valley
Air Pollution Control District***

PERMIT UNIT: N-266-264-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,766 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 651 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-265-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,703 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 652 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-266-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,311 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 653 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-267-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,317 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 654 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-268-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,313 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 655 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-269-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,317 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 656 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-270-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,314 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 657 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-271-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,740 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 661 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-272-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,740 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 662 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

***San Joaquin Valley
Air Pollution Control District***

PERMIT UNIT: N-266-273-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,740 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 663 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-274-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,740 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 664 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-275-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,722 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 665 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-276-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,682 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 666 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-277-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,676 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 671 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-278-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,734 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 672 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-279-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,722 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 673 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-280-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,728 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 674 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-281-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,734 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 675 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

***San Joaquin Valley
Air Pollution Control District***

PERMIT UNIT: N-266-282-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,663 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 676 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-283-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,651 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 681 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-284-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,690 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 682 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-285-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,645 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 683 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-286-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,689 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 684 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-287-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,600 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 685 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

***San Joaquin Valley
Air Pollution Control District***

PERMIT UNIT: N-266-288-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,715 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 686 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-289-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,238 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 691 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-290-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,090 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 692 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

***San Joaquin Valley
Air Pollution Control District***

PERMIT UNIT: N-266-291-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,105 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 693 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-292-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,114 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 694 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-293-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,107 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 695 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

***San Joaquin Valley
Air Pollution Control District***

PERMIT UNIT: N-266-294-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

44,361 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 801 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-295-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

44,412 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 802 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-296-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

44,404 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 803 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

***San Joaquin Valley
Air Pollution Control District***

PERMIT UNIT: N-266-297-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

44,395 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 804 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-298-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

44,240 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 805 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

***San Joaquin Valley
Air Pollution Control District***

PERMIT UNIT: N-266-299-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

44,206 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 806 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-266-300-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

44,257 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 807 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-301-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

49,362 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 808 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-302-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

44,413 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 809 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-303-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

44,395 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 810 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-304-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

44,370 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 811 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-266-305-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

44,328 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 812 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-306-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,190 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 813 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-307-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,087 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 814 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

***San Joaquin Valley
Air Pollution Control District***

PERMIT UNIT: N-266-308-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,910 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 821 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-309-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,921 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 822 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-310-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,930 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 823 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-311-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,553 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 824 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-312-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,940 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 825 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-313-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,882 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 826 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-314-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,940 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 827 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-315-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,900 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 828 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-316-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,910 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 829 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-317-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,911 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 830 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

***San Joaquin Valley
Air Pollution Control District***

PERMIT UNIT: N-266-318-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,966 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 831 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

***San Joaquin Valley
Air Pollution Control District***

PERMIT UNIT: N-266-319-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,872 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 832 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-320-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,271 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 833 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-321-5

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,238 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 834 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE.

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine or distilled spirits storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine or distilled spirits storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine or distilled spirits stored in this tank shall not exceed 97 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine or distilled spirits storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1] Federally Enforceable Through Title V Permit
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine or distilled spirits storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine or distilled spirits storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine or distilled spirits storage operations may be determined using the total annual wine or distilled spirits throughput and a single storage emissions factor based on the average ethanol content of the annual wine or distilled spirits throughput; or using the throughputs for different batches of wine or distilled spirits and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-322-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,892 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 841 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-323-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,706 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 842 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-324-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,747 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 843 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-325-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,706 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 844 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-326-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

51,097 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 845 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-327-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

80,687 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 846 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-328-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,716 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 847 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

***San Joaquin Valley
Air Pollution Control District***

PERMIT UNIT: N-266-329-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,745 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 848 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-330-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,892 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 849 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-331-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,706 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 850 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-332-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,706 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 851 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-333-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,891 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 852 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-334-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,103 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 853 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-335-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,060 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 854 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-338-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

49,422 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1001 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-339-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

49,574 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1002 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-340-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

49,239 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1003 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-341-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

49,473 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1004 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

***San Joaquin Valley
Air Pollution Control District***

PERMIT UNIT: N-266-342-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

49,416 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1005 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-343-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

49,415 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1006 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-344-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

49,414 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1011 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-345-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

49,424 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1012 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-346-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

49,433 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1013 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-347-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

49,459 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1014 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-348-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

49,597 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1015 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-349-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

49,435 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1016 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-350-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,565 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1021 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-351-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,655 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1022 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

***San Joaquin Valley
Air Pollution Control District***

PERMIT UNIT: N-266-352-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,573 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1023 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

***San Joaquin Valley
Air Pollution Control District***

PERMIT UNIT: N-266-353-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,565 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1024 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-354-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,573 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1025 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-355-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,628 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1026 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

***San Joaquin Valley
Air Pollution Control District***

PERMIT UNIT: N-266-356-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,655 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1027 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-357-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,655 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1031 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-358-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,565 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1032 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-266-359-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,565 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1033 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-360-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,647 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1034 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

***San Joaquin Valley
Air Pollution Control District***

PERMIT UNIT: N-266-361-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,557 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1035 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-362-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,655 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1036 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-363-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,565 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1037 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-364-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,565 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1041 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-365-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,573 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1042 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-366-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,557 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1043 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-367-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,655 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1044 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

***San Joaquin Valley
Air Pollution Control District***

PERMIT UNIT: N-266-368-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,557 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1045 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-369-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,573 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1046 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-370-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,655 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1047 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-371-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,548 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1051 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-372-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,655 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1052 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-373-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,647 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1053 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-374-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,655 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1054 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-375-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,655 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1055 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-376-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,672 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1056 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-377-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,573 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1057 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-378-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,664 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1061 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-379-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,604 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1062 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-380-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,675 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1063 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-381-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,651 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1064 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-382-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,644 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1065 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-383-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,593 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1066 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-384-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,593 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1067 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-385-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,589 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1068 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-386-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,593 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1069 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-387-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,522 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1070 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-388-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,640 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1081 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-389-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,649 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1082 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-390-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,707 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1083 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-391-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,644 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1084 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-392-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,644 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1085 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-393-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,569 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1086 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-394-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,644 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1087 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-395-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,712 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1088 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-396-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,720 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1089 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-397-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,649 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1090 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-398-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

3,613 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1091 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-399-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

3,613 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1092 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-400-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

3,613 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1093 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

***San Joaquin Valley
Air Pollution Control District***

PERMIT UNIT: N-266-401-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,856 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1094 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-402-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,821 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1095 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-403-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,817 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1096 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-404-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,871 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1097 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-405-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,821 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1098 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

***San Joaquin Valley
Air Pollution Control District***

PERMIT UNIT: N-266-406-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,853 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1099 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-407-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1101 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-408-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1102 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-409-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1103 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-410-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1104 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-411-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1105 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-412-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1106 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-413-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1107 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-414-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,544 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1108 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-415-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1109 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-416-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1110 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-417-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1111 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-418-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1121 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-419-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1122 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-420-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1123 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-421-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1124 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-422-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1125 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-423-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1126 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-424-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1127 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-425-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1128 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-426-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1129 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-427-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1130 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-428-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1131 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-429-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1141 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-430-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1142 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-431-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1143 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-432-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1144 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-433-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1145 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-434-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1146 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-435-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1147 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley *Air Pollution Control District*

PERMIT UNIT: N-266-436-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1148 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

***San Joaquin Valley
Air Pollution Control District***

PERMIT UNIT: N-266-437-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

3,613 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1149 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-438-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

3,613 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1150 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-439-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

3,613 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1151 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-440-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

3,613 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1152 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

***San Joaquin Valley
Air Pollution Control District***

PERMIT UNIT: N-266-441-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

88,432 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1201 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-442-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

88,432 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1202 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

***San Joaquin Valley
Air Pollution Control District***

PERMIT UNIT: N-266-443-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

88,471 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1203 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-444-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

88,247 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1204 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

***San Joaquin Valley
Air Pollution Control District***

PERMIT UNIT: N-266-445-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

101,348 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1205 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-446-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

102,041 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1206 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-447-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

101,637 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1207 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-448-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

101,750 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1208 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-449-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

88,281 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1211 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-450-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

88,526 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1212 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-451-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

88,264 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1213 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-452-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

88,459 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1214 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-453-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

101,234 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1215 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley *Air Pollution Control District*

PERMIT UNIT: N-266-454-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

101,638 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1216 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-455-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

102,042 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1217 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-456-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

101,703 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1218 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-457-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

49,867 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1221 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-458-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,030 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1222 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-459-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

49,869 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1223 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-460-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

49,854 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1224 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-461-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

49,633 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1225 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-462-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

49,610 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1226 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-463-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,050 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1227 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-464-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,087 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1228 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-465-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

49,820 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1231 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-466-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

49,835 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1232 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-467-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,078 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1233 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-468-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

49,836 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1234 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-469-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

49,640 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1235 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-470-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

49,603 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1236 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-471-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,080 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1237 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-472-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,093 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1238 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-473-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,422 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1241 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

***San Joaquin Valley
Air Pollution Control District***

PERMIT UNIT: N-266-474-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,512 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1242 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-475-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,381 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1243 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-476-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,495 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1244 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-477-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,403 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1245 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

***San Joaquin Valley
Air Pollution Control District***

PERMIT UNIT: N-266-478-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,501 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1246 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-479-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,422 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1247 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-480-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,414 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1248 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-266-481-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,414 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1249 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

***San Joaquin Valley
Air Pollution Control District***

PERMIT UNIT: N-266-482-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,299 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1250 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

***San Joaquin Valley
Air Pollution Control District***

PERMIT UNIT: N-266-483-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,532 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1251 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-484-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,633 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1252 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-485-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,565 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1253 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-486-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,442 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1254 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-487-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,403 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1255 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-488-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,403 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1256 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-489-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,186 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1257 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-490-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,411 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1258 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-491-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,299 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1259 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-492-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,403 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1260 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-493-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,318 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1261 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-494-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,318 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1262 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-495-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,318 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1263 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-496-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,318 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1264 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-497-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,318 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1265 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-498-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,318 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1266 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-499-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,458 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1267 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-500-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,458 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1268 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

***San Joaquin Valley
Air Pollution Control District***

PERMIT UNIT: N-266-501-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,425 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1269 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-502-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,425 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1270 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-503-6

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

5.978 MMBTU/HR FULTON NATURAL GAS-FIRED BOILER WITH A FULTON MODEL 102347 LOW NOX BURNER

PERMIT UNIT REQUIREMENTS

1. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
3. The unit shall only be fired on PUC-quality natural gas. [District Rules 2201, 4201, 4320, and 4801] Federally Enforceable Through Title V Permit
4. This boiler shall be equipped with an operational, non-resettable, totalizing fuel flow meter that records the quantity of fuel into this boiler. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Heat input rate to this unit shall not exceed 125 MMBtu in any one day (equal to use of 125,000 scf/day of natural gas). [District Rule 2201] Federally Enforceable Through Title V Permit
6. NOx emissions shall not exceed 9 ppmvd @ 3% O₂ (0.011 lb/MMBtu) referenced as NO₂. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
7. CO emissions shall not exceed 50 ppmvd @ 3% O₂ (0.037 lb/MMBtu). [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
8. SOx emissions shall not exceed 0.00285 lb/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
9. PM₁₀ emissions shall not exceed 0.003 lb/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
10. VOC emissions shall not exceed 0.004 lb/MMBtu (referenced as methane). [District Rule 2201] Federally Enforceable Through Title V Permit
11. Source testing to measure NOx and CO emissions shall be conducted at least once every twelve months. After demonstrating compliance on two consecutive annual source tests, the unit shall be tested not less than once every thirty-six months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve months. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
12. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
13. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
14. NOx emissions for source test purposes shall be determined using EPA Method 7E or ARB Method 100 on a ppmv basis, or EPA Method 19 on a heat input basis. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

15. CO emissions for source test purposes shall be determined using EPA Method 10 or ARB Method 100. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
16. Stack gas oxygen (O₂) shall be determined using EPA Method 3 or 3A or ARB Method 100. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
17. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
18. The higher heating value (HHV) of the fuel shall be certified by third-party fuel supplier or determined using ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels, or an alternative method approved by EPA and the District. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
19. Fuel sulfur content shall be determined using EPA Method 11 or Method 15, as appropriate. [District Rule 4320] Federally Enforceable Through Title V Permit
20. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
21. The results of each source test shall be submitted to the District within 60 days after completion of the source test. [District Rule 1081] Federally Enforceable Through Title V Permit
22. The permittee shall monitor and record the stack concentration of NO_x, CO, and O₂ at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
23. If either the NO_x or CO concentrations corrected to 3% O₂, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of performing the notification and testing required by this condition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
24. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
25. The permittee shall maintain records of: (1) the date and time of NO_x, CO, and O₂ measurements, (2) the O₂ concentration in percent and the measured NO_x and CO concentrations corrected to 3% O₂, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

26. Permittee shall determine sulfur content of combusted gas annually or shall demonstrate that the combusted gas is provided from a PUC or FERC regulated source. [District Rules 1081 and 4320] Federally Enforceable Through Title V Permit
27. The permittee shall maintain daily records of the fuel combusted (scf/day) in this boiler. [District Rule 2201] Federally Enforceable Through Title V Permit
28. All records shall be maintained and retained on-site for a period of at least 5 years and shall be made available for District inspection upon request. [District Rules 1070, 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
29. An Emission Control Plan and any Authority to Construct (ATC) application required for this unit for compliance with the applicable Tier 2 emission limits of District Rules 4306 and 4320 shall be submitted to the APCO pursuant to Section 6.4 of each rule. The owner or operator of this unit shall comply with all applicable deadlines in Section 7.0 of District Rules 4306 and 4320, including for submission of the Emission Control Plan and any required ATC application, and full compliance with District Rules 4306 and 4320. [District Rules 4306 and 4320] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-569-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,184 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1229 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-570-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,184 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1230 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

***San Joaquin Valley
Air Pollution Control District***

PERMIT UNIT: N-266-571-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,184 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1239 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-572-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,184 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1240 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

***San Joaquin Valley
Air Pollution Control District***

PERMIT UNIT: N-266-573-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1271 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-574-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1272 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-575-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1273 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-576-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1274 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

***San Joaquin Valley
Air Pollution Control District***

PERMIT UNIT: N-266-577-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1401 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

***San Joaquin Valley
Air Pollution Control District***

PERMIT UNIT: N-266-578-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1402 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-579-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1403 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-580-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1404 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-581-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1405 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

***San Joaquin Valley
Air Pollution Control District***

PERMIT UNIT: N-266-582-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1406 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-583-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1407 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-584-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1408 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-585-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1409 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-586-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1410 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-587-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1411 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-588-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1412 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-589-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1413 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

***San Joaquin Valley
Air Pollution Control District***

PERMIT UNIT: N-266-590-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1414 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-591-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1415 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-592-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1416 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-593-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1417 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

***San Joaquin Valley
Air Pollution Control District***

PERMIT UNIT: N-266-594-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1418 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-595-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1419 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-596-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1420 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-597-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1421 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-599-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1422 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-600-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1423 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

***San Joaquin Valley
Air Pollution Control District***

PERMIT UNIT: N-266-601-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1424 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-602-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1425 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-603-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1426 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-604-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1427 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

***San Joaquin Valley
Air Pollution Control District***

PERMIT UNIT: N-266-605-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1428 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-606-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1431 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

***San Joaquin Valley
Air Pollution Control District***

PERMIT UNIT: N-266-607-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1432 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-608-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1433 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-609-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1434 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-610-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1435 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-611-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1436 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-612-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1437 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-613-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1438 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-614-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

103,660 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1441 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

***San Joaquin Valley
Air Pollution Control District***

PERMIT UNIT: N-266-615-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

103,660 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1442 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

***San Joaquin Valley
Air Pollution Control District***

PERMIT UNIT: N-266-616-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

103,660 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1443 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

***San Joaquin Valley
Air Pollution Control District***

PERMIT UNIT: N-266-617-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

103,660 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1444 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-618-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

103,660 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1451 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

***San Joaquin Valley
Air Pollution Control District***

PERMIT UNIT: N-266-619-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

103,660 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1452 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-620-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

103,660 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1453 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

***San Joaquin Valley
Air Pollution Control District***

PERMIT UNIT: N-266-621-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

103,660 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1454 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-622-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

103,660 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1461 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

***San Joaquin Valley
Air Pollution Control District***

PERMIT UNIT: N-266-623-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

103,660 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1462 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

***San Joaquin Valley
Air Pollution Control District***

PERMIT UNIT: N-266-624-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

103,660 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1463 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-625-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

103,660 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1464 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-626-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

103,660 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1465 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-627-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

103,660 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1466 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

***San Joaquin Valley
Air Pollution Control District***

PERMIT UNIT: N-266-628-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

103,660 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1471 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

***San Joaquin Valley
Air Pollution Control District***

PERMIT UNIT: N-266-629-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

103,660 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1472 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-630-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

103,660 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1473 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

***San Joaquin Valley
Air Pollution Control District***

PERMIT UNIT: N-266-631-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

103,660 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1474 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

***San Joaquin Valley
Air Pollution Control District***

PERMIT UNIT: N-266-632-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

103,660 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1475 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

***San Joaquin Valley
Air Pollution Control District***

PERMIT UNIT: N-266-633-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

103,660 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1476 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-634-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

74,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 185 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-635-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

74,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 186 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-636-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

74,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 193 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-637-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

74,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 194 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-638-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

74,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 195 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-639-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

74,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 196 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-640-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

ORGANIC WASTE AND FEEDSTOCK MATERIAL RECEIVING, STORAGE, AND MIXING OPERATION.

PERMIT UNIT REQUIREMENTS

1. All materials for processing shall be maintained adequately moist to prevent visible emissions in excess of 20% opacity. [District Rule 4101] Federally Enforceable Through Title V Permit
2. The permittee is allowed to receive the following wastes for the composting operation: green waste, food waste, and construction wood waste. Green waste is defined as any organic waste material generated from gardening, agriculture, or landscaping activities including, but not limited to grass clippings, leave, tree and shrub trimmings, and plant remains. Food waste is defined as table scraps, vegetable and fruit peelings, meat, bones and fish, egg shells, solid dairy products, coffee grounds, bread and toast, paper waste including, but not limited to, napkins, towels, plates, coffee filters, and tea bags. Construction wood waste is defined as any untreated wood materials, including but not limited to, lumber, paper, and cardboard from construction. [District Rule 2010] Federally Enforceable Through Title V Permit
3. The permittee is prohibited to receive the following wastes for the composting operation: biosolids, animal manure, and poultry litter. Biosolids is defined as organic material resulting from the treatment os sewage sludge or wastewater. Animal manure is defines as non-human animal excretions and waste, including, but not limited to, dried solids and urine from cows, cattle, or swine. Poultry litter is defined as poultry excretions and waste, including, but not limited to, dried solids and urine from chickens, turkeys, geese, or ducks. [District Rule 2010] Federally Enforceable Through Title V Permit
4. The quantity of organic waste materials received at this facility shall not exceed 900 wet-tons in any single day and 82,000 wet tons in any one calendar year. For the purposes of this permit, organic waste material is considered to be green waste, food waste, and construction wood waste. [District Rules 2201 and 4566] Federally Enforceable Through Title V Permit
5. PM10 emissions from the receiving, handling, and mixing of the organic waste materials shall not exceed 0.00167 lb-PM10/wet-ton of material received and processed. [District Rule 2201] Federally Enforceable Through Title V Permit
6. VOC emissions from the storage and processing of the organic waste materials shall not exceed 10.63 lb-VOC/wet-ton of material stored and processed. [District Rule 2201] Federally Enforceable Through Title V Permit
7. NH3 emissions from the storage and processing of the organic waste materials shall not exceed 3.18 lb-NH3/wet-ton of material stored and processed. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The operator shall perform one of the following to organic materials within 10 days of receipt at the facility to satisfy the stockpile requirements: (a). Remove the organic material from the facility; (b). Place the organic material in the active-phase composting windrow and start active phase composting; (c). Cover the organic material with a waterproof cover that have at least a six-foot overlap of adjacent sheets and be securely anchored. [District Rule 4566] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

9. A daily operations log shall be maintained and shall include the following: (a) The date, type, and weight (in wet tons) of each organic material received; (b). The date each stockpile was initially formed; (c). The date and action taken on each stockpile to satisfy the stockpile requirements; (d). Total quantity and type of each organic waste material stored for composting (in wet tons); (e). Total quantity and type of each organic waste material mixed for composting (in wet tons); and (f). Any other information necessary to demonstrate compliance with Rule 4566. [District Rules 1070 & 4566] Federally Enforceable Through Title V Permit
10. A cumulative annual log shall be maintained and shall indicate the total quantity and type of each organic waste material received (in wet tons). The records shall be updated at least monthly. [District Rule 1070] Federally Enforceable Through Title V Permit
11. All records shall be maintained and retained on-site for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 1070 & 4566] Federally Enforceable Through Title V Permit
12. This permit does not authorize the facility to operate without the required permits from other local, state or federal agency and does not authorize the violation of any conditions established for this facility in the Conditional Use Permit (CUP), Special Use Permit (SUP), Site Approval, Site Plan Review (SPR), or other approval documents issued by a local, state or federal agency. [District Rules 2070 and 2080, and Public Resources Code 21000-21177: California Environmental Quality Act] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-641-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

OPEN WINDROW ACTIVE AND CURING PHASE ORGANIC MATERIAL COMPOSTING OPERATION WITH AN INDEPENDENT WATERING SYSTEM SERVING THE ACTIVE-PHASE COMPOSTING WINDROW PILES.

PERMIT UNIT REQUIREMENTS

1. All materials for processing shall be maintained adequately moist to prevent visible emissions in excess of 20% opacity. [District Rule 4101] Federally Enforceable Through Title V Permit
2. PM10 emissions from the organic material composting operation shall not exceed 0.6 pounds in any single day. Compliance with this condition shall be demonstrated using the following equation: $PM10 \text{ Emissions (lb/day)} = 0.00066 \text{ lb-PM10/wet-ton} \times \text{Total daily quantity of material transferred from the feedstock piles to active-phase composting windrows (in wet-tons/day)}$. [District Rule 2201] Federally Enforceable Through Title V Permit
3. VOC emissions from the organic material composting operation shall not exceed 360.2 pounds in any single day. Compliance with this condition shall be demonstrated using the following equation: $VOC \text{ Emissions (lb/day)} = 0.06966 \text{ lb-VOC/wet-ton} \times \text{Total daily quantity of active phase composting piles utilized onsite (in wet-tons/day)} + 0.0095 \text{ lb-VOC/wet-ton} \times \text{Total quantity of curing phase composting piles utilized onsite (in wet-tons/day)}$. [District Rule 2201] Federally Enforceable Through Title V Permit
4. NH3 emissions from the organic material composting operation shall not exceed 86.0 pounds in any single day. Compliance with this condition shall be demonstrated using the following equation: $NH3 \text{ Emissions (lb/day)} = 0.017 \text{ lb-NH3/wet-ton} \times \text{Total daily quantity of active phase composting piles utilized onsite (in wet-tons/day)} + 0.0019 \text{ lb-NH3/wet-ton} \times \text{Total daily quantity of curing phase composting piles utilized onsite (in wet-tons/day)}$. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The total quantity of organic materials composted shall not exceed 82,000 wet tons in any one calendar year. [District Rules 2201 & 4566] Federally Enforceable Through Title V Permit
6. The operator shall implement at least three turns of each organic material composting windrow during the active-phase of the composting process. [District Rule 4566]
7. The operator shall install, maintain, and utilize an independent watering system to apply water to the surface of each active-phase composting windrow prior to turning. The operator shall test each windrow within three hours before turning for adequate water by taking a sample of the organic material in the windrow and passing a "Ball Test". The "Ball Test" is performed by taking a sample of the compostable material from at least three inches below the surface, between the vertical midpoint and the peak of the windrow and forming the sample into a ball using hand pressure. There should be at least enough water in the material to form a ball when compressed by hand, but the ball may break when tapped. If the material cannot form a ball or crumbles during the ball test, then application of additional water to the windrow prior to turning is required until the material passes the ball test. If a rain event occurs prior to turning the windrow, application of additional water to the surface of the windrow will not be required if the material passes the ball test as previously described. [District Rule 4566] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

8. A daily operations log shall be maintained and shall include the following: (a). The date and time the organic material from the windrow was tested for adequate water content using the "Ball Test" and indicate if the material passed the ball test. If the windrow material did not pass the ball test indicate the corrective action taken; (b). The date and time each windrow was turned; (c). Total quantity of organic material transferred from the feedstock piles to the active-phase composting windrows (in wet tons); (d). Total quantity of active phase composting piles utilized onsite (in wet tons); (e). Total quantity of curing phase composting piles utilized onsite (in wet tons); and (f). Any other information necessary to demonstrate compliance with Rule 4566. [District Rules 1070 & 4566] Federally Enforceable Through Title V Permit
9. A cumulative annual log shall be maintained and shall include the following: (a). Total quantity of active-phase composting piles utilized onsite (in wet tons); (b). Total quantity of curing phase composting piles utilized onsite (in wet tons). The records shall be updated at least monthly. [District Rule 1070] Federally Enforceable Through Title V Permit
10. All records shall be maintained and retained on-site for a period of at least 5 years and shall be made available for District inspection upon request. [District Rules 1070 & 4566] Federally Enforceable Through Title V Permit
11. This permit does not authorize the facility to operate without the required permits from other local, state or federal agency and does not authorize the violation of any conditions established for this facility in the Conditional Use Permit (CUP), Special Use Permit (SUP), Site Approval, Site Plan Review (SPR), or other approval documents issued by a local, state or federal agency. [District Rules 2070 and 2080, and Public Resources Code 21000-21177: California Environmental Quality Act] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-642-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:
FINISHED COMPOST LOADOUT OPERATION.

DRAFT

PERMIT UNIT REQUIREMENTS

1. All materials for processing shall be maintained adequately moist to prevent visible emissions in excess of 20% opacity. [District Rule 4101] Federally Enforceable Through Title V Permit
2. A daily log shall be maintained and shall indicate the number of vehicles used to load out finished compost and the total quantity of finished compost loaded out (in wet tons). [District Rule 1070 and San Joaquin County Rule 107] Federally Enforceable Through Title V Permit
3. A cumulative annual log shall be maintained and shall indicate the total quantity of finished compost loaded out (in wet tons). The records shall be updated at least monthly. [District Rule 1070 and San Joaquin County Rule 107] Federally Enforceable Through Title V Permit
4. All records shall be maintained and retained on-site for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 1070 and San Joaquin County Rule 107] Federally Enforceable Through Title V Permit
5. This permit does not authorize the facility to operate without the required permits from other local, state, or federal agency and does not authorize the violation of any conditions established for this facility in the Conditional Use Permit (CUP), Special Use Permit (SUP), Site Approval, Site Plan Review (SPR), or other approval documents issued by a local, state, or federal agency. [District Rules 2070 and 2080] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-643-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B22 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

***San Joaquin Valley
Air Pollution Control District***

PERMIT UNIT: N-266-644-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B24 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-645-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B19 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-646-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B20 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-647-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B21 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-648-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B23 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-649-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

14,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B08 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-650-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

14,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B09 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-651-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

14,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B17 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-652-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

14,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B18 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-653-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,700 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B06 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-654-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,700 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B07 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-655-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,700 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B15 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-656-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,700 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B16 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-657-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

8,500 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B04 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-658-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

8,500 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B05 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-659-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

8,500 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B13 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-660-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

8,500 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B14 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-661-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,200 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B01 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-662-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,200 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B02 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-663-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,200 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B03 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-664-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,200 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B10 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-665-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,200 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B11 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-666-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,200 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B12 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-667-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

200,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 352 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-668-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

200,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 353 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-669-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

200,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 354 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-670-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

200,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 355 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-671-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

200,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 356 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-672-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

200,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 362 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-673-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

200,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 363 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-674-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

200,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 364 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-675-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

200,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 365 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-676-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

200,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 366 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-678-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

70,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 712 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-679-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

70,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 714 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-680-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

70,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 715 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-681-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

70,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 716 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-682-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

70,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 717 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-683-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

70,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 718 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-684-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

70,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 719 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-685-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

70,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 720 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-686-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

70,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 721 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-687-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

70,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 722 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-688-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

70,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 723 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-689-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

70,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 724 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-690-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

70,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 725 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-691-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

70,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 726 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-692-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

70,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 727 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-693-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

70,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 728 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-694-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

70,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 729 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-695-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

70,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 730 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-696-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

70,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 731 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-697-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

70,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 733 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-698-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1507 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-699-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1508 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-700-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1509 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-701-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1510 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-702-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1517 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-703-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1518 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-704-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1519 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-705-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1520 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-706-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1527 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-707-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1528 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-708-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1529 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-709-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1530 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-710-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1537 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-711-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1538 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-712-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1539 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-713-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1540 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-714-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1547 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-715-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1548 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-716-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1549 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-717-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1550 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-718-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1557 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-719-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1558 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-720-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1559 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-721-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1560 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-722-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,000 GALLON, INSULATED, STAINLESS STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 2501 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-723-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,000 GALLON, INSULATED, STAINLESS STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 2502 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-724-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,000 GALLON, INSULATED, STAINLESS STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 2503 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-725-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,000 GALLON, INSULATED, STAINLESS STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 2504 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-726-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,000 GALLON, INSULATED, STAINLESS STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 2511 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-727-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,000 GALLON, INSULATED, STAINLESS STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 2512 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-728-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,000 GALLON, INSULATED, STAINLESS STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 2513 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-729-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,000 GALLON, INSULATED, STAINLESS STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 2514 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-730-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

13,000 GALLON, INSULATED, STAINLESS STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1321 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-731-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

13,000 GALLON, INSULATED, STAINLESS STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1322 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-732-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

13,000 GALLON, INSULATED, STAINLESS STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1323 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-733-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

13,000 GALLON, INSULATED, STAINLESS STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1324 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-734-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

13,000 GALLON, INSULATED, STAINLESS STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1325 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-735-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

13,000 GALLON, INSULATED, STAINLESS STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1326 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-736-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

13,000 GALLON, INSULATED, STAINLESS STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1327 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-737-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

13,000 GALLON, INSULATED, STAINLESS STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1328 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-738-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

7,000 GALLON, INSULATED, STAINLESS STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1314 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-739-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

7,000 GALLON, INSULATED, STAINLESS STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1315 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-740-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

7,000 GALLON, INSULATED, STAINLESS STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1319 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-741-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

7,000 GALLON, INSULATED, STAINLESS STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1320 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-742-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK
1505 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-743-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK
1506 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-744-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK
1515 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-745-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK
1516 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-746-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK
1525 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-747-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK
1526 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-748-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK
1536 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-749-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK
1535 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-750-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

60,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 230
EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-751-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

60,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 231
EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-752-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

60,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 232
EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-753-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

60,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 233
EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-754-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

60,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 234
EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-755-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

60,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 235
EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-756-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

60,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 236
EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-757-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

60,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 237
EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-758-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

60,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 239
EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-759-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

60,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 243
EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-760-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 2505
EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-761-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 2506 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-762-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 2515
EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-763-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 2516 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-764-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

13,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1329
EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-765-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

13,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1330
EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-766-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

13,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1331
EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-767-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

13,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1332
EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-768-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

13,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1333
EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-769-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

13,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1334
EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-770-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

13,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1335
EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-771-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

13,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1336
EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-772-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

7,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1312
EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-773-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

7,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1313
EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-774-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

7,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1317
EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-775-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

7,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1318
EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-776-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON (OR EQUIVALENT) WINE STORAGE TANK (TANK #1545) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed ten times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from permit units N-266-776 through -783, calculated on a rolling 12-month total basis, shall not exceed 5,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
13. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
14. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-777-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON (OR EQUIVALENT) WINE STORAGE TANK (TANK #1546) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed ten times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from permit units N-266-776 through -783, calculated on a rolling 12-month total basis, shall not exceed 5,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
13. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
14. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-778-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

60,000 GALLON (OR EQUIVALENT) WINE STORAGE TANK (TANK #242) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed ten times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from permit units N-266-776 through -783, calculated on a rolling 12-month total basis, shall not exceed 5,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
13. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
14. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-779-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

60,000 GALLON (OR EQUIVALENT) WINE STORAGE TANK (TANK #238) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed ten times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from permit units N-266-776 through -783, calculated on a rolling 12-month total basis, shall not exceed 5,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
13. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
14. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-780-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

60,000 GALLON (OR EQUIVALENT) WINE STORAGE TANK (TANK #240) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed ten times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from permit units N-266-776 through -783, calculated on a rolling 12-month total basis, shall not exceed 5,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
13. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
14. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-781-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

60,000 GALLON (OR EQUIVALENT) WINE STORAGE TANK (TANK #241) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed ten times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from permit units N-266-776 through -783, calculated on a rolling 12-month total basis, shall not exceed 5,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
13. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
14. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-782-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

60,000 GALLON (OR EQUIVALENT) WINE STORAGE TANK (TANK #244) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed ten times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from permit units N-266-776 through -783, calculated on a rolling 12-month total basis, shall not exceed 5,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
13. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
14. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-783-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

60,000 GALLON (OR EQUIVALENT) WINE STORAGE TANK (TANK #245) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed ten times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from permit units N-266-776 through -783, calculated on a rolling 12-month total basis, shall not exceed 5,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
13. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
14. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-784-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON NOMINAL (154,433 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1502) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-785-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON NOMINAL (154,443 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1503) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-786-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON NOMINAL (153,888 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1504) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The nominal tank dimensions are 25 feet in diameter and 40 feet in height with a proposed volume of 154,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
2. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
5. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
8. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
14. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
17. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-787-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON NOMINAL (153,785 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1511) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-788-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON NOMINAL (154,308 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1512) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-789-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON NOMINAL (154,435 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1513) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-790-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON NOMINAL (153,842 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1514) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-791-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON NOMINAL (153,537 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1521) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-792-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON NOMINAL (153,932 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1522) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-793-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON NOMINAL (153,842 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1523) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-794-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON NOMINAL (153,986 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1524) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-795-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON NOMINAL (153,365 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK # (1531) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-796-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON NOMINAL (154,523 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1532) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-797-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON NOMINAL (154,208 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1533) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-798-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON NOMINAL (154,066 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1534) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-799-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON NOMINAL (153,935 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1541) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-800-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON NOMINAL (154,107 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1542) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-801-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON NOMINAL (153,458 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1543) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-802-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON NOMINAL (153,940 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1544) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-803-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON NOMINAL (154,170 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1551) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-804-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON NOMINAL (154,342 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1552) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-805-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON NOMINAL (153,842 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1553) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-806-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

103,000 GALLON NOMINAL (103,315 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1161) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-807-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

103,000 GALLON NOMINAL (103,315 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1162) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-808-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

103,000 GALLON NOMINAL (103,826 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1163) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-809-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

103,000 GALLON NOMINAL (103,705 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1164) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley
Air Pollution Control District*

PERMIT UNIT: N-266-810-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

103,000 GALLON NOMINAL (103,477 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1171) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-811-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

103,000 GALLON NOMINAL (103,712 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1172) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-812-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

103,000 GALLON NOMINAL (103,351 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1173) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-813-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

103,000 GALLON NOMINAL (103,302 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1174) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-814-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

103,000 GALLON NOMINAL (103,603 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1181) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-815-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

103,000 GALLON NOMINAL (103,480 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1182) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

***San Joaquin Valley
Air Pollution Control District***

PERMIT UNIT: N-266-816-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

103,000 GALLON NOMINAL (103,508 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1183) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

***San Joaquin Valley
Air Pollution Control District***

PERMIT UNIT: N-266-817-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

103,000 GALLON NOMINAL (102,777 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1184) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-818-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

103,000 GALLON NOMINAL (103,408 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1191) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-819-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

103,000 GALLON NOMINAL (103,088 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1192) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-820-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

103,000 GALLON NOMINAL (102,901 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1193) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

***San Joaquin Valley
Air Pollution Control District***

PERMIT UNIT: N-266-821-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

103,000 GALLON NOMINAL (103,826 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1194) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-950-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

DIATOMACEOUS EARTH (DE) MATERIAL RECEIVING, STORAGE, AND TRANSFER OPERATION CONSISTING OF ONE 8,200 CUBIC FOOT STORAGE SILO SERVED BY FOUR DYNAMIC AIR MODEL MODU-KLEEN SERIES 343/200 BIN VENT FILTERS, AND THREE ENCLOSED HOPPERS EACH SERVED BY A DYNAMIC AIR MODEL MODU-KLEEN SERIES 343/200 BIN VENT FILTER

PERMIT UNIT REQUIREMENTS

1. The bin vent filter shall be maintained and operated according to manufacturer's specifications. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The bin vent filter cleaning frequency and duration shall be adjusted to optimize the control efficiency. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Emissions shall not exceed 0.00086 lb PM10 per ton of DE processed. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The maximum throughput for the receiving/pre-cleaning operation shall not exceed 50 tons of DE per day. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The maximum throughput for the transfer to the hoppers shall not exceed 50 tons of DE per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
7. Records of all maintenance of the bin vent filters, including all change outs of filter media, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Daily records of DE processed shall be maintained, retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-952-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

250 BHP (INTERMITTENT) JOHN DEERE MODEL 6068HFC48 TIER 3 CERTIFIED DIESEL-FIRED EMERGENCY IC ENGINE POWERING A FIREWATER PUMP

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. This engine shall be equipped with a non-resettable hour meter with a minimum display capability of 9,999 hours, unless the District determines that a non-resettable hour meter with a different minimum display capability is appropriate in consideration of the historical use of the engine and the owner or operator's compliance history. [District Rules 4701 and 4702, 17 CCR 93115, and 40 CFR Part 60 Subpart IIII] Federally Enforceable Through Title V Permit
3. Only CARB certified diesel fuel containing not more than 0.0015% sulfur by weight shall be used. [District Rules 2201 and 4801, 17 CCR 93115, and 40 CFR Part 60 Subpart IIII] Federally Enforceable Through Title V Permit
4. Emissions from this IC engine shall not exceed any of the following limits: 2.47 g-NOx/bhp-hr, 0.45 g-CO/bhp-hr, or 0.08 g-VOC/bhp-hr. [District Rules 2201 and 4801, 17 CCR 93115, and 40 CFR 60 Subpart IIII] Federally Enforceable Through Title V Permit
5. Emissions from this IC engine shall not exceed 0.07 g-PM10/bhp-hr based on USEPA certification using ISO 8178 test procedure. [District Rules 2201 and 4102, 17 CCR 93115, and 40 CFR 60 Subpart IIII] Federally Enforceable Through Title V Permit
6. This engine shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier. [40 CFR 60 Subpart IIII] Federally Enforceable Through Title V Permit
7. This engine shall be operated only for testing and maintenance of the engine, required regulatory purposes, and during emergency situations. For testing purposes, the engine shall only be operated the number of hours necessary to comply with the testing requirements of the National Fire Protection Association (NFPA) 25 - "Standard for the Inspection, Testing, and Maintenance of Water-Based Fire Protection Systems", 2002 edition. Total hours of operation for all maintenance, testing, and required regulatory purposes shall not exceed 100 hours per calendar year. [District Rules 2201, 4102, 4701, and 4702, 17 CCR 93115, and 40 CFR 60 Subpart IIII] Federally Enforceable Through Title V Permit
8. The permittee shall maintain monthly records of emergency and non-emergency operation. Records shall include the number of hours of emergency operation, the date and number of hours of all testing and maintenance operations, and the purpose of the operation (for example: load testing, weekly testing, emergency usage, etc.). For units with automated testing systems, the operator may, as an alternative to keeping records of actual operation for testing purposes, maintain a readily accessible written record of the automated testing schedule. [District Rules 4701 and 4702, 17 CCR 93115, and 40 CFR Part 60 Subpart IIII] Federally Enforceable Through Title V Permit
9. The permittee shall maintain monthly records of the type of fuel purchased. [District Rules 4701, 4702, 17 CCR 93115, and 40 CFR Part 60 Subpart IIII] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 4702, 17 CCR 93115, and 40 CFR Part 60 Subpart III] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-953-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

302 BHP (INTERMITTENT) DOOSAN MODEL D111L RICH-BURN NATURAL GAS-FIRED EMERGENCY STANDBY IC ENGINE WITH NON-SELECTIVE CATALYTIC REDUCTION (NSCR) POWERING AN ELECTRICAL GENERATOR

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102]
3. This engine shall be equipped with an operational non-resettable elapsed time meter. [District Rule 4702 and 40 CFR 60.4237] Federally Enforceable Through Title V Permit
4. This IC engine shall be equipped with a three-way catalyst. [District Rule 2201 and 40 CFR 60.4243] Federally Enforceable Through Title V Permit
5. The air-to-fuel ratio controller must be maintained and operated appropriately in order to ensure proper operation of the engine and control device to minimize emissions at all times. [40 CFR 60.4243] Federally Enforceable Through Title V Permit
6. This IC engine shall be fired on Public Utility Commission (PUC) regulated natural gas only. [District Rules 2201 and 4801] Federally Enforceable Through Title V Permit
7. Emissions from this IC engine shall not exceed any of the following limits: 0.022 g-NO_x/bhp-hr, 0.063 g-PM₁₀/bhp-hr, 0.216 g-CO/bhp-hr, or 0.254 g-VOC/bhp-hr. [District Rule 2201] Federally Enforceable Through Title V Permit
8. This engine shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier. [District Rule 4702 and 40 CFR 60.4243] Federally Enforceable Through Title V Permit
9. During periods of operation for maintenance, testing, and required regulatory purposes, the permittee shall monitor the operational characteristics of the engine as recommended by the manufacturer or emission control system supplier (for example: check engine fluid levels, battery, cables and connections; change engine oil and filters; replace engine coolant; and/or other operational characteristics as recommended by the manufacturer or supplier). [District Rule 4702] Federally Enforceable Through Title V Permit
10. This engine shall be operated only for testing and maintenance of the engine, required regulatory purposes, and during emergency situations. Operation of the engine for maintenance, testing, and required regulatory purposes shall not exceed 100 hours per calendar year. [District Rules 4701 and 4702, and 40 CFR 60.4243] Federally Enforceable Through Title V Permit
11. An emergency situation is an unscheduled electrical power outage caused by sudden and reasonably unforeseen natural disasters or sudden and reasonably unforeseen events beyond the control of the permittee. [District Rule 4702] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

12. This engine shall not be used to produce power for the electrical distribution system, as part of a voluntary utility demand reduction program, or for an interruptible power contract. [District Rule 4702] Federally Enforceable Through Title V Permit
13. The permittee shall maintain monthly records of emergency and non-emergency operation. Records shall include the number of hours of emergency operation, the date and number of hours of all testing and maintenance operations, the purpose of the operation (for example: load testing, weekly testing, rolling blackout, general area power outage, etc.) and records of operational characteristics monitoring. For units with automated testing systems, the operator may, as an alternative to keeping records of actual operation for testing purposes, maintain a readily accessible written record of the automated testing schedule. [District Rules 4701 and 4702, and 40 CFR 60.4245] Federally Enforceable Through Title V Permit
14. The operator shall maintain monthly records of the type of fuel used. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit
15. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 4701 and 4702, and 40 CFR 60.4245] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

ATTACHMENT B

Previous Title V Operating Permit

Permit to Operate

FACILITY: N-266

EXPIRATION DATE: 10/31/2020

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

FACILITY LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

FACILITY DESCRIPTION: WINERY

The Facility's Permit to Operate may include Facility-wide Requirements as well as requirements that apply to specific permit units.

This Permit to Operate remains valid through the permit expiration date listed above, subject to payment of annual permit fees and compliance with permit conditions and all applicable local, state, and federal regulations. This permit is valid only at the location specified above, and becomes void upon any transfer of ownership or location. Any modification of the equipment or operation, as defined in District Rule 2201, will require prior District approval. This permit shall be posted as prescribed in District Rule 2010.

Samir Sheikh
Executive Director / APCO

Brian Clements
Director of Permit Services

San Joaquin Valley

Air Pollution Control District

FACILITY: N-266-0-1

EXPIRATION DATE: 10/31/2020

FACILITY-WIDE REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100, 6.1; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit
3. The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100, 7.0; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit
4. The owner or operator of any stationary source operation that emits more than 25 tons per year of nitrogen oxides or reactive organic compounds, shall provide the District annually with a written statement in such form and at such time as the District prescribes, showing actual emissions of nitrogen oxides and reactive organic compounds from that source. [District Rule 1160, 5.0] Federally Enforceable Through Title V Permit
5. Any person building, altering or replacing any operation, article, machine, equipment, or other contrivance, the use of which may cause the issuance of air contaminants or the use of which may eliminate, reduce, or control the issuance of air contaminants, shall first obtain an Authority to Construct (ATC) from the District unless exempted by District Rule 2020 (12/20/07). [District Rule 2010, 3.0 and 4.0; and 2020] Federally Enforceable Through Title V Permit
6. The permittee must comply with all conditions of the permit including permit revisions originated by the District. All terms and conditions of a permit that are required pursuant to the Clean Air Act (CAA), including provisions to limit potential to emit, are enforceable by the EPA and Citizens under the CAA. Any permit noncompliance constitutes a violation of the CAA and the District Rules and Regulations, and is grounds for enforcement action, for permit termination, revocation, reopening and reissuance, or modification; or for denial of a permit renewal application. [District Rules 2070, 7.0; 2080; and 2520, 9.8.1 and 9.12.1] Federally Enforceable Through Title V Permit
7. A Permit to Operate or an Authority to Construct shall not be transferred unless a new application is filed with and approved by the District. [District Rule 2031] Federally Enforceable Through Title V Permit
8. Every application for a permit required under Rule 2010 (12/17/92) shall be filed in a manner and form prescribed by the District. [District Rule 2040] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of required monitoring that include: 1) the date, place, and time of sampling or measurement; 2) the date(s) analyses were performed; 3) the company or entity that performed the analysis; 4) the analytical techniques or methods used; 5) the results of such analysis; and 6) the operating conditions at the time of sampling or measurement. [District Rule 2520, 9.4.1] Federally Enforceable Through Title V Permit
10. The operator shall retain records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, or report. Support information includes copies of all reports required by the permit and, for continuous monitoring instrumentation, all calibration and maintenance records and all original strip-chart recordings. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate. Any amendments to these Facility-wide Requirements that affect specific Permit Units may constitute modification of those Permit Units.

Facility Name: DELICATO VINEYARDS
Location: 12001 S HIGHWAY 99,MANTECA, CA 95336
N-266-0-1 : Sep 15 2021 12:55PM -- NORMANR

11. The operator shall submit reports of any required monitoring at least every six months unless a different frequency is required by an applicable requirement. All instances of deviations from permit requirements must be clearly identified in such reports. [District Rule 2520, 9.5.1] Federally Enforceable Through Title V Permit
12. Deviations from permit conditions must be promptly reported, including deviations attributable to upset conditions, as defined in the permit. For the purpose of this condition, promptly means as soon as reasonably possible, but no later than 10 days after detection. The report shall include the probable cause of such deviations, and any corrective actions or preventive measures taken. All required reports must be certified by a responsible official consistent with section 10.0 of District Rule 2520 (6/21/01). [District Rules 2520, 9.5.2 and 1100, 7.0] Federally Enforceable Through Title V Permit
13. If for any reason a permit requirement or condition is being challenged for its constitutionality or validity by a court of competent jurisdiction, the outcome of such challenge shall not affect or invalidate the remainder of the conditions or requirements in that permit. [District Rule 2520, 9.7] Federally Enforceable Through Title V Permit
14. It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. [District Rule 2520, 9.8.2] Federally Enforceable Through Title V Permit
15. The permit may be modified, revoked, reopened and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition. [District Rule 2520, 9.8.3] Federally Enforceable Through Title V Permit
16. The permit does not convey any property rights of any sort, or any exclusive privilege. [District Rule 2520, 9.8.4] Federally Enforceable Through Title V Permit
17. The Permittee shall furnish to the District, within a reasonable time, any information that the District may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the District copies of records required to be kept by the permit or, for information claimed to be confidential, the permittee may furnish such records directly to EPA along with a claim of confidentiality. [District Rule 2520, 9.8.5] Federally Enforceable Through Title V Permit
18. The permittee shall pay annual permit fees and other applicable fees as prescribed in Regulation III of the District Rules and Regulations. [District Rule 2520, 9.9] Federally Enforceable Through Title V Permit
19. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 2520, 9.13.2.1] Federally Enforceable Through Title V Permit
20. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 2520, 9.13.2.2] Federally Enforceable Through Title V Permit
21. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to inspect at reasonable times any facilities, equipment, practices, or operations regulated or required under the permit. [District Rule 2520, 9.13.2.3] Federally Enforceable Through Title V Permit
22. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements. [District Rule 2520, 9.13.2.4] Federally Enforceable Through Title V Permit
23. No air contaminants shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101 (02/17/05). If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

24. No person shall manufacture, blend, repackage, supply, sell, solicit or apply any architectural coating with a VOC content in excess of the corresponding limit specified in the Table of Standards of District Rule 4601 (12/17/09) for use or sale within the District. [District Rule 4601, 5.1] Federally Enforceable Through Title V Permit
25. All VOC-containing materials for architectural coatings subject to Rule 4601 (12/17/09) shall be stored in closed containers when not in use. [District Rule 4601, 5.4] Federally Enforceable Through Title V Permit
26. The permittee shall comply with all the Labeling and Test Methods requirements outlined in Rule 4601 sections 6.1 and 6.3 (12/17/09). [District Rule 4601, 6.1 and 6.3] Federally Enforceable Through Title V Permit
27. With each report or document submitted under a permit requirement or a request for information by the District or EPA, the permittee shall include a certification of truth, accuracy, and completeness by a responsible official. [District Rule 2520, 9.13.1 and 10.0] Federally Enforceable Through Title V Permit
28. If the permittee performs maintenance on, or services, repairs, or disposes of appliances, the permittee shall comply with the standards for Recycling and Emissions Reduction pursuant to 40 CFR 82, Subpart F. [40 CFR 82 Subpart F] Federally Enforceable Through Title V Permit
29. If the permittee performs service on motor vehicles when this service involves the ozone-depleting refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the standards for Servicing of Motor Vehicle Air Conditioners pursuant to all the applicable requirements as specified in 40 CFR 82, Subpart B. [40 CFR 82, Subpart B] Federally Enforceable Through Title V Permit
30. Disturbances of soil related to any construction, demolition, excavation, extraction, or other earthmoving activities shall comply with the requirements for fugitive dust control in District Rule 8021 unless specifically exempted under Section 4.0 of Rule 8021 (8/19/04) or Rule 8011 (8/19/04). [District Rules 8021 and 8011] Federally Enforceable Through Title V Permit
31. Outdoor handling, storage and transport of any bulk material which emits dust shall comply with the requirements of District Rule 8031, unless specifically exempted under Section 4.0 of Rule 8031 (8/19/04) or Rule 8011 (8/19/04). [District Rules 8031 and 8011] Federally Enforceable Through Title V Permit
32. An owner/operator shall prevent or cleanup any carryout or trackout in accordance with the requirements of District Rule 8041 Section 5.0, unless specifically exempted under Section 4.0 of Rule 8041 (8/19/04) or Rule 8011 (8/19/04). [District Rules 8041 and 8011] Federally Enforceable Through Title V Permit
33. Whenever open areas are disturbed or vehicles are used in open areas, the facility shall comply with the requirements of Section 5.0 of District Rule 8051, unless specifically exempted under Section 4.0 of Rule 8051 (8/19/04) or Rule 8011 (8/19/04). [District Rules 8051 and 8011] Federally Enforceable Through Title V Permit
34. Any paved road or unpaved road shall comply with the requirements of District Rule 8061 unless specifically exempted under Section 4.0 of Rule 8061 (8/19/04) or Rule 8011 (8/19/04). [District Rules 8061 and 8011] Federally Enforceable Through Title V Permit
35. Any unpaved vehicle/equipment area that anticipates more than 75 vehicle trips per day shall comply with the requirements of Section 5.1.1 of District Rule 8071. Any unpaved vehicle/equipment area that anticipates more than 100 vehicle trips per day shall comply with the requirements of Section 5.1.2 of District Rule 8071. All sources shall comply with the requirements of Section 5.0 of District Rule 8071 unless specifically exempted under Section 4.0 of Rule 8071 (9/16/04) or Rule 8011 (8/19/04). [District Rules 8071 and 8011] Federally Enforceable Through Title V Permit
36. Any owner or operator of a demolition or renovation activity, as defined in 40 CFR 61.141, shall comply with the applicable inspection, notification, removal, and disposal procedures for asbestos containing materials as specified in 40 CFR 61.145 (Standard for Demolition and Renovation). [40 CFR 61 Subpart M] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

37. The permittee shall submit certifications of compliance with the terms and standards contained in Title V permits, including emission limits, standards and work practices, to the District and the EPA annually (or more frequently as specified in an applicable requirement or as specified by the District). The certification shall include the identification of each permit term or condition, the compliance status, whether compliance was continuous or intermittent, the methods used for determining the compliance status, and any other facts required by the District to determine the compliance status of the source. [District Rule 2520, 9.16] Federally Enforceable Through Title V Permit
38. The permittee shall submit an application for Title V permit renewal to the District at least six months, but not greater than 18 months, prior to the permit expiration date. [District Rule 2520, 5.2] Federally Enforceable Through Title V Permit
39. When a term is not defined in a Title V permit condition, the definition in the rule cited as the origin and authority for the condition in a Title V permits shall apply. [District Rule 2520, 9.1.1] Federally Enforceable Through Title V Permit
40. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following outdated SIP requirements: Rule 110 (Fresno, Stanislaus, San Joaquin), Rule 109 (Merced), Rule 113 (Madera), and Rule 111 (Kern, Tulare, Kings). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
41. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following applicable requirements: SJVUAPCD Rules 1100, sections 6.1 and 7.0 (12/17/92); 2010, sections 3.0 and 4.0 (12/17/92); 2031 (12/17/92); 2040 (12/17/92); 2070, section 7.0 (12/17/92); 2080 (12/17/92); 4101 (02/17/05); 4601, sections 5.1, 5.2, 5.3, 5.8 and 8.0 (12/17/09); 8021 (8/19/04); 8031 (8/19/04); 8041 (8/19/04); 8051 (8/19/04); 8061 (8/19/04); and 8071 (9/16/04). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
42. On October 1, 2010, the initial Title V permit was issued. The reporting periods for the Report of Required Monitoring and the Compliance Certification Report are based upon this initial permit issuance date, unless alternative dates are approved by the District Compliance Division. These reports are due within 30 days after the end of the reporting period. [District Rule 2520] Federally Enforceable Through Title V Permit
43. The winery operator shall achieve required annual emissions reductions (RAER) equal to at least 35% of the winery's baseline fermentation emissions (BFE) [District Rule 4694]
44. By December 1, 2006, and every three years thereafter, the winery operator subject to the requirements of Section 5.1 shall submit to the District a three-year compliance plan that demonstrates compliance with the applicable requirements of District Rule 4694 for each year of the applicable compliance period. The three-year compliance plan shall include all the information specified in sections 6.1.1 through 6.1.8 of the rule. [District Rule 4694, 6.1]
45. By July 1, 2007, and every three years thereafter, the winery operator shall submit to the District a three-year compliance plan verification that demonstrates that the three-year compliance plan elements are in effect. The compliance plan verification shall include all the information specified in sections 6.2.1 through 6.2.5 of District Rule 4694. [District Rule 4694, 6.2]
46. By March 1, 2008, and every year thereafter on or before March 1, the winery operator shall submit to the District an annual compliance plan demonstration that shows compliance with the applicable requirements of District Rule 4694. The compliance plan demonstration shall include all the information specified in sections 6.3.1 through 6.3.7 of the rule. All additional Required Annual Emissions Reductions (RAER) shall be obtained by April 1 of the year of the Annual Compliance Demonstration, per section 6.3.7.2 of the rule. [District Rule 4694, 6.3]
47. Operators using certified emission reductions (CER) to mitigate fermentation emissions shall perform all monitoring and recordkeeping, as established in their approved three-year compliance plan, and shall maintain all records necessary to demonstrate compliance. [District Rule 4694]
48. Payment of District Obtained Emissions Reductions (DOER) and administrative fees shall be made to the District no later than March 1, of the first year in the applicable compliance period. [District Rule 4694, 6.1.5.3.5]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-1-6

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

GASOLINE DISPENSING OPERATION WITH ONE 4,000 GALLON (SPLIT 2,000 GALLON GASOLINE/2,000 GALLON DIESEL) CONVAULT ABOVEGROUND STORAGE TANK SERVED BY MORRISON BROTHERS PHASE I VAPOR RECOVERY SYSTEM (VR-402-B), STANDING LOSS CONTROL (VR-301-E), AND 1 FUELING POINT WITH 1 GASOLINE DISPENSING NOZZLE SERVED BY BALANCE PHASE II VAPOR RECOVERY SYSTEM (G-70-116F)

PERMIT UNIT REQUIREMENTS

1. The Phase I, Phase II, and Standing Loss Control Vapor recovery systems shall be installed and maintained in accordance with the manufacturer specifications and the ARB Executive Orders specified in this permit, including applicable rules and regulations of the Division of Measurement Standards of the Department of Food and Agriculture, the Office of the State Fire Marshal of the Department of Forestry and Fire Protection, the Division of Occupational Safety and Health of the Department of Industrial Relations, and the Division of Water Quality of the State Water Resources Control Board that have been made conditions of the certification. [District Rules 4621 and 4622 and CH&SC 41950] Federally Enforceable Through Title V Permit
2. This gasoline storage and dispensing equipment shall not be used in retail sales, where gasoline dispensed by the unit is subject to payment of California sales tax on gasoline sales. [District Rule 4622] Federally Enforceable Through Title V Permit
3. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
4. The storage container(s) shall be installed, maintained, and operated such that they are leak-free. [District Rule 4621] Federally Enforceable Through Title V Permit
5. The Phase I and Phase II vapor recovery systems and gasoline dispensing equipment shall be maintained without leaks as determined in accordance with the test method specified in this permit. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
6. A leak is defined as the dripping of VOC-containing liquid at a rate of more than three (3) drops per minute, or the detection of any gaseous or vapor emissions with a concentration of total organic compound greater than 10,000 ppmv, as methane, above background when measured in accordance with EPA Test Method 21. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
7. No gasoline delivery vessel shall be operated or be allowed to operate unless valid State of California decals are displayed on the cargo container, which attest to the vapor integrity of the container. [District Rule 4621] Federally Enforceable Through Title V Permit
8. No person shall operate any ARB certified Phase II vapor recovery system or any portion thereof that has a major defect or an equipment defect that is identified in any applicable ARB Executive Order until the following conditions have been met: 1) the defect has been repaired, replaced, or adjusted as necessary to correct the defect; 2) the District has been notified, and the District has reinspected the system or authorized the system for use (such authorization shall not include the authority to operate the equipment prior to the correction of the defective components); and 3) all major defects, after repair, are duly entered into the Operations and Maintenance (O&M) manual. [District Rule 4622] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

9. Upon identification of any major defects, the permittee shall tag "Out-of-Order" all dispensing equipment for which vapor recovery has been impaired. Tagged equipment shall be rendered inoperable and the tag(s) shall not be removed until the defective equipment has been repaired, replaced, or adjusted, as necessary. In the case of defects identified by the District, tagged equipment shall be rendered inoperable, and the tag shall not be removed until the District has been notified of the repairs, and the District has either reinspected the system or authorized the tagged equipment for use. [District Rule 4622] Federally Enforceable Through Title V Permit
10. The permittee shall implement a periodic maintenance inspection program for the certified Phase II vapor recovery system consistent with the requirements of this permit. The program shall be documented in an operation and maintenance (O&M) manual and shall at a minimum contain the following information: 1) copies of all vapor recovery performance tests; 2) all applicable ARB Executive Orders, Approval Letters, and District Permits; 3) the manufacturer's specifications and instructions for installation, operation, repair, and maintenance required pursuant to ARB Certification Procedure CP-201, and any additional instruction provided by the manufacturer; 4) system and/or component testing requirements, including test schedules and passing criteria for each of the standard tests required by this permit (the owner/operator may include any non-ARB required diagnostic and other tests as part of the testing requirements), and 5) additional O&M instructions, if any, that are designed to ensure compliance with the applicable rules, regulations, ARB Executive Orders, and District permit conditions, including replacement schedules for failure or wear prone components. [District Rule 4622] Federally Enforceable Through Title V Permit
11. The permittee shall conduct periodic maintenance inspections based on the greatest monthly throughput of gasoline dispensed by the facility in the previous year as follows: A) less than 2,500 gallons - one day per month; B) 2,500 to less than 25,000 gallons - one day per week; or C) 25,000 gallons or greater - five days per week. All inspections shall be documented within the O & M Manual. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
12. Periodic maintenance inspections of the Phase I vapor recovery system shall include, at a minimum, verification that 1) the fill caps and vapor caps are not missing, damaged, or loose; 2) the fill cap gasket and vapor cap gaskets are not missing or damaged; 3) the fill adapter and vapor adapter are securely attached to the risers; 4) where applicable, the spring-loaded submerged fill tube seals properly against the coaxial tubing; 5) the dry break (poppet-valve) is not missing or damaged; and 6) the submerged fill tube is not missing or damaged. [District Rule 4621] Federally Enforceable Through Title V Permit
13. Periodic maintenance inspections of the Phase II vapor recovery system shall include, at a minimum, verification that 1) the following nozzle components are in place and in good condition as specified in ARB Executive Order as applicable: faceplate/facecone, bellows, latching device spring, vapor check valve, spout (proper diameter/vapor collection holes), insertion interlock mechanism, automatic shut-off mechanism, and hold open latch (unless prohibited by law or the local fire control authority); 2) the hoses are not torn, flattened or crimped; 3) the vapor path of the coaxial hoses associated with bellows equipped nozzles does not contain more than 100 ml of liquid if applicable; and 4) the vapor processing unit is functioning properly, for operations that are required to have or possess such a unit. [District Rule 4622] Federally Enforceable Through Title V Permit
14. In the event of a separation due to a drive off, the permittee shall, unless otherwise specified in the applicable ARB Executive Order, conduct a visual inspection of the affected equipment and either 1) perform qualified repairs on any damaged components and conduct applicable re-verification tests pursuant to the requirements of this permit, or 2) replace the affected nozzles, coaxial hoses, breakaway couplings, and any other damaged components with new or certified rebuilt components that are ARB certified. The activities shall be documented in accordance with the requirements of this permit before placing the affected equipment back in service. [District Rule 4622] Federally Enforceable Through Title V Permit
15. The gasoline throughput for this permit unit shall not exceed 657,000 gallons in any one calendar year. [District Rule 2201] Federally Enforceable Through Title V Permit
16. The permittee shall conduct all periodic vapor recovery system performance tests specified in this permit, no more than 30 days before or after the required compliance testing date, unless otherwise required under the applicable ARB Executive Order. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

17. The permittee shall perform and pass a Static Leak Test "Determination of Static Pressure Performance of Vapor Recovery Systems at Gasoline Dispensing Facilities with Aboveground Tanks" in accordance with the Executive Order specified in this permit for the Phase I Vapor Recovery System at least once every 12 months. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
18. For certified Phase II vapor recovery systems with liquid removal devices, the permittee shall perform and pass an ARB TP-201.6C Liquid Removal Test whenever the liquid in the vapor path exceeds 100 ml of liquid, or as required by the applicable ARB Executive Order. The amount of liquid in the vapor path shall be measured by lowering the gasoline dispensing nozzle into a container until such time that no more liquid drains from the nozzle. The amount of liquid drained into the container shall be measured using a graduated cylinder or graduated beaker. The vapor path shall be inspected according to the monitoring frequency as determined by monthly gasoline throughput. [District Rule 4622] Federally Enforceable Through Title V Permit
19. A person conducting testing of, or repairs to, a certified vapor recovery system shall be in compliance with District Rule 1177 (Gasoline Dispensing Facility Tester Certification). [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
20. A person performing installation of, or maintenance on, a certified Phase I or Phase II vapor recovery system shall be certified by the ICC for Vapor Recovery System Installation and Repair, or work under the direct and personal supervision of an individual physically present at the work site who is certified. The ICC certification shall be renewed every 24 months. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
21. Proof of the ICC certification and all other certifications required by the Executive Order and installation and operation manual shall be made available onsite. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
22. The permittee shall notify the District at least 7 days prior to each performance test. The test results shall be submitted to the District no later than 30 days after the completion of each test. [District Rule 4621] Federally Enforceable Through Title V Permit
23. The permittee shall maintain a copy of all test results. The test results shall be dated and shall contain the name, address, and telephone number of the company responsible for system installation and testing. [District Rule 4622] Federally Enforceable Through Title V Permit
24. The permittee shall maintain on the premises a log of any repairs made to the certified Phase I or Phase II vapor recovery system. The repair log shall include the following: 1) date and time of each repair; 2) the name and applicable certification numbers of the person(s) who performed the repair, and if applicable, the name, address and phone number of the person's employer; 3) description of service performed; 4) each component that was repaired, serviced, or removed; 5) each component that was installed as replacement, if applicable; and 6) receipts or other documents for parts used in the repair and, if applicable, work orders which shall include the name and signature of the person responsible for performing the repairs. [District Rule 4622] Federally Enforceable Through Title V Permit
25. The O&M manual shall be kept at the dispensing operation and made available to any person who operates, inspects, maintains, repairs, or tests the equipment at the operation as well as to District personnel upon request. [District Rule 4622] Federally Enforceable Through Title V Permit
26. The permittee shall maintain monthly and annual gasoline throughput records. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
27. All records required by this permit shall be retained on-site for a period of at least five years and shall be made available for District inspection upon request. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-3-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

106 HP DEUTZ MODEL NDC-BF4 M1013ES DIESEL-FIRED EMERGENCY IC ENGINE POWERING A FIRE PUMP.

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. This engine shall be operated only for maintenance, testing, and required regulatory purposes, and during emergency situations. For testing purposes, the engine shall only be operated the number of hours necessary to comply with the testing requirements of the National Fire Protection Association (NFPA) 25 - "Standard for the Inspection, Testing, and Maintenance of Water-Based Fire Protection Systems", 1998 edition. Total hours of operation for all maintenance, testing, and required regulatory purposes shall not exceed 50 hours per calendar year. [District Rules 2201, 4701, 4.2; 4702, 4.3.1, 17 CCR 93115, and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
3. This engine shall be equipped with either a positive crankcase ventilation (PCV) system that recirculates crankcase emissions into the air intake system for combustion, or a crankcase emissions control device of at least 90% control efficiency. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102]
5. This engine shall be operated using only CARB certified diesel fuel. [17 CCR 93115 and District Rules 2201 and 4801; and County Rule 407 (San Joaquin)] Federally Enforceable Through Title V Permit
6. NOx emissions shall not exceed 5.9 g/hp-hr. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The PM10 emissions rate shall not exceed 0.1 g/hp-hr based on US EPA certification using ISO 8178 test procedure. [District Rule 2201] Federally Enforceable Through Title V Permit
8. This engine shall be equipped with an operational non-resettable elapsed operating time meter or other APCO approved alternative. [17 CCR 93115, District Rule 4702, 4.3, and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
9. This engine shall be used exclusively for fire fighting purposes. [District Rule 4702, 4.3.1] Federally Enforceable Through Title V Permit
10. This engine shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier [CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
11. The permittee must minimize the engine's time spent at idle during startup and minimize the engine's startup time to a period needed for appropriate and safe loading of the engine, not to exceed 30 minutes. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
12. The engine's oil and filter shall be changed every 500 hours of operation or every 12 months, whichever comes first. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

13. The engine's air filter shall be inspected every 1,000 hours of operation or every 12 months, whichever comes first, and replaced as necessary. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
14. The engine's hoses and belts shall be inspected every 500 hours of operation or every 12 months, whichever comes first, and replaced as necessary. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
15. The permittee has the option of utilizing an oil analysis program in order to extend the specified oil change requirement in Tables 2c and 2d of Subpart ZZZZ. The oil analysis must be performed at the same frequency specified for changing the oil in Table 2c or 2d to this subpart. The analysis program must at a minimum analyze the following three parameters: Total Base Number, viscosity, and percent water content. The condemning limits for these parameters are as follows: Total Base Number is less than 30 percent of the Total Base Number of the oil when new; viscosity of the oil has changed by more than 20 percent from the viscosity of the oil when new; or percent water content (by volume) is greater than 0.5. If all of these condemning limits are not exceeded, the engine owner or operator is not required to change the oil. If any of the limits are exceeded, the engine owner or operator must change the oil within 2 days of receiving the results of the analysis; if the engine is not in operation when the results of the analysis are received, the engine owner or operator must change the oil within 2 days or before commencing operation, whichever is later. The owner or operator must keep records of the parameters that are analyzed as part of the program, the results of the analysis, and the oil changes for the engine. The analysis program must be part of the maintenance plan for the engine. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
16. The permittee must maintain records of all required maintenance performed on the air pollution control and monitoring equipment. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
17. The permittee shall maintain monthly records of the occurrence and duration of each malfunction of operation (i.e., process equipment) or the air pollution control and monitoring equipment. The permittee shall also maintain monthly records of action taken during periods of malfunction to minimize emissions, including corrective actions to restore malfunctioning process and air pollution control and monitoring equipment to its normal or usual manner of operation. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
18. The permittee shall maintain monthly records of emergency and non-emergency operation. Records shall include the number of hours of emergency operation, the date and number of hours of all testing and maintenance operations, and the purpose of the operation (for example: load testing, weekly testing, rolling blackout, general area power outage, etc.). For units with automated testing systems, the operator may, as an alternative to keeping records of actual operation for testing purposes, maintain a readily accessible written record of the automated testing schedule. [District Rule 4702, 17 CCR 93115, and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
19. The permittee shall maintain monthly records of the type of fuel purchased, the amount of fuel purchased, date when the fuel was purchased, signature of the permittee who received the fuel, and signature of the fuel supplier indicating that the fuel was delivered. [17 CCR 93115]
20. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 4701 and 4702; 17 CCR 93115, and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-9-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

14,579 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 34 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-10-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

14,707 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 35 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-20-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

7,184 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 45 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-21-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

7,192 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 46 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-22-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

7,180 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 47 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-23-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

7,168 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 48 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-24-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

7,151 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 49 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-25-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

7,188 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 50 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-26-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

7,192 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 51 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-27-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

7,201 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 52 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-28-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

7,188 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 53 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-29-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

7,180 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 54 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-30-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,663 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 55 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-31-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,728 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 56 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-32-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,663 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 57 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-33-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,696 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 58 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-38-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

8,590 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 63 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-39-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

8,563 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 64 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-48-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,720 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 73 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-49-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,735 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 74 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-56-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

51,486 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 108 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-57-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

51,460 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 109 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-58-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

51,446 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 110 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-59-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

51,406 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 111 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-60-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

51,446 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 112 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-61-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

51,460 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 113 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-62-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

51,433 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 114 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-63-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

51,420 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 115 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley *Air Pollution Control District*

PERMIT UNIT: N-266-64-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

51,446 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 116 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-65-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

51,433 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 117 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-66-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

51,460 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 118 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-67-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

51,500 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 119 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-68-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

51,700 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 120 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-69-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

51,500 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 121 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-70-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

51,500 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 122 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-71-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

51,687 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 123 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-72-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

51,741 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 124 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-73-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

51,674 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 125 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-74-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

51,741 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 126 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-75-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

51,687 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 127 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-76-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

51,714 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 128 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-77-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

44,309 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 151 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-78-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

44,327 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 152 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley *Air Pollution Control District*

PERMIT UNIT: N-266-79-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

44,327 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 153 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-80-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

44,370 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 154 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-81-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

44,361 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 155 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-82-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

44,309 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 156 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-83-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

44,309 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 157 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-84-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

44,327 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 158 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-85-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

44,378 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 161 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-86-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

44,356 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 162 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-87-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

44,206 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 163 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-88-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

44,361 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 164 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-89-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

44,155 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 165 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-90-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

44,206 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 166 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-91-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

44,327 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 167 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-92-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

44,344 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 168 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-93-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

44,176 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 171 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-94-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

44,335 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 172 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-95-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

44,172 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 173 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-96-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

44,361 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 174 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-97-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

44,206 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 175 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-98-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

44,155 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 176 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-99-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

44,172 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 177 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-100-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

44,206 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 178 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-101-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

73,375 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 187 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-102-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

73,373 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 188 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-103-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

72,048 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 189 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-104-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

73,336 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 197 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-105-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

73,355 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 198 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-106-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

72,031 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 199 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-113-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

60,339 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 207 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-114-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

60,158 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 208 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-115-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

60,094 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 209 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-116-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

60,090 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 210 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-117-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

60,109 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 211 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-118-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

60,076 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 212 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-119-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

60,076 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 219 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-120-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

60,010 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 220 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley *Air Pollution Control District*

PERMIT UNIT: N-266-121-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

60,066 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 221 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-122-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

60,109 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 222 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-123-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

60,058 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 229 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-124-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

127,903 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 250 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-125-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

127,709 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 251 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-126-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

128,223 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 252 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-127-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

128,327 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 253 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-128-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

127,566 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 254 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-129-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

128,256 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 255 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-130-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

128,493 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 256 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-131-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

127,579 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 260 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-132-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

128,016 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 261 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-133-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

127,129 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 262 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-134-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

128,290 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 263 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-135-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

128,467 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 264 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-136-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

127,768 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 265 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-137-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

128,324 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 266 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-138-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

128,511 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 270 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-139-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

127,507 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 271 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-140-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

128,647 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 272 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-141-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

128,425 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 273 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-142-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

128,639 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 274 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-143-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

128,915 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 275 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-144-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

128,290 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 276 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-145-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

128,425 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 280 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-146-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

129,372 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 281 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-147-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

128,155 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 282 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-148-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

128,425 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 283 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-149-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

128,695 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 284 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-150-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

128,670 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 285 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-151-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

128,636 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 286 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-152-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

127,738 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 290 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-153-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

129,435 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 291 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-154-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

127,535 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 292 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-155-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

23,100 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 293 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-156-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

23,100 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 294 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-157-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

23,100 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 295 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-158-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

23,100 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 296 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-159-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

23,100 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 297 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-160-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

352,002 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 301 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-161-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

350,790 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 302 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-162-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

351,769 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 303 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-163-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

351,655 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 304 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-164-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

352,067 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 305 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-165-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

351,022 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 306 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-166-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

351,141 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 307 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-167-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

351,079 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 311 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-168-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

351,724 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 312 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-169-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

351,039 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 313 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-170-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

350,496 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 314 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-171-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

351,219 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 315 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-172-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

351,521 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 316 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-173-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

351,051 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 317 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-174-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

350,760 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 321 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-175-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

350,946 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 322 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-176-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

351,267 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 323 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-177-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

351,930 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 324 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-178-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

352,374 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 325 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-179-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

351,625 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 326 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-180-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

351,374 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 327 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-181-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

351,125 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 331 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-182-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

351,178 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 332 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-183-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

349,827 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 333 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-184-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

352,011 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 334 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-185-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

350,672 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 335 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-186-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

352,014 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 336 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-187-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

351,229 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 337 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-188-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

351,941 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 341 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-189-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

352,833 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 342 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-190-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

351,917 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 343 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley *Air Pollution Control District*

PERMIT UNIT: N-266-191-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

351,965 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 344 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-192-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

351,845 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 345 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley *Air Pollution Control District*

PERMIT UNIT: N-266-193-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

352,592 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 346 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-194-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

353,300 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 347 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-195-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

352,592 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 401 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-196-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

351,868 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 402 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-197-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

352,116 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 403 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-198-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

351,381 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 404 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-199-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

352,556 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 405 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-200-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

352,028 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 406 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-201-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

352,291 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 411 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-202-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

350,900 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 412 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-203-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

351,876 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 413 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-204-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

351,019 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 414 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-205-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

352,127 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 415 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-206-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

352,381 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 416 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-207-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

351,750 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 421 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-208-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

351,575 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 422 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-209-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

351,991 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 423 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley *Air Pollution Control District*

PERMIT UNIT: N-266-210-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

351,503 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 424 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-211-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

351,404 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 425 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-212-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

352,189 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 426 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-213-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

184,614 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 501 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-214-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

184,476 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 502 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-215-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

184,682 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 503 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-216-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

185,169 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 504 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-217-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

251,301 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 505 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-218-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

251,909 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 506 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-219-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

185,400 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 511 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-220-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

185,273 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 512 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-221-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

184,262 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 513 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-222-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

185,453 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 514 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-223-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

250,885 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 515 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-224-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

250,230 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 516 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-225-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

212,399 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 521 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-226-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

211,951 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 522 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-227-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

211,775 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 523 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-228-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

212,847 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 524 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-229-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

249,902 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 525 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-230-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

251,435 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 526 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-231-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

211,653 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 531 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-232-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

211,496 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 532 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-233-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

211,198 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 533 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-234-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

212,367 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 534 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-235-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

251,482 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 535 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-236-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

250,731 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 536 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-237-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

56,046 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 601 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-238-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

55,572 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 602 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-239-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

55,824 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 603 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-240-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

55,815 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 604 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-241-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

55,778 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 611 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-242-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

55,572 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 612 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-243-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

55,825 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 613 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-244-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

55,592 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 614 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-245-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

49,395 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 621 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-246-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

49,771 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 622 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-247-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

49,226 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 623 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-248-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

49,379 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 624 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-249-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

49,755 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 631 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-250-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

49,793 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 632 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-251-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

49,208 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 633 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-252-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,054 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 634 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-253-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

49,692 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 635 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-254-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

49,397 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 636 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-255-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

49,413 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 637 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-256-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

49,535 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 638 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-257-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,734 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 641 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-258-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,638 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 642 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-259-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,321 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 643 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-260-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

3,269 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 644 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-261-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,324 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 645 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-262-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,311 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 646 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-263-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,324 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 647 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-264-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,766 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 651 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-265-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,703 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 652 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-266-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,311 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 653 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-267-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,317 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 654 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley *Air Pollution Control District*

PERMIT UNIT: N-266-268-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,313 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 655 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-269-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,317 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 656 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-270-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,314 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 657 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-271-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,740 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 661 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-272-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,740 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 662 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley *Air Pollution Control District*

PERMIT UNIT: N-266-273-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,740 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 663 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-274-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,740 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 664 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-275-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,722 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 665 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-276-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,682 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 666 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-277-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,676 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 671 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-278-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,734 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 672 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-279-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,722 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 673 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-280-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,728 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 674 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley *Air Pollution Control District*

PERMIT UNIT: N-266-281-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,734 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 675 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-282-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,663 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 676 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-283-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,651 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 681 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-284-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,690 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 682 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-285-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,645 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 683 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-286-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,689 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 684 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-287-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,600 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 685 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-288-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,715 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 686 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-289-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,238 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 691 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-290-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,090 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 692 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-291-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,105 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 693 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-292-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,114 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 694 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-293-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,107 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 695 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-294-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

44,361 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 801 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-295-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

44,412 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 802 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-296-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

44,404 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 803 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-297-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

44,395 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 804 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley *Air Pollution Control District*

PERMIT UNIT: N-266-298-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

44,240 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 805 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-299-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

44,206 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 806 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-300-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

44,257 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 807 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-301-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

49,362 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 808 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-302-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

44,413 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 809 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-303-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

44,395 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 810 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-304-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

44,370 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 811 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-305-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

44,328 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 812 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-306-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,190 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 813 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-307-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,087 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 814 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-308-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,910 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 821 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-309-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,921 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 822 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-310-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,930 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 823 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-311-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,553 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 824 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-312-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,940 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 825 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-313-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,882 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 826 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-314-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,940 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 827 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-315-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,900 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 828 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-316-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,910 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 829 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-317-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,911 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 830 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-318-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,966 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 831 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley *Air Pollution Control District*

PERMIT UNIT: N-266-319-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,872 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 832 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-320-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,271 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 833 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-321-4

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,238 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 834 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE.

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine or distilled spirits storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine or distilled spirits storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine or distilled spirits stored in this tank shall not exceed 97 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine or distilled spirits storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1] Federally Enforceable Through Title V Permit
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine or distilled spirits storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine or distilled spirits storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine or distilled spirits storage operations may be determined using the total annual wine or distilled spirits throughput and a single storage emissions factor based on the average ethanol content of the annual wine or distilled spirits throughput; or using the throughputs for different batches of wine or distilled spirits and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-322-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,892 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 841 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-323-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,706 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 842 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-324-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,747 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 843 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-325-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,706 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 844 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-266-326-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

51,097 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 845 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-327-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

80,687 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 846 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-328-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,716 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 847 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-329-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,745 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 848 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-330-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,892 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 849 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-331-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,706 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 850 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-332-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,706 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 851 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-333-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,891 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 852 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-334-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,103 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 853 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-335-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,060 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 854 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-338-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

49,422 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1001 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-339-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

49,574 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1002 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-340-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

49,239 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1003 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-341-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

49,473 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1004 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-342-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

49,416 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1005 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-343-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

49,415 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1006 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-344-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

49,414 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1011 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-345-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

49,424 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1012 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-346-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

49,433 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1013 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-347-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

49,459 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1014 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-348-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

49,597 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1015 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-349-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

49,435 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1016 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-350-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,565 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1021 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-351-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,655 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1022 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-352-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,573 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1023 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-353-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,565 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1024 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-354-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,573 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1025 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-355-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,628 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1026 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-356-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,655 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1027 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-357-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,655 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1031 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-358-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,565 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1032 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-359-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,565 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1033 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-360-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,647 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1034 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-361-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,557 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1035 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-362-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,655 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1036 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-363-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,565 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1037 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-364-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,565 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1041 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-365-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,573 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1042 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-366-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,557 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1043 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-367-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,655 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1044 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-368-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,557 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1045 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-369-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,573 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1046 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-370-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,655 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1047 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-371-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,548 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1051 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-372-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,655 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1052 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-373-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,647 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1053 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-374-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,655 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1054 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-375-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,655 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1055 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-376-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,672 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1056 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-377-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,573 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1057 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-378-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,664 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1061 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-379-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,604 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1062 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-380-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,675 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1063 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-381-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,651 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1064 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-382-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,644 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1065 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-383-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,593 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1066 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-384-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,593 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1067 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-385-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,589 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1068 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-386-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,593 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1069 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-387-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,522 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1070 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-388-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,640 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1081 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-389-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,649 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1082 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-390-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,707 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1083 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-391-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,644 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1084 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley *Air Pollution Control District*

PERMIT UNIT: N-266-392-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,644 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1085 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-393-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,569 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1086 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-394-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,644 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1087 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-395-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,712 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1088 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-396-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,720 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1089 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-397-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,649 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1090 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-398-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

3,613 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1091 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-399-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

3,613 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1092 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-400-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

3,613 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1093 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-401-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,856 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1094 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-402-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,821 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1095 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-403-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,817 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1096 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-404-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,871 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1097 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-405-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,821 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1098 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-406-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,853 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1099 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley *Air Pollution Control District*

PERMIT UNIT: N-266-407-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1101 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-408-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1102 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-409-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1103 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley *Air Pollution Control District*

PERMIT UNIT: N-266-410-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1104 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-411-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1105 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-412-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1106 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-413-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1107 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-414-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,544 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1108 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-415-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1109 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-416-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1110 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-417-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1111 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-418-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1121 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-419-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1122 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-420-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1123 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-421-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1124 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-422-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1125 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-423-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1126 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-424-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1127 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-425-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1128 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-426-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1129 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-427-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1130 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-428-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1131 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-429-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1141 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-430-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1142 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-431-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1143 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-432-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1144 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-433-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1145 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-434-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1146 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley *Air Pollution Control District*

PERMIT UNIT: N-266-435-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1147 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-436-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1148 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-437-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

3,613 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1149 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-438-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

3,613 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1150 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-439-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

3,613 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1151 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-440-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

3,613 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1152 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-441-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

88,432 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1201 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-442-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

88,432 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1202 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-443-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

88,471 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1203 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-444-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

88,247 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1204 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-445-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

101,348 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1205 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-446-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

102,041 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1206 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-447-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

101,637 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1207 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-448-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

101,750 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1208 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-449-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

88,281 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1211 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-450-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

88,526 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1212 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-451-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

88,264 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1213 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-452-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

88,459 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1214 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-453-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

101,234 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1215 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-454-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

101,638 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1216 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-455-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

102,042 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1217 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-456-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

101,703 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1218 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-457-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

49,867 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1221 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-458-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,030 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1222 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-459-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

49,869 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1223 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-460-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

49,854 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1224 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-461-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

49,633 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1225 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-462-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

49,610 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1226 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-463-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,050 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1227 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-464-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,087 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1228 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-465-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

49,820 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1231 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-466-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

49,835 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1232 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-467-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,078 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1233 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-468-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

49,836 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1234 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-469-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

49,640 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1235 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-470-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

49,603 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1236 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-471-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,080 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1237 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-472-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,093 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1238 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-473-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,422 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1241 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-474-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,512 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1242 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-475-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,381 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1243 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-476-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,495 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1244 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-477-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,403 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1245 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-478-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,501 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1246 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-479-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,422 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1247 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-480-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,414 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1248 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-481-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,414 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1249 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-482-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,299 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1250 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-483-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,532 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1251 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-484-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,633 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1252 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-485-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,565 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1253 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-486-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,442 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1254 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-487-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,403 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1255 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-488-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,403 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1256 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-489-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,186 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1257 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley *Air Pollution Control District*

PERMIT UNIT: N-266-490-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,411 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1258 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-491-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,299 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1259 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-492-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,403 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1260 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-493-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,318 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1261 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-494-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,318 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1262 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-495-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,318 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1263 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-496-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,318 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1264 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-497-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,318 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1265 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-498-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,318 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1266 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-499-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,458 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1267 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-500-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,458 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1268 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-501-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,425 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1269 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-502-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,425 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1270 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-503-5

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

5.978 MMBTU/HR FULTON BOILER EQUIPPED WITH FULTON MODEL 102347 BURNER

PERMIT UNIT REQUIREMENTS

1. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
3. The unit shall only be fired on PUC-quality natural gas. [District Rules 2201, 4201 and 4320] Federally Enforceable Through Title V Permit
4. This boiler shall be equipped with an operational, non-resettable, totalizing fuel flow meter that records the quantity of fuel into this boiler. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Heat input rate to this unit shall not exceed 125 MMBtu in any one day (equal to use of 125,000 scf/day of natural gas). [District Rule 2201] Federally Enforceable Through Title V Permit
6. NOx emissions shall not exceed 9 ppmvd @ 3% O₂ (0.011 lb/MMBtu) referenced as NO₂. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
7. CO emissions shall not exceed 50 ppmvd @ 3% O₂ (0.037 lb/MMBtu). [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
8. SOx emissions shall not exceed 0.00285 lb/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
9. PM₁₀ emissions shall not exceed 0.003 lb/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
10. VOC emissions shall not exceed 0.004 lb/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
12. Source testing to measure NOx and CO emissions shall be conducted at least once every twelve months. After demonstrating compliance on two consecutive annual source tests, the unit shall be tested not less than once every thirty-six months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve months. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
13. NOx emissions for source test purposes shall be determined using EPA Method 7E or ARB Method 100 on a ppmv basis, or EPA Method 19 on a heat input basis. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
14. CO emissions for source test purposes shall be determined using EPA Method 10 or ARB Method 100. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: DELICATO VINEYARDS

Location: 12001 S HIGHWAY 99,MANTECA, CA 95336

N-266-503-5 : Sep 15 2021 1:00PM -- NORMANR

15. Stack gas oxygen (O₂) shall be determined using EPA Method 3 or 3A or ARB Method 100. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
16. Fuel sulfur content shall be determined using EPA Method 11 or Method 15. [District Rule 4320] Federally Enforceable Through Title V Permit
17. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
18. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
19. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
20. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
21. The permittee shall monitor and record the stack concentration of NO_x, CO, and O₂ at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
22. If either the NO_x or CO concentrations corrected to 3% O₂, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of performing the notification and testing required by this condition. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
23. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
24. The permittee shall maintain records of: (1) the date and time of NO_x, CO, and O₂ measurements, (2) the O₂ concentration in percent and the measured NO_x and CO concentrations corrected to 3% O₂, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
25. Permittee shall determine sulfur content of combusted gas annually or shall demonstrate that the combusted gas is provided from a PUC or FERC regulated source. [District Rules 1081 and 4320] Federally Enforceable Through Title V Permit
26. The permittee shall maintain daily records of the fuel combusted (scf/day) in this boiler. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

27. All records shall be maintained and retained on-site for a period of at least 5 years and shall be made available for District inspection upon request. [District Rules 1070, 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-569-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,184 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1229 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-570-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,184 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1230 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-571-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,184 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1239 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-572-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,184 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1240 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-573-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1271 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-574-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1272 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-575-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1273 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-576-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1274 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-577-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1401 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-578-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1402 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-579-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1403 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-580-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1404 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-581-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1405 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-582-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1406 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-583-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1407 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-584-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1408 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-585-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1409 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-586-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1410 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-587-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1411 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-588-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1412 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-589-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1413 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-590-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1414 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-591-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1415 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-592-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1416 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-593-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1417 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-594-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1418 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-595-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1419 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley *Air Pollution Control District*

PERMIT UNIT: N-266-596-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1420 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-597-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1421 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-599-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1422 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-600-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1423 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-601-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1424 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-602-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1425 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-603-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1426 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-604-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1427 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-605-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1428 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-606-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1431 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-607-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1432 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-608-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1433 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-609-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1434 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-610-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1435 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-611-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1436 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-612-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1437 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-613-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1438 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-614-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

103,660 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1441 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-615-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

103,660 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1442 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-616-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

103,660 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1443 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-617-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

103,660 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1444 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-618-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

103,660 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1451 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-619-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

103,660 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1452 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-620-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

103,660 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1453 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-621-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

103,660 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1454 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-622-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

103,660 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1461 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-623-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

103,660 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1462 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-624-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

103,660 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1463 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-625-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

103,660 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1464 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-626-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

103,660 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1465 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-627-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

103,660 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1466 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-628-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

103,660 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1471 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-629-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

103,660 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1472 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-630-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

103,660 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1473 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-631-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

103,660 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1474 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-632-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

103,660 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1475 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-633-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

103,660 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1476 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-634-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

74,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 185 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-635-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

74,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 186 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-636-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

74,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 193 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-637-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

74,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 194 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-638-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

74,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 195 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-639-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

74,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 196 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-640-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

ORGANIC WASTE AND FEEDSTOCK MATERIAL RECEIVING, STORAGE, AND MIXING OPERATION.

PERMIT UNIT REQUIREMENTS

1. All materials for processing shall be maintained adequately moist to prevent visible emissions in excess of 20% opacity. [District Rule 4101] Federally Enforceable Through Title V Permit
2. The permittee is allowed to receive the following wastes for the composting operation: green waste, food waste, and construction wood waste. Green waste is defined as any organic waste material generated from gardening, agriculture, or landscaping activities including, but not limited to grass clippings, leave, tree and shrub trimmings, and plant remains. Food waste is defined as table scraps, vegetable and fruit peelings, meat, bones and fish, egg shells, solid dairy products, coffee grounds, bread and toast, paper waste including, but not limited to, napkins, towels, plates, coffee filters, and tea bags. Construction wood waste is defined as any untreated wood materials, including but not limited to, lumber, paper, and cardboard from construction. [District Rule 2010] Federally Enforceable Through Title V Permit
3. The permittee is prohibited to receive the following wastes for the composting operation: biosolids, animal manure, and poultry litter. Biosolids is defined as organic material resulting from the treatment os sewage sludge or wastewater. Animal manure is defines as non-human animal excretions and waste, including, but not limited to, dried solids and urine from cows, cattle, or swine. Poultry litter is defined as poultry excretions and waste, including, but not limited to, dried solids and urine from chickens, turkeys, geese, or ducks. [District Rule 2010] Federally Enforceable Through Title V Permit
4. The quantity of organic waste materials received at this facility shall not exceed 900 wet-tons in any single day and 82,000 wet tons in any one calendar year. For the purposes of this permit, organic waste material is considered to be green waste, food waste, and construction wood waste. [District Rules 2201 and 4566] Federally Enforceable Through Title V Permit
5. PM10 emissions from the receiving, handling, and mixing of the organic waste materials shall not exceed 0.00167 lb-PM10/wet-ton of material received and processed. [District Rule 2201] Federally Enforceable Through Title V Permit
6. VOC emissions from the storage and processing of the organic waste materials shall not exceed 10.63 lb-VOC/wet-ton of material stored and processed. [District Rule 2201] Federally Enforceable Through Title V Permit
7. NH3 emissions from the storage and processing of the organic waste materials shall not exceed 3.18 lb-NH3/wet-ton of material stored and processed. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The operator shall perform one of the following to organic materials within 10 days of receipt at the facility to satisfy the stockpile requirements: (a). Remove the organic material from the facility; (b). Place the organic material in the active-phase composting windrow and start active phase composting; (c). Cover the organic material with a waterproof cover that have at least a six-foot overlap of adjacent sheets and be securely anchored. [District Rule 4566] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

9. A daily operations log shall be maintained and shall include the following: (a) The date, type, and weight (in wet tons) of each organic material received; (b). The date each stockpile was initially formed; (c). The date and action taken on each stockpile to satisfy the stockpile requirements; (d). Total quantity and type of each organic waste material stored for composting (in wet tons); (e). Total quantity and type of each organic waste material mixed for composting (in wet tons); and (f). Any other information necessary to demonstrate compliance with Rule 4566. [District Rules 1070 & 4566] Federally Enforceable Through Title V Permit
10. A cumulative annual log shall be maintained and shall indicate the total quantity and type of each organic waste material received (in wet tons). The records shall be updated at least monthly. [District Rule 1070] Federally Enforceable Through Title V Permit
11. All records shall be maintained and retained on-site for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 1070 & 4566] Federally Enforceable Through Title V Permit
12. This permit does not authorize the facility to operate without the required permits from other local, state or federal agency and does not authorize the violation of any conditions established for this facility in the Conditional Use Permit (CUP), Special Use Permit (SUP), Site Approval, Site Plan Review (SPR), or other approval documents issued by a local, state or federal agency. [District Rules 2070 and 2080, and Public Resources Code 21000-21177: California Environmental Quality Act] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-641-3

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

OPEN WINDROW ACTIVE AND CURING PHASE ORGANIC MATERIAL COMPOSTING OPERATION WITH AN INDEPENDENT WATERING SYSTEM SERVING THE ACTIVE-PHASE COMPOSTING WINDROW PILES.

PERMIT UNIT REQUIREMENTS

1. All materials for processing shall be maintained adequately moist to prevent visible emissions in excess of 20% opacity. [District Rule 4101] Federally Enforceable Through Title V Permit
2. PM10 emissions from the organic material composting operation shall not exceed 0.6 pounds in any single day. Compliance with this condition shall be demonstrated using the following equation: $PM10 \text{ Emissions (lb/day)} = 0.00066 \text{ lb-PM10/wet-ton} \times \text{Total daily quantity of material transferred from the feedstock piles to active-phase composting windrows (in wet-tons/day)}$. [District Rule 2201] Federally Enforceable Through Title V Permit
3. VOC emissions from the organic material composting operation shall not exceed 360.2 pounds in any single day. Compliance with this condition shall be demonstrated using the following equation: $VOC \text{ Emissions (lb/day)} = 0.06966 \text{ lb-VOC/wet-ton} \times \text{Total daily quantity of active phase composting piles utilized onsite (in wet-tons/day)} + 0.0095 \text{ lb-VOC/wet-ton} \times \text{Total quantity of curing phase composting piles utilized onsite (in wet-tons/day)}$. [District Rule 2201] Federally Enforceable Through Title V Permit
4. NH3 emissions from the organic material composting operation shall not exceed 86.0 pounds in any single day. Compliance with this condition shall be demonstrated using the following equation: $NH3 \text{ Emissions (lb/day)} = 0.017 \text{ lb-NH3/wet-ton} \times \text{Total daily quantity of active phase composting piles utilized onsite (in wet-tons/day)} + 0.0019 \text{ lb-NH3/wet-ton} \times \text{Total daily quantity of curing phase composting piles utilized onsite (in wet-tons/day)}$. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The total quantity of organic materials composted shall not exceed 82,000 wet tons in any one calendar year. [District Rules 2201 & 4566] Federally Enforceable Through Title V Permit
6. The operator shall implement at least three turns of each organic material composting windrow during the active-phase of the composting process. [District Rule 4566]
7. The operator shall install, maintain, and utilize an independent watering system to apply water to the surface of each active-phase composting windrow prior to turning. The operator shall test each windrow within three hours before turning for adequate water by taking a sample of the organic material in the windrow and passing a "Ball Test". The "Ball Test" is performed by taking a sample of the compostable material from at least three inches below the surface, between the vertical midpoint and the peak of the windrow and forming the sample into a ball using hand pressure. There should be at least enough water in the material to form a ball when compressed by hand, but the ball may break when tapped. If the material cannot form a ball or crumbles during the ball test, then application of additional water to the windrow prior to turning is required until the material passes the ball test. If a rain event occurs prior to turning the windrow, application of additional water to the surface of the windrow will not be required if the material passes the ball test as previously described. [District Rule 4566] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

8. A daily operations log shall be maintained and shall include the following: (a). The date and time the organic material from the windrow was tested for adequate water content using the "Ball Test" and indicate if the material passed the ball test. If the windrow material did not pass the ball test indicate the corrective action taken; (b). The date and time each windrow was turned; (c). Total quantity of organic material transferred from the feedstock piles to the active-phase composting windrows (in wet tons); (d). Total quantity of active phase composting piles utilized onsite (in wet tons); (e). Total quantity of curing phase composting piles utilized onsite (in wet tons); and (f). Any other information necessary to demonstrate compliance with Rule 4566. [District Rules 1070 & 4566] Federally Enforceable Through Title V Permit
9. A cumulative annual log shall be maintained and shall include the following: (a). Total quantity of active-phase composting piles utilized onsite (in wet tons); (b). Total quantity of curing phase composting piles utilized onsite (in wet tons). The records shall be updated at least monthly. [District Rule 1070] Federally Enforceable Through Title V Permit
10. All records shall be maintained and retained on-site for a period of at least 5 years and shall be made available for District inspection upon request. [District Rules 1070 & 4566] Federally Enforceable Through Title V Permit
11. This permit does not authorize the facility to operate without the required permits from other local, state or federal agency and does not authorize the violation of any conditions established for this facility in the Conditional Use Permit (CUP), Special Use Permit (SUP), Site Approval, Site Plan Review (SPR), or other approval documents issued by a local, state or federal agency. [District Rules 2070 and 2080, and Public Resources Code 21000-21177: California Environmental Quality Act] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-642-2

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

FINISHED COMPOST LOADOUT OPERATION.

PERMIT UNIT REQUIREMENTS

1. All materials for processing shall be maintained adequately moist to prevent visible emissions in excess of 20% opacity. [District Rule 4101] Federally Enforceable Through Title V Permit
2. A daily log shall be maintained and shall indicate the number of vehicles used to load out finished compost and the total quantity of finished compost loaded out (in wet tons). [District Rule 1070 and San Joaquin County Rule 107] Federally Enforceable Through Title V Permit
3. A cumulative annual log shall be maintained and shall indicate the total quantity of finished compost loaded out (in wet tons). The records shall be updated at least monthly. [District Rule 1070 and San Joaquin County Rule 107] Federally Enforceable Through Title V Permit
4. All records shall be maintained and retained on-site for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 1070 and San Joaquin County Rule 107] Federally Enforceable Through Title V Permit
5. This permit does not authorize the facility to operate without the required permits from other local, state, or federal agency and does not authorize the violation of any conditions established for this facility in the Conditional Use Permit (CUP), Special Use Permit (SUP), Site Approval, Site Plan Review (SPR), or other approval documents issued by a local, state, or federal agency. [District Rules 2070 and 2080] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-643-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B22 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-644-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B24 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-645-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B19 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-646-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B20 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-647-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B21 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-648-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B23 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-649-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

14,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B08 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-650-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

14,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B09 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-651-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

14,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B17 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-652-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

14,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B18 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-653-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,700 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B06 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-654-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,700 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B07 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-655-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,700 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B15 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-656-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

12,700 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B16 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley *Air Pollution Control District*

PERMIT UNIT: N-266-657-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

8,500 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B04 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley *Air Pollution Control District*

PERMIT UNIT: N-266-658-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

8,500 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B05 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-659-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

8,500 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B13 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-660-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

8,500 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B14 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-661-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,200 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B01 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley *Air Pollution Control District*

PERMIT UNIT: N-266-662-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,200 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B02 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-663-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,200 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B03 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-664-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,200 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B10 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley *Air Pollution Control District*

PERMIT UNIT: N-266-665-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,200 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B11 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-666-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

6,200 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B12 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-667-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

200,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 352 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-668-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

200,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 353 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-669-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

200,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 354 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-670-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

200,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 355 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-671-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

200,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 356 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-672-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

200,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 362 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-673-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

200,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 363 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-674-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

200,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 364 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-675-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

200,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 365 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-676-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

200,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 366 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-678-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

70,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 712 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-679-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

70,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 714 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-680-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

70,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 715 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-681-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

70,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 716 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-682-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

70,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 717 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-683-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

70,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 718 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-684-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

70,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 719 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-685-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

70,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 720 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-686-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

70,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 721 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-687-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

70,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 722 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-688-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

70,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 723 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-689-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

70,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 724 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-690-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

70,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 725 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-691-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

70,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 726 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-692-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

70,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 727 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-693-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

70,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 728 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-694-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

70,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 729 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-695-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

70,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 730 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-696-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

70,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 731 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-697-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

70,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 733 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-698-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1507 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley *Air Pollution Control District*

PERMIT UNIT: N-266-699-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1508 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-700-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1509 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-701-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1510 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-702-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1517 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-703-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1518 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-704-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1519 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-705-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1520 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-706-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1527 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-707-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1528 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-708-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1529 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-709-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1530 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-710-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1537 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley *Air Pollution Control District*

PERMIT UNIT: N-266-711-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1538 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-712-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1539 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley *Air Pollution Control District*

PERMIT UNIT: N-266-713-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1540 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-714-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1547 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-715-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1548 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-716-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1549 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-717-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1550 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-718-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1557 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-719-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1558 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-720-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1559 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley *Air Pollution Control District*

PERMIT UNIT: N-266-721-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1560 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-722-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,000 GALLON, INSULATED, STAINLESS STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 2501 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-723-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,000 GALLON, INSULATED, STAINLESS STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 2502 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley *Air Pollution Control District*

PERMIT UNIT: N-266-724-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,000 GALLON, INSULATED, STAINLESS STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 2503 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-725-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,000 GALLON, INSULATED, STAINLESS STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 2504 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-726-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,000 GALLON, INSULATED, STAINLESS STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 2511 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-727-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,000 GALLON, INSULATED, STAINLESS STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 2512 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-728-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,000 GALLON, INSULATED, STAINLESS STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 2513 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-729-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,000 GALLON, INSULATED, STAINLESS STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 2514 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-730-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

13,000 GALLON, INSULATED, STAINLESS STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1321 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley *Air Pollution Control District*

PERMIT UNIT: N-266-731-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

13,000 GALLON, INSULATED, STAINLESS STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1322 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-732-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

13,000 GALLON, INSULATED, STAINLESS STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1323 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-733-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

13,000 GALLON, INSULATED, STAINLESS STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1324 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley *Air Pollution Control District*

PERMIT UNIT: N-266-734-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

13,000 GALLON, INSULATED, STAINLESS STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1325 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-735-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

13,000 GALLON, INSULATED, STAINLESS STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1326 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-736-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

13,000 GALLON, INSULATED, STAINLESS STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1327 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-737-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

13,000 GALLON, INSULATED, STAINLESS STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1328 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-738-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

7,000 GALLON, INSULATED, STAINLESS STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1314 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-739-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

7,000 GALLON, INSULATED, STAINLESS STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1315 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-740-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

7,000 GALLON, INSULATED, STAINLESS STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1319 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-741-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

7,000 GALLON, INSULATED, STAINLESS STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1320 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-742-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK
1505 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-743-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK
1506 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-744-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK
1515 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-745-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK
1516 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-746-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK
1525 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-747-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK
1526 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-748-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK
1536 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-749-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK
1535 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-750-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

60,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 230
EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-751-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

60,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 231
EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-752-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

60,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 232
EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-753-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

60,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 233
EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley *Air Pollution Control District*

PERMIT UNIT: N-266-754-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

60,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 234
EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-755-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

60,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 235
EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-756-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

60,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 236
EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-757-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

60,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 237
EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-758-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

60,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 239
EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-759-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

60,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 243
EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-760-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 2505
EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-761-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 2506
EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-762-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 2515
EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-763-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

25,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 2516
EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley *Air Pollution Control District*

PERMIT UNIT: N-266-764-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

13,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1329
EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-765-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

13,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1330
EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-766-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

13,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1331
EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-767-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

13,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1332
EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-768-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

13,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1333
EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-769-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

13,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1334
EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-770-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

13,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1335
EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-771-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

13,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1336
EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-772-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

7,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1312
EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-773-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

7,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1313
EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-774-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

7,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1317
EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-775-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

7,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1318
EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley *Air Pollution Control District*

PERMIT UNIT: N-266-776-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON (OR EQUIVALENT) WINE STORAGE TANK (TANK #1545) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed ten times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from permit units N-266-776 through -783, calculated on a rolling 12-month total basis, shall not exceed 5,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
13. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
14. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley *Air Pollution Control District*

PERMIT UNIT: N-266-777-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON (OR EQUIVALENT) WINE STORAGE TANK (TANK #1546) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed ten times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from permit units N-266-776 through -783, calculated on a rolling 12-month total basis, shall not exceed 5,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
13. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
14. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley *Air Pollution Control District*

PERMIT UNIT: N-266-778-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

60,000 GALLON (OR EQUIVALENT) WINE STORAGE TANK (TANK #242) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed ten times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from permit units N-266-776 through -783, calculated on a rolling 12-month total basis, shall not exceed 5,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
13. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
14. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley *Air Pollution Control District*

PERMIT UNIT: N-266-779-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

60,000 GALLON (OR EQUIVALENT) WINE STORAGE TANK (TANK #238) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed ten times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from permit units N-266-776 through -783, calculated on a rolling 12-month total basis, shall not exceed 5,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
13. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
14. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-780-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

60,000 GALLON (OR EQUIVALENT) WINE STORAGE TANK (TANK #240) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed ten times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from permit units N-266-776 through -783, calculated on a rolling 12-month total basis, shall not exceed 5,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
13. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
14. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley *Air Pollution Control District*

PERMIT UNIT: N-266-781-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

60,000 GALLON (OR EQUIVALENT) WINE STORAGE TANK (TANK #241) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed ten times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from permit units N-266-776 through -783, calculated on a rolling 12-month total basis, shall not exceed 5,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
13. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
14. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley *Air Pollution Control District*

PERMIT UNIT: N-266-782-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

60,000 GALLON (OR EQUIVALENT) WINE STORAGE TANK (TANK #244) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed ten times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from permit units N-266-776 through -783, calculated on a rolling 12-month total basis, shall not exceed 5,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
13. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
14. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley *Air Pollution Control District*

PERMIT UNIT: N-266-783-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

60,000 GALLON (OR EQUIVALENT) WINE STORAGE TANK (TANK #245) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed ten times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from permit units N-266-776 through -783, calculated on a rolling 12-month total basis, shall not exceed 5,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
13. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
14. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-784-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON NOMINAL (154,433 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1502) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-785-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON NOMINAL (154,443 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1503) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-786-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON NOMINAL (153,888 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1504) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This Authority to Construct serves as a written certificate of conformity with the procedural requirements of 40 CFR 70.7 and 70.8 and with the compliance requirements of 40 CFR 70.6(c). [District Rule 2201] Federally Enforceable Through Title V Permit
2. Prior to operating with modifications authorized by this Authority to Construct, the facility shall submit an application to modify the Title V permit with an administrative amendment in accordance with District Rule 2520 Section 5.3.4. [District Rule 2520, 5.3.4] Federally Enforceable Through Title V Permit
3. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
4. The nominal tank dimensions are 25 feet in diameter and 40 feet in height with a proposed volume of 154,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
5. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
7. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
11. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

12. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
18. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
19. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
20. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
21. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley *Air Pollution Control District*

PERMIT UNIT: N-266-787-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON NOMINAL (153,785 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1511) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley *Air Pollution Control District*

PERMIT UNIT: N-266-788-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON NOMINAL (154,308 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1512) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-789-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON NOMINAL (154,435 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1513) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-790-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON NOMINAL (153,842 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1514) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-791-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON NOMINAL (153,537 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1521) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley *Air Pollution Control District*

PERMIT UNIT: N-266-792-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON NOMINAL (153,932 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1522) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-793-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON NOMINAL (153,842 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1523) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-794-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON NOMINAL (153,986 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1524) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-795-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON NOMINAL (153,365 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK #(1531) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-796-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON NOMINAL (154,523 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1532) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-797-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON NOMINAL (154,208 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1533) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-798-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON NOMINAL (154,066 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1534) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-799-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON NOMINAL (153,935 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1541) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-800-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON NOMINAL (154,107 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1542) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley *Air Pollution Control District*

PERMIT UNIT: N-266-801-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON NOMINAL (153,458 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1543) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley *Air Pollution Control District*

PERMIT UNIT: N-266-802-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON NOMINAL (153,940 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1544) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley *Air Pollution Control District*

PERMIT UNIT: N-266-803-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON NOMINAL (154,170 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1551) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley *Air Pollution Control District*

PERMIT UNIT: N-266-804-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON NOMINAL (154,342 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1552) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-805-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

154,000 GALLON NOMINAL (153,842 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1553) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-806-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

103,000 GALLON NOMINAL (103,315 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1161) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley *Air Pollution Control District*

PERMIT UNIT: N-266-807-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

103,000 GALLON NOMINAL (103,315 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1162) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley *Air Pollution Control District*

PERMIT UNIT: N-266-808-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

103,000 GALLON NOMINAL (103,826 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1163) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-266-809-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

103,000 GALLON NOMINAL (103,705 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1164) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley *Air Pollution Control District*

PERMIT UNIT: N-266-810-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

103,000 GALLON NOMINAL (103,477 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1171) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-811-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

103,000 GALLON NOMINAL (103,712 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1172) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley *Air Pollution Control District*

PERMIT UNIT: N-266-812-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

103,000 GALLON NOMINAL (103,351 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1173) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-813-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

103,000 GALLON NOMINAL (103,302 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1174) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-814-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

103,000 GALLON NOMINAL (103,603 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1181) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley *Air Pollution Control District*

PERMIT UNIT: N-266-815-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

103,000 GALLON NOMINAL (103,480 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1182) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley *Air Pollution Control District*

PERMIT UNIT: N-266-816-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

103,000 GALLON NOMINAL (103,508 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1183) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-817-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

103,000 GALLON NOMINAL (102,777 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1184) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley *Air Pollution Control District*

PERMIT UNIT: N-266-818-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

103,000 GALLON NOMINAL (103,408 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1191) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley *Air Pollution Control District*

PERMIT UNIT: N-266-819-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

103,000 GALLON NOMINAL (103,088 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1192) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-820-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

103,000 GALLON NOMINAL (102,901 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1193) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley *Air Pollution Control District*

PERMIT UNIT: N-266-821-1

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

103,000 GALLON NOMINAL (103,826 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1194) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = a * P^2 + b * P + c$; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24), $a = -0.38194$, $b = 0.97917$ and $c = 0$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-950-0

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

DIATOMACEOUS EARTH (DE) MATERIAL RECEIVING, STORAGE, AND TRANSFER OPERATION CONSISTING OF ONE 8,200 CUBIC FOOT STORAGE SILO SERVED BY FOUR DYNAMIC AIR MODEL MODU-KLEEN SERIES 343/200 BIN VENT FILTERS, AND THREE ENCLOSED HOPPERS EACH SERVED BY A DYNAMIC AIR MODEL MODU-KLEEN SERIES 343/200 BIN VENT FILTER

PERMIT UNIT REQUIREMENTS

1. The bin vent filter shall be maintained and operated according to manufacturer's specifications. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The bin vent filter cleaning frequency and duration shall be adjusted to optimize the control efficiency. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Emissions shall not exceed 0.00086 lb PM10 per ton of DE processed. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The maximum throughput for the receiving/pre-cleaning operation shall not exceed 50 tons of DE per day. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The maximum throughput for the transfer to the hoppers shall not exceed 50 tons of DE per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
7. Records of all maintenance of the bin vent filters, including all change outs of filter media, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Daily records of DE processed shall be maintained, retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-952-0

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

250 BHP (INTERMITTENT) JOHN DEERE MODEL 6068HF485T TIER 3 CERTIFIED DIESEL-FIRED EMERGENCY STANDBY IC ENGINE POWERING A FIRE PUMP

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. This engine shall be equipped with an operational non-resettable elapsed time meter or other APCO approved alternative. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
3. Only CARB certified diesel fuel containing not more than 0.0015% sulfur by weight is to be used. [District Rules 2201 and 4801, 17 CCR 93115, and 40 CFR Part 60 Subpart III] Federally Enforceable Through Title V Permit
4. Emissions from this IC engine shall not exceed any of the following limits: 2.47 g-NOx/bhp-hr, 0.45 g-CO/bhp-hr, or 0.08 g-VOC/bhp-hr. [District Rules 2201 and 4801, 17 CCR 93115, and 40 CFR 60 Subpart III] Federally Enforceable Through Title V Permit
5. Emissions from this IC engine shall not exceed 0.07 g-PM10/bhp-hr based on USEPA certification using ISO 8178 test procedure. [District Rules 2201 and 4102, 17 CCR 93115, and 40 CFR 60 Subpart III] Federally Enforceable Through Title V Permit
6. This engine shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier. [District Rule 4702 and 40 CFR 60 Subpart III] Federally Enforceable Through Title V Permit
7. This engine shall be operated only for testing and maintenance of the engine, required regulatory purposes, and during emergency situations. For testing purposes, the engine shall only be operated the number of hours necessary to comply with the testing requirements of the National Fire Protection Association (NFPA) 25 - "Standard for the Inspection, Testing, and Maintenance of Water-Based Fire Protection Systems", 2002 edition. Total hours of operation for all maintenance, testing, and required regulatory purposes shall not exceed 100 hours per calendar year. [District Rules 2201, 4102, 4701 and 4702, 17 CCR 93115, and 40 CFR 60 Subpart III] Federally Enforceable Through Title V Permit
8. During periods of operation for maintenance, testing, and required regulatory purposes, the permittee shall monitor the operational characteristics of the engine as recommended by the manufacturer or emission control system supplier (for example: check engine fluid levels, battery, cables and connections; change engine oil and filters; replace engine coolant; and/or other operational characteristics as recommended by the manufacturer or supplier). [District Rule 4702] Federally Enforceable Through Title V Permit
9. The permittee shall maintain monthly records of emergency and non-emergency operation. Records shall include the number of hours of emergency operation, the date and number of hours of all testing and maintenance operations, and the purpose of the operation (for example: load testing, weekly testing, emergency usage, etc.). For units with automated testing systems, the operator may, as an alternative to keeping records of actual operation for testing purposes, maintain a readily accessible written record of the automated testing schedule. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. The permittee shall maintain monthly records of the type of fuel purchased. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
11. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley

Air Pollution Control District

PERMIT UNIT: N-266-953-0

EXPIRATION DATE: 10/31/2020

EQUIPMENT DESCRIPTION:

302 BHP (INTERMITTENT) DOOSAN MODEL D111L RICH-BURN NATURAL GAS-FIRED EMERGENCY STANDBY IC ENGINE WITH NON-SELECTIVE CATALYTIC REDUCTION (NSCR) POWERING AN ELECTRICAL GENERATOR

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101] Federally Enforceable Through Title V Permit
2. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
3. Emissions from this IC engine shall not exceed any of the following limits: 0.022 g-NOx/bhp-hr, 0.063 g-PM10/bhp-hr, 0.216 g-CO/bhp-hr, or 0.254 g-VOC/bhp-hr. [District Rule 2201] Federally Enforceable Through Title V Permit
4. This IC engine shall be equipped with a three-way catalyst. [District Rule 2201] Federally Enforceable Through Title V Permit
5. This IC engine shall be fired on Public Utility Commission (PUC) regulated natural gas only. [District Rules 2201 and 4801] Federally Enforceable Through Title V Permit
6. This engine shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier. [District Rule 4702] Federally Enforceable Through Title V Permit
7. During periods of operation for maintenance, testing, and required regulatory purposes, the permittee shall monitor the operational characteristics of the engine as recommended by the manufacturer or emission control system supplier (for example: check engine fluid levels, battery, cables and connections; change engine oil and filters; replace engine coolant; and/or other operational characteristics as recommended by the manufacturer or supplier). [District Rule 4702] Federally Enforceable Through Title V Permit
8. The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102] Federally Enforceable Through Title V Permit
9. This engine shall be equipped with an operational non-resettable elapsed time meter or other APCO approved alternative. [District Rule 4702] Federally Enforceable Through Title V Permit
10. An emergency situation is an unscheduled electrical power outage caused by sudden and reasonably unforeseen natural disasters or sudden and reasonably unforeseen events beyond the control of the permittee. [District Rule 4702] Federally Enforceable Through Title V Permit
11. This engine shall not be used to produce power for the electrical distribution system, as part of a voluntary utility demand reduction program, or for an interruptible power contract. [District Rule 4702] Federally Enforceable Through Title V Permit
12. This engine shall be operated only for testing and maintenance of the engine, required regulatory purposes, and during emergency situations. Operation of the engine for maintenance, testing, and required regulatory purposes shall not exceed 100 hours per calendar year. [District Rule 4702] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

13. The permittee shall maintain monthly records of emergency and non-emergency operation. Records shall include the number of hours of emergency operation, the date and number of hours of all testing and maintenance operations, the purpose of the operation (for example: load testing, weekly testing, rolling blackout, general area power outage, etc.) and records of operational characteristics monitoring. For units with automated testing systems, the operator may, as an alternative to keeping records of actual operation for testing purposes, maintain a readily accessible written record of the automated testing schedule. [District Rule 4702] Federally Enforceable Through Title V Permit
14. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 4702] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

ATTACHMENT C

Detailed Summary List of Facility Permits

Detailed Facility Report
For Facility=266 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

DELICATO VINEYARDS 12001 S HIGHWAY 99 MANTECA, CA 95336	FAC # STATUS: TELEPHONE:	N 266 A 2092391215	TYPE: TOXIC ID:	TitleV 70179	EXPIRE ON: AREA: INSP. DATE:	10/31/2020 11 / 302 03/22
--	--------------------------------	---	--------------------	-------------------------------	------------------------------------	--

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-266-1-6	1 nozzle	3020-11 A	1	42.00	42.00	A	GASOLINE DISPENSING OPERATION WITH ONE 4,000 GALLON (SPLIT 2,000 GALLON GASOLINE/2,000 GALLON DIESEL) CONVAULT ABOVEGROUND STORAGE TANK SERVED BY MORRISON BROTHERS PHASE I VAPOR RECOVERY SYSTEM (VR-402-B), STANDING LOSS CONTROL (VR-301-E), AND 1 FUELING POINT WITH 1 GASOLINE DISPENSING NOZZLE SERVED BY BALANCE PHASE II VAPOR RECOVERY SYSTEM (G-70-116F)
N-266-3-2	106 bhp	3020-10 B	1	143.00	143.00	A	106 HP DEUTZ MODEL NDC-BF4 M1013ES DIESEL-FIRED EMERGENCY IC ENGINE POWERING A FIRE PUMP.
N-266-9-3	14,579 Gallons	3020-05 B	1	113.00	113.00	A	14,579 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 34 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-10-3	14,707 Gallons	3020-05 B	1	113.00	113.00	A	14,707 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 35 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-20-3	7,184 Gallons	3020-05 B	1	113.00	113.00	A	7,184 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 45 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-21-3	7,192 Gallons	3020-05 B	1	113.00	113.00	A	7,192 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 46 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-22-3	7,180 Gallons	3020-05 B	1	113.00	113.00	A	7,180 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 47 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-23-3	7,168 Gallons	3020-05 B	1	113.00	113.00	A	7,168 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 48 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-24-3	7,151 Gallons	3020-05 B	1	113.00	113.00	A	7,151 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 49 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-25-3	7,188 Gallons	3020-05 B	1	113.00	113.00	A	7,188 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 50 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-26-3	7,192 Gallons	3020-05 B	1	113.00	113.00	A	7,192 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 51 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-27-3	7,201 Gallons	3020-05 B	1	113.00	113.00	A	7,201 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 52 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

Detailed Facility Report
For Facility=266 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-266-28-3	7,188 Gallons	3020-05 B	1	113.00	113.00	A	7,188 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 53 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-29-3	7,180 Gallons	3020-05 B	1	113.00	113.00	A	7,180 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 54 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-30-3	12,663 Gallons	3020-05 B	1	113.00	113.00	A	12,663 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 55 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-31-3	12,728 Gallons	3020-05 B	1	113.00	113.00	A	12,728 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 56 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-32-3	12,663 Gallons	3020-05 B	1	113.00	113.00	A	12,663 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 57 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-33-3	12,696 Gallons	3020-05 B	1	113.00	113.00	A	12,696 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 58 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-38-3	8,590 Gallons	3020-05 B	1	113.00	113.00	A	8,590 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 63 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-39-3	8,563 Gallons	3020-05 B	1	113.00	113.00	A	8,563 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 64 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-48-3	12,720 Gallons	3020-05 B	1	113.00	113.00	A	12,720 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 73 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-49-3	12,735 Gallons	3020-05 B	1	113.00	113.00	A	12,735 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 74 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-56-3	51,486 Gallons	3020-05 D	1	223.00	223.00	A	51,486 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 108 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-57-3	51,460 Gallons	3020-05 D	1	223.00	223.00	A	51,460 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 109 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-58-3	51,446 Gallons	3020-05 D	1	223.00	223.00	A	51,446 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 110 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-59-3	51,406 Gallons	3020-05 D	1	223.00	223.00	A	51,406 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 111 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

Detailed Facility Report
For Facility=266 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-266-60-3	51,446 Gallons	3020-05 D	1	223.00	223.00	A	51,446 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 112 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-61-3	51,460 Gallons	3020-05 D	1	223.00	223.00	A	51,460 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 113 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-62-3	51,433 Gallons	3020-05 D	1	223.00	223.00	A	51,433 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 114 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-63-3	51,420 Gallons	3020-05 D	1	223.00	223.00	A	51,420 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 115 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-64-3	51,446 Gallons	3020-05 D	1	223.00	223.00	A	51,446 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 116 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-65-3	51,433 Gallons	3020-05 D	1	223.00	223.00	A	51,433 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 117 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-66-3	51,460 Gallons	3020-05 D	1	223.00	223.00	A	51,460 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 118 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-67-3	51,500 Gallons	3020-05 D	1	223.00	223.00	A	51,500 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 119 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-68-3	51,700 Gallons	3020-05 D	1	223.00	223.00	A	51,700 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 120 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-69-3	51,500 Gallons	3020-05 D	1	223.00	223.00	A	51,500 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 121 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-70-3	51,500 Gallons	3020-05 D	1	223.00	223.00	A	51,500 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 122 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-71-3	51,687 Gallons	3020-05 D	1	223.00	223.00	A	51,687 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 123 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-72-3	51,741 Gallons	3020-05 D	1	223.00	223.00	A	51,741 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 124 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-73-3	51,674 Gallons	3020-05 D	1	223.00	223.00	A	51,674 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 125 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

Detailed Facility Report
For Facility=266 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-266-74-3	51,741 Gallons	3020-05 D	1	223.00	223.00	A	51,741 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 126 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-75-3	51,687 Gallons	3020-05 D	1	223.00	223.00	A	51,687 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 127 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-76-3	51,714 Gallons	3020-05 D	1	223.00	223.00	A	51,714 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 128 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-77-3	44,309 Gallons	3020-05 C	1	165.00	165.00	A	44,309 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 151 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-78-3	44,327 Gallons	3020-05 C	1	165.00	165.00	A	44,327 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 152 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-79-3	44,327 Gallons	3020-05 C	1	165.00	165.00	A	44,327 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 153 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-80-3	44,370 Gallons	3020-05 C	1	165.00	165.00	A	44,370 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 154 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-81-3	44,361 Gallons	3020-05 C	1	165.00	165.00	A	44,361 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 155 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-82-3	44,309 Gallons	3020-05 C	1	165.00	165.00	A	44,309 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 156 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-83-3	44,309 Gallons	3020-05 C	1	165.00	165.00	A	44,309 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 157 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-84-3	44,327 Gallons	3020-05 C	1	165.00	165.00	A	44,327 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 158 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-85-3	44,378 Gallons	3020-05 C	1	165.00	165.00	A	44,378 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 161 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-86-3	44,356 Gallons	3020-05 C	1	165.00	165.00	A	44,356 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 162 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-87-3	44,206 Gallons	3020-05 C	1	165.00	165.00	A	44,206 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 163 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

Detailed Facility Report
For Facility=266 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-266-88-3	44,361 Gallons	3020-05 C	1	165.00	165.00	A	44,361 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 164 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-89-3	44,155 Gallons	3020-05 C	1	165.00	165.00	A	44,155 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 165 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-90-3	44,206 Gallons	3020-05 C	1	165.00	165.00	A	44,206 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 166 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-91-3	44,327 Gallons	3020-05 C	1	165.00	165.00	A	44,327 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 167 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-92-3	44,344 Gallons	3020-05 C	1	165.00	165.00	A	44,344 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 168 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-93-3	44,176 Gallons	3020-05 C	1	165.00	165.00	A	44,176 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 171 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-94-3	44,335 Gallons	3020-05 C	1	165.00	165.00	A	44,335 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 172 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-95-3	44,172 Gallons	3020-05 C	1	165.00	165.00	A	44,172 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 173 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-96-3	44,361 Gallons	3020-05 C	1	165.00	165.00	A	44,361 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 174 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-97-3	44,206 Gallons	3020-05 C	1	165.00	165.00	A	44,206 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 175 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-98-3	44,155 Gallons	3020-05 C	1	165.00	165.00	A	44,155 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 176 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-99-3	44,172 Gallons	3020-05 C	1	165.00	165.00	A	44,172 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 177 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-100-3	44,206 Gallons	3020-05 C	1	165.00	165.00	A	44,206 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 178 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-101-3	73,375 Gallons	3020-05 D	1	223.00	223.00	A	73,375 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 187 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

Detailed Facility Report
For Facility=266 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-266-102-3	73,373 Gallons	3020-05 D	1	223.00	223.00	A	73,373 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 188 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-103-3	72,048 Gallons	3020-05 D	1	223.00	223.00	A	72,048 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 189 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-104-3	73,336 Gallons	3020-05 D	1	223.00	223.00	A	73,336 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 197 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-105-3	73,355 Gallons	3020-05 D	1	223.00	223.00	A	73,355 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 198 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-106-3	72,031 Gallons	3020-05 D	1	223.00	223.00	A	72,031 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 199 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-113-3	60,339 Gallons	3020-05 D	1	223.00	223.00	A	60,339 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 207 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-114-3	60,158 Gallons	3020-05 D	1	223.00	223.00	A	60,158 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 208 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-115-3	60,094 Gallons	3020-05 D	1	223.00	223.00	A	60,094 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 209 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-116-3	60,090 Gallons	3020-05 D	1	223.00	223.00	A	60,090 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 210 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-117-3	60,109 Gallons	3020-05 D	1	223.00	223.00	A	60,109 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 211 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-118-3	60,076 Gallons	3020-05 D	1	223.00	223.00	A	60,076 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 212 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-119-3	60,076 Gallons	3020-05 D	1	223.00	223.00	A	60,076 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 219 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-120-3	60,010 Gallons	3020-05 D	1	223.00	223.00	A	60,010 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 220 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-121-3	60,066 Gallons	3020-05 D	1	223.00	223.00	A	60,066 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 221 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

Detailed Facility Report
For Facility=266 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-266-122-3	60,109 Gallons	3020-05 D	1	223.00	223.00	A	60,109 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 222 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-123-3	60,058 Gallons	3020-05 D	1	223.00	223.00	A	60,058 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 229 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-124-3	127,903 Gallons	3020-05 E	1	296.00	296.00	A	127,903 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 250 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-125-3	127,709 Gallons	3020-05 E	1	296.00	296.00	A	127,709 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 251 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-126-3	128,223 Gallons	3020-05 E	1	296.00	296.00	A	128,223 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 252 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-127-3	128,327 Gallons	3020-05 E	1	296.00	296.00	A	128,327 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 253 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-128-3	127,566 Gallons	3020-05 E	1	296.00	296.00	A	127,566 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 254 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-129-3	128,256 Gallons	3020-05 E	1	296.00	296.00	A	128,256 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 255 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-130-3	128,493 Gallons	3020-05 E	1	296.00	296.00	A	128,493 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 256 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-131-3	127,579 Gallons	3020-05 E	1	296.00	296.00	A	127,579 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 260 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-132-3	128,016 Gallons	3020-05 E	1	296.00	296.00	A	128,016 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 261 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-133-3	127,129 Gallons	3020-05 E	1	296.00	296.00	A	127,129 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 262 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-134-3	128,290 Gallons	3020-05 E	1	296.00	296.00	A	128,290 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 263 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-135-3	128,467 Gallons	3020-05 E	1	296.00	296.00	A	128,467 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 264 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

Detailed Facility Report
For Facility=266 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-266-136-3	127,768 Gallons	3020-05 E	1	296.00	296.00	A	127,768 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 265 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-137-3	128,324 Gallons	3020-05 E	1	296.00	296.00	A	128,324 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 266 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-138-3	128,511 Gallons	3020-05 E	1	296.00	296.00	A	128,511 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 270 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-139-3	127,507 Gallons	3020-05 E	1	296.00	296.00	A	127,507 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 271 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-140-3	128,647 Gallons	3020-05 E	1	296.00	296.00	A	128,647 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 272 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-141-3	128,425 Gallons	3020-05 E	1	296.00	296.00	A	128,425 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 273 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-142-3	128,639 Gallons	3020-05 E	1	296.00	296.00	A	128,639 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 274 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-143-3	128,915 Gallons	3020-05 E	1	296.00	296.00	A	128,915 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 275 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-144-3	128,290 Gallons	3020-05 E	1	296.00	296.00	A	128,290 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 276 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-145-3	128,425 Gallons	3020-05 E	1	296.00	296.00	A	128,425 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 280 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-146-3	129,372 Gallons	3020-05 E	1	296.00	296.00	A	129,372 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 281 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-147-3	128,155 Gallons	3020-05 E	1	296.00	296.00	A	128,155 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 282 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-148-3	128,425 Gallons	3020-05 E	1	296.00	296.00	A	128,425 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 283 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-149-3	128,695 Gallons	3020-05 E	1	296.00	296.00	A	128,695 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 284 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

Detailed Facility Report
For Facility=266 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-266-150-3	128,670 Gallons	3020-05 E	1	296.00	296.00	A	128,670 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 285 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-151-3	128,636 Gallons	3020-05 E	1	296.00	296.00	A	128,636 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 286 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-152-3	127,738 Gallons	3020-05 E	1	296.00	296.00	A	127,738 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 290 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-153-3	129,435 Gallons	3020-05 E	1	296.00	296.00	A	129,435 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 291 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-154-3	127,535 Gallons	3020-05 E	1	296.00	296.00	A	127,535 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 292 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-155-3	23,100 Gallons	3020-05 C	1	165.00	165.00	A	23,100 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 293 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-156-3	23,100 Gallons	3020-05 C	1	165.00	165.00	A	23,100 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 294 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-157-3	23,100 Gallons	3020-05 C	1	165.00	165.00	A	23,100 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 295 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-158-3	23,100 Gallons	3020-05 C	1	165.00	165.00	A	23,100 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 296 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-159-3	23,100 Gallons	3020-05 C	1	165.00	165.00	A	23,100 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 297 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-160-3	352,002 Gallons	3020-05 E	1	296.00	296.00	A	352,002 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 301 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-161-3	350,790 Gallons	3020-05 E	1	296.00	296.00	A	350,790 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 302 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-162-3	351,769 Gallons	3020-05 E	1	296.00	296.00	A	351,769 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 303 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-163-3	351,655 Gallons	3020-05 E	1	296.00	296.00	A	351,655 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 304 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

Detailed Facility Report
For Facility=266 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-266-164-3	352,067 Gallons	3020-05 E	1	296.00	296.00	A	352,067 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 305 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-165-3	351,022 Gallons	3020-05 E	1	296.00	296.00	A	351,022 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 306 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-166-3	351,141 Gallons	3020-05 E	1	296.00	296.00	A	351,141 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 307 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-167-3	351,079 Gallons	3020-05 E	1	296.00	296.00	A	351,079 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 311 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-168-3	351,724 Gallons	3020-05 E	1	296.00	296.00	A	351,724 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 312 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-169-3	351,039 Gallons	3020-05 E	1	296.00	296.00	A	351,039 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 313 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-170-3	350,496 Gallons	3020-05 E	1	296.00	296.00	A	350,496 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 314 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-171-3	351,219 Gallons	3020-05 E	1	296.00	296.00	A	351,219 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 315 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-172-3	351,521 Gallon	3020-05 E	1	296.00	296.00	A	351,521 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 316 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-173-3	351,051 Gallons	3020-05 E	1	296.00	296.00	A	351,051 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 317 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-174-3	350,760 Gallons	3020-05 E	1	296.00	296.00	A	350,760 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 321 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-175-3	350,946 Gallons	3020-05 E	1	296.00	296.00	A	350,946 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 322 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-176-3	351,267 Gallons	3020-05 E	1	296.00	296.00	A	351,267 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 323 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-177-3	351,930 Gallons	3020-05 E	1	296.00	296.00	A	351,930 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 324 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

Detailed Facility Report
For Facility=266 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-266-178-3	352,374 Gallons	3020-05 E	1	296.00	296.00	A	352,374 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 325 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-179-3	351,625 Gallons	3020-05 E	1	296.00	296.00	A	351,625 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 326 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-180-3	351,374 Gallons	3020-05 E	1	296.00	296.00	A	351,374 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 327 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-181-3	351,125 Gallons	3020-05 E	1	296.00	296.00	A	351,125 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 331 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-182-3	351,178 Gallons	3020-05 E	1	296.00	296.00	A	351,178 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 332 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-183-3	349,827 Gallons	3020-05 E	1	296.00	296.00	A	349,827 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 333 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-184-3	352,011 Gallons	3020-05 E	1	296.00	296.00	A	352,011 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 334 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-185-3	350,672 Gallons	3020-05 E	1	296.00	296.00	A	350,672 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 335 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-186-3	352,014 Gallons	3020-05 E	1	296.00	296.00	A	352,014 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 336 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-187-3	351,229 Gallons	3020-05 E	1	296.00	296.00	A	351,229 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 337 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-188-3	351,941 Gallons	3020-05 E	1	296.00	296.00	A	351,941 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 341 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-189-3	352,833 Gallons	3020-05 E	1	296.00	296.00	A	352,833 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 342 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-190-3	351,917 Gallons	3020-05 E	1	296.00	296.00	A	351,917 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 343 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-191-3	351,965 Gallons	3020-05 E	1	296.00	296.00	A	351,965 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 344 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

Detailed Facility Report
For Facility=266 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-266-192-3	351,845 Gallons	3020-05 E	1	296.00	296.00	A	351,845 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 345 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-193-3	352,592 Gallons	3020-05 E	1	296.00	296.00	A	352,592 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 346 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-194-3	353,300 Gallons	3020-05 E	1	296.00	296.00	A	353,300 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 347 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-195-3	352,592 Gallons	3020-05 E	1	296.00	296.00	A	352,592 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 401 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-196-3	351,868 Gallons	3020-05 E	1	296.00	296.00	A	351,868 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 402 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-197-3	352,116 Gallons	3020-05 E	1	296.00	296.00	A	352,116 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 403 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-198-3	351,381 Gallons	3020-05 E	1	296.00	296.00	A	351,381 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 404 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-199-3	352,556 Gallons	3020-05 E	1	296.00	296.00	A	352,556 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 405 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-200-3	352,028 Gallons	3020-05 E	1	296.00	296.00	A	352,028 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 406 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-201-3	352,291 Gallons	3020-05 E	1	296.00	296.00	A	352,291 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 411 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-202-3	350,900 Gallons	3020-05 E	1	296.00	296.00	A	350,900 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 412 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-203-3	351,876 Gallons	3020-05 E	1	296.00	296.00	A	351,876 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 413 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-204-3	351,019 Gallons	3020-05 E	1	296.00	296.00	A	351,019 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 414 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-205-3	352,127 Gallons	3020-05 E	1	296.00	296.00	A	352,127 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 415 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

Detailed Facility Report
For Facility=266 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-266-206-3	352,381 Gallons	3020-05 E	1	296.00	296.00	A	352,381 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 416 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-207-3	351,750 Gallons	3020-05 E	1	296.00	296.00	A	351,750 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 421 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-208-3	351,575 Gallons	3020-05 E	1	296.00	296.00	A	351,575 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 422 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-209-3	351,991 Gallons	3020-05 E	1	296.00	296.00	A	351,991 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 423 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-210-3	351,503 Gallons	3020-05 E	1	296.00	296.00	A	351,503 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 424 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-211-3	351,404 Gallons	3020-05 E	1	296.00	296.00	A	351,404 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 425 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-212-3	352,189 Gallons	3020-05 E	1	296.00	296.00	A	352,189 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 426 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-213-3	184,614 Gallons	3020-05 E	1	296.00	296.00	A	184,614 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 501 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-214-3	184,476 Gallons	3020-05 E	1	296.00	296.00	A	184,476 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 502 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-215-3	184,682 Gallons	3020-05 E	1	296.00	296.00	A	184,682 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 503 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-216-3	185,169 Gallons	3020-05 E	1	296.00	296.00	A	185,169 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 504 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-217-3	251,301 Gallons	3020-05 E	1	296.00	296.00	A	251,301 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 505 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-218-3	251,909 Gallons	3020-05 E	1	296.00	296.00	A	251,909 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 506 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-219-3	185,400 Gallons	3020-05 E	1	296.00	296.00	A	185,400 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 511 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

Detailed Facility Report
For Facility=266 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-266-220-3	185,273 Gallons	3020-05 E	1	296.00	296.00	A	185,273 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 512 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-221-3	184,262 Gallons	3020-05 E	1	296.00	296.00	A	184,262 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 513 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-222-3	185,453 Gallons	3020-05 E	1	296.00	296.00	A	185,453 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 514 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-223-3	250,885 Gallons	3020-05 E	1	296.00	296.00	A	250,885 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 515 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-224-3	250,230 Gallons	3020-05 E	1	296.00	296.00	A	250,230 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 516 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-225-3	212,399 Gallons	3020-05 E	1	296.00	296.00	A	212,399 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 521 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-226-3	211,951 Gallons	3020-05 E	1	296.00	296.00	A	211,951 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 522 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-227-3	211,775 Gallons	3020-05 E	1	296.00	296.00	A	211,775 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 523 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-228-3	212,847 Gallons	3020-05 E	1	296.00	296.00	A	212,847 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 524 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-229-3	249,902 Gallons	3020-05 E	1	296.00	296.00	A	249,902 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 525 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-230-3	251,435 Gallons	3020-05 E	1	296.00	296.00	A	251,435 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 526 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-231-3	211,653 Gallons	3020-05 E	1	296.00	296.00	A	211,653 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 531 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-232-3	211,496 Gallons	3020-05 E	1	296.00	296.00	A	211,496 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 532 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-233-3	211,198 Gallons	3020-05 E	1	296.00	296.00	A	211,198 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 533 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

Detailed Facility Report
For Facility=266 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-266-234-3	212,367 Gallons	3020-05 E	1	296.00	296.00	A	212,367 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 534 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-235-3	251,482 Gallons	3020-05 E	1	296.00	296.00	A	251,482 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 535 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-236-3	250,731 Gallons	3020-05 E	1	296.00	296.00	A	250,731 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 536 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-237-3	56,046 Gallons	3020-05 D	1	223.00	223.00	A	56,046 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 601 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-238-3	55,572 Gallons	3020-05 D	1	223.00	223.00	A	55,572 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 602 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-239-3	55,824 Gallons	3020-05 D	1	223.00	223.00	A	55,824 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 603 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-240-3	55,815 Gallons	3020-05 D	1	223.00	223.00	A	55,815 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 604 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-241-3	55,778 Gallons	3020-05 D	1	223.00	223.00	A	55,778 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 611 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-242-3	55,572 Gallons	3020-05 D	1	223.00	223.00	A	55,572 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 612 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-243-3	55,825 Gallons	3020-05 D	1	223.00	223.00	A	55,825 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 613 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-244-3	55,592 Gallons	3020-05 D	1	223.00	223.00	A	55,592 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 614 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-245-3	49,395 Gallons	3020-05 C	1	165.00	165.00	A	49,395 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 621 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-246-3	49,771 Gallons	3020-05 C	1	165.00	165.00	A	49,771 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 622 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-247-3	49,226 Gallons	3020-05 C	1	165.00	165.00	A	49,226 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 623 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

Detailed Facility Report
For Facility=266 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-266-248-3	49,379 Gallons	3020-05 C	1	165.00	165.00	A	49,379 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 624 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-249-3	49,755 Gallons	3020-05 C	1	165.00	165.00	A	49,755 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 631 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-250-3	49,793 Gallons	3020-05 C	1	165.00	165.00	A	49,793 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 632 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-251-3	49,208 Gallons	3020-05 C	1	165.00	165.00	A	49,208 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 633 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-252-3	50,054 Gallons	3020-05 D	1	223.00	223.00	A	50,054 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 634 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-253-3	49,692 Gallons	3020-05 C	1	165.00	165.00	A	49,692 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 635 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-254-3	49,397 Gallons	3020-05 C	1	165.00	165.00	A	49,397 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 636 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-255-3	49,413 Gallons	3020-05 C	1	165.00	165.00	A	49,413 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 637 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-256-3	49,535 Gallons	3020-05 C	1	165.00	165.00	A	49,535 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 638 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-257-3	12,734 Gallons	3020-05 B	1	113.00	113.00	A	12,734 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 641 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-258-3	12,638 Gallons	3020-05 B	1	113.00	113.00	A	12,638 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 642 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-259-3	6,321 Gallons	3020-05 B	1	113.00	113.00	A	6,321 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 643 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-260-3	3,269 Gallons	3020-05 A	1	91.00	91.00	A	3,269 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 644 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-261-3	6,324 Gallons	3020-05 B	1	113.00	113.00	A	6,324 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 645 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

Detailed Facility Report
For Facility=266 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-266-262-3	6,311 Gallons	3020-05 B	1	113.00	113.00	A	6,311 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 646 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-263-3	6,324 Gallons	3020-05 B	1	113.00	113.00	A	6,324 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 647 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-264-3	12,766 Gallons	3020-05 B	1	113.00	113.00	A	12,766 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 651 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-265-3	12,703 Gallons	3020-05 B	1	113.00	113.00	A	12,703 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 652 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-266-3	6,311 Gallons	3020-05 B	1	113.00	113.00	A	6,311 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 653 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-267-3	6,317 Gallons	3020-05 B	1	113.00	113.00	A	6,317 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 654 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-268-3	6,313 Gallons	3020-05 B	1	113.00	113.00	A	6,313 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 655 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-269-3	6,317 Gallons	3020-05 B	1	113.00	113.00	A	6,317 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 656 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-270-3	6,314 Gallons	3020-05 B	1	113.00	113.00	A	6,314 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 657 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-271-3	12,740 Gallons	3020-05 B	1	113.00	113.00	A	12,740 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 661 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-272-3	12,740 Gallons	3020-05 B	1	113.00	113.00	A	12,740 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 662 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-273-3	12,740 Gallons	3020-05 B	1	113.00	113.00	A	12,740 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 663 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-274-3	12,740 Gallons	3020-05 B	1	113.00	113.00	A	12,740 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 664 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-275-3	12,722 Gallons	3020-05 B	1	113.00	113.00	A	12,722 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 665 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

Detailed Facility Report
For Facility=266 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-266-276-3	12,682 Gallons	3020-05 B	1	113.00	113.00	A	12,682 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 666 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-277-3	12,676 Gallons	3020-05 B	1	113.00	113.00	A	12,676 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 671 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-278-3	12,734 Gallons	3020-05 B	1	113.00	113.00	A	12,734 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 672 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-279-3	12,722 Gallons	3020-05 B	1	113.00	113.00	A	12,722 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 673 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-280-3	12,728 Gallons	3020-05 B	1	113.00	113.00	A	12,728 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 674 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-281-3	12,734 Gallons	3020-05 B	1	113.00	113.00	A	12,734 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 675 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-282-3	12,663 Gallons	3020-05 B	1	113.00	113.00	A	12,663 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 676 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-283-3	12,651 Gallons	3020-05 B	1	113.00	113.00	A	12,651 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 681 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-284-3	12,690 Gallons	3020-05 B	1	113.00	113.00	A	12,690 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 682 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-285-3	12,645 Gallons	3020-05 B	1	113.00	113.00	A	12,645 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 683 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-286-3	12,689 Gallons	3020-05 B	1	113.00	113.00	A	12,689 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 684 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-287-3	12,600 Gallons	3020-05 B	1	113.00	113.00	A	12,600 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 685 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-288-3	12,715 Gallons	3020-05 B	1	113.00	113.00	A	12,715 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 686 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-289-3	25,238 Gallons	3020-05 C	1	165.00	165.00	A	25,238 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 691 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

Detailed Facility Report
For Facility=266 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-266-290-3	25,090 Gallons	3020-05 C	1	165.00	165.00	A	25,090 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 692 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-291-3	25,105 Gallons	3020-05 C	1	165.00	165.00	A	25,105 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 693 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-292-3	25,114 Gallons	3020-05 C	1	165.00	165.00	A	25,114 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 694 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-293-3	25,107 Gallons	3020-05 C	1	165.00	165.00	A	25,107 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 695 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-294-3	44,361 Gallons	3020-05 C	1	165.00	165.00	A	44,361 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 801 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-295-3	44,412 Gallons	3020-05 C	1	165.00	165.00	A	44,412 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 802 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-296-3	44,404 Gallons	3020-05 C	1	165.00	165.00	A	44,404 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 803 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-297-3	44,395 Gallons	3020-05 C	1	165.00	165.00	A	44,395 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 804 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-298-3	44,240 Gallons	3020-05 C	1	165.00	165.00	A	44,240 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 805 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-299-3	44,206 Gallons	3020-05 C	1	165.00	165.00	A	44,206 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 806 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-300-3	44,257 Gallons	3020-05 C	1	165.00	165.00	A	44,257 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 807 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-301-3	44,362 Gallons	3020-05 C	1	165.00	165.00	A	49,362 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 808 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-302-3	44,413 Gallons	3020-05 C	1	165.00	165.00	A	44,413 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 809 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-303-3	44,395 Gallons	3020-05 C	1	165.00	165.00	A	44,395 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 810 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

Detailed Facility Report
For Facility=266 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-266-304-3	44,370 Gallons	3020-05 C	1	165.00	165.00	A	44,370 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 811 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-305-3	44,328 Gallons	3020-05 C	1	165.00	165.00	A	44,328 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 812 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-306-3	25,190 Gallons	3020-05 C	1	165.00	165.00	A	25,190 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 813 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-307-3	25,087 Gallons	3020-05 C	1	165.00	165.00	A	25,087 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 814 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-308-3	50,910 Gallons	3020-05 D	1	223.00	223.00	A	50,910 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 821 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-309-3	50,921 Gallons	3020-05 D	1	223.00	223.00	A	50,921 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 822 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-310-3	50,930 Gallons	3020-05 D	1	223.00	223.00	A	50,930 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 823 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-311-3	50,553 Gallons	3020-05 D	1	223.00	223.00	A	50,553 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 824 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-312-3	50,940 Gallons	3020-05 D	1	223.00	223.00	A	50,940 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 825 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-313-3	50,882 Gallons	3020-05 D	1	223.00	223.00	A	50,882 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 826 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-314-3	50,940 Gallons	3020-05 D	1	223.00	223.00	A	50,940 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 827 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-315-3	50,900 Gallons	3020-05 D	1	223.00	223.00	A	50,900 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 828 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-316-3	50,910 Gallons	3020-05 D	1	223.00	223.00	A	50,910 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 829 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-317-3	50,911 Gallons	3020-05 D	1	223.00	223.00	A	50,911 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 830 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

Detailed Facility Report
For Facility=266 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-266-318-3	50,966 Gallons	3020-05 D	1	223.00	223.00	A	50,966 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 831 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-319-3	50,872 Gallons	3020-05 D	1	223.00	223.00	A	50,872 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 832 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-320-3	25,271 Gallons	3020-05 C	1	165.00	165.00	A	25,271 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 833 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-321-4	25,238 Gallons	3020-05 C	1	165.00	165.00	A	25,238 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 834 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE.
N-266-322-3	50,890 Gallons	3020-05 D	1	223.00	223.00	A	50,892 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 841 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-323-3	50,706 Gallons	3020-05 D	1	223.00	223.00	A	50,706 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 842 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-324-3	50,747 Gallons	3020-05 D	1	223.00	223.00	A	50,747 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 843 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-325-3	50,706 Gallons	3020-05 D	1	223.00	223.00	A	50,706 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 844 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-326-3	51,097 Gallons	3020-05 D	1	223.00	223.00	A	51,097 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 845 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-327-3	80,687 Gallons	3020-05 D	1	223.00	223.00	A	80,687 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 846 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-328-3	50,716 Gallons	3020-05 D	1	223.00	223.00	A	50,716 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 847 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-329-3	50,745 Gallons	3020-05 D	1	223.00	223.00	A	50,745 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 848 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-330-3	50,892 Gallons	3020-05 D	1	223.00	223.00	A	50,892 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 849 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-331-3	50,706 Gallons	3020-05 D	1	223.00	223.00	A	50,706 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 850 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

Detailed Facility Report
For Facility=266 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-266-332-3	50,706 Gallons	3020-05 D	1	223.00	223.00	A	50,706 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 851 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-333-3	50,891 Gallons	3020-05 D	1	223.00	223.00	A	50,891 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 852 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-334-3	25,103 Gallons	3020-05 C	1	165.00	165.00	A	25,103 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 853 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-335-3	25,060 Gallons	3020-05 C	1	165.00	165.00	A	25,060 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 854 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-338-3	49,422 Gallons	3020-05 C	1	165.00	165.00	A	49,422 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1001 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-339-3	49,574 Gallons	3020-05 C	1	165.00	165.00	A	49,574 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1002 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-340-3	49,239 Gallons	3020-05 C	1	165.00	165.00	A	49,239 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1003 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-341-3	49,473 Gallons	3020-05 C	1	165.00	165.00	A	49,473 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1004 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-342-3	49,416 Gallons	3020-05 C	1	165.00	165.00	A	49,416 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1005 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-343-3	49,415 Gallons	3020-05 C	1	165.00	165.00	A	49,415 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1006 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-344-3	49,414 Gallons	3020-05 C	1	165.00	165.00	A	49,414 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1011 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-345-3	49,424 Gallons	3020-05 C	1	165.00	165.00	A	49,424 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1012 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-346-3	49,433 Gallons	3020-05 C	1	165.00	165.00	A	49,433 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1013 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-347-3	49,459 Gallons	3020-05 C	1	165.00	165.00	A	49,459 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1014 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

Detailed Facility Report
For Facility=266 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-266-348-3	49,597 Gallons	3020-05 C	1	165.00	165.00	A	49,597 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1015 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-349-3	49,435 Gallons	3020-05 C	1	165.00	165.00	A	49,435 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1016 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-350-3	25,565 Gallons	3020-05 C	1	165.00	165.00	A	25,565 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1021 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-351-3	25,655 Gallons	3020-05 C	1	165.00	165.00	A	25,655 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1022 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-352-3	25,573 Gallons	3020-05 C	1	165.00	165.00	A	25,573 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1023 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-353-3	25,565 Gallons	3020-05 C	1	165.00	165.00	A	25,565 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1024 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-354-3	25,573 Gallons	3020-05 C	1	165.00	165.00	A	25,573 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1025 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-355-3	25,628 Gallons	3020-05 C	1	165.00	165.00	A	25,628 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1026 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-356-3	25,655 Gallons	3020-05 C	1	165.00	165.00	A	25,655 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1027 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-357-3	25,655 Gallons	3020-05 C	1	165.00	165.00	A	25,655 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1031 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-358-3	25,565 Gallons	3020-05 C	1	165.00	165.00	A	25,565 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1032 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-359-3	25,565 Gallons	3020-05 C	1	165.00	165.00	A	25,565 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1033 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-360-3	25,647 Gallons	3020-05 C	1	165.00	165.00	A	25,647 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1034 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-361-3	25,557 Gallons	3020-05 C	1	165.00	165.00	A	25,557 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1035 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

Detailed Facility Report
For Facility=266 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-266-362-3	25,655 Gallons	3020-05 C	1	165.00	165.00	A	25,655 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1036 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-363-3	25,565 Gallons	3020-05 C	1	165.00	165.00	A	25,565 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1037 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-364-3	25,565 Gallons	3020-05 C	1	165.00	165.00	A	25,565 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1041 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-365-3	25,573 Gallons	3020-05 C	1	165.00	165.00	A	25,573 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1042 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-366-3	25,557 Gallons	3020-05 C	1	165.00	165.00	A	25,557 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1043 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-367-3	25,655 Gallons	3020-05 C	1	165.00	165.00	A	25,655 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1044 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-368-3	25,557 Gallons	3020-05 C	1	165.00	165.00	A	25,557 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1045 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-369-3	25,573 Gallons	3020-05 C	1	165.00	165.00	A	25,573 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1046 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-370-3	25,655 Gallons	3020-05 C	1	165.00	165.00	A	25,655 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1047 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-371-3	25,548 Gallons	3020-05 C	1	165.00	165.00	A	25,548 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1051 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-372-3	25,655 Gallons	3020-05 C	1	165.00	165.00	A	25,655 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1052 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-373-3	25,647 Gallons	3020-05 C	1	165.00	165.00	A	25,647 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1053 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-374-3	25,655 Gallons	3020-05 C	1	165.00	165.00	A	25,655 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1054 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-375-3	25,655 Gallons	3020-05 C	1	165.00	165.00	A	25,655 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1055 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

Detailed Facility Report
For Facility=266 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-266-376-3	25,672 Gallons	3020-05 C	1	165.00	165.00	A	25,672 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1056 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-377-3	25,573 Gallons	3020-05 C	1	165.00	165.00	A	25,573 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1057 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-378-3	12,664 Gallons	3020-05 B	1	113.00	113.00	A	12,664 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1061 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-379-3	12,604 Gallons	3020-05 B	1	113.00	113.00	A	12,604 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1062 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-380-3	12,675 Gallons	3020-05 B	1	113.00	113.00	A	12,675 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1063 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-381-3	12,651 Gallons	3020-05 B	1	113.00	113.00	A	12,651 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1064 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-382-3	12,664 Gallons	3020-05 B	1	113.00	113.00	A	12,644 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1065 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-383-3	12,593 Gallons	3020-05 B	1	113.00	113.00	A	12,593 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1066 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-384-3	12,593 Gallons	3020-05 B	1	113.00	113.00	A	12,593 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1067 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-385-3	12,589 Gallons	3020-05 B	1	113.00	113.00	A	12,589 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1068 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-386-3	12,593 Gallons	3020-05 B	1	113.00	113.00	A	12,593 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1069 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-387-3	12,522 Gallons	3020-05 B	1	113.00	113.00	A	12,522 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1070 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-388-3	12,640 Gallons	3020-05 B	1	113.00	113.00	A	12,640 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1081 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-389-3	12,649 Gallons	3020-05 B	1	113.00	113.00	A	12,649 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1082 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

Detailed Facility Report
For Facility=266 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-266-390-3	12,707 Gallons	3020-05 B	1	113.00	113.00	A	12,707 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1083 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-391-3	12,644 Gallons	3020-05 B	1	113.00	113.00	A	12,644 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1084 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-392-3	12,644 Gallons	3020-05 B	1	113.00	113.00	A	12,644 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1085 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-393-3	12,569 Gallons	3020-05 B	1	113.00	113.00	A	12,569 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1086 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-394-3	12,644 Gallons	3020-05 B	1	113.00	113.00	A	12,644 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1087 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-395-3	12,712 Gallons	3020-05 B	1	113.00	113.00	A	12,712 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1088 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-396-3	12,720 Gallons	3020-05 B	1	113.00	113.00	A	12,720 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1089 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-397-3	12,649 Gallons	3020-05 B	1	113.00	113.00	A	12,649 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1090 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-398-3	3,613 Gallons	3020-05 A	1	91.00	91.00	A	3,613 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1091 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-399-3	3,613 Gallons	3020-05 A	1	91.00	91.00	A	3,613 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1092 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-400-3	3,613 Gallons	3020-05 A	1	91.00	91.00	A	3,613 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1093 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-401-3	6,856 Gallons	3020-05 B	1	113.00	113.00	A	6,856 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1094 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-402-3	6,821 Gallons	3020-05 B	1	113.00	113.00	A	6,821 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1095 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-403-3	6,817 Gallons	3020-05 B	1	113.00	113.00	A	6,817 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1096 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

Detailed Facility Report
For Facility=266 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-266-404-3	6,871 Gallons	3020-05 B	1	113.00	113.00	A	6,871 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1097 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-405-3	6,821 Gallons	3020-05 B	1	113.00	113.00	A	6,821 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1098 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-406-3	6,853 Gallons	3020-05 B	1	113.00	113.00	A	6,853 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1099 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-407-3	6,244 Gallons	3020-05 B	1	113.00	113.00	A	6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1101 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-408-3	6,244 Gallons	3020-05 B	1	113.00	113.00	A	6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1102 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-409-3	6,244 Gallons	3020-05 B	1	113.00	113.00	A	6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1103 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-410-3	6,244 Gallons	3020-05 B	1	113.00	113.00	A	6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1104 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-411-3	6,244 Gallons	3020-05 B	1	113.00	113.00	A	6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1105 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-412-3	6,244 Gallons	3020-05 B	1	113.00	113.00	A	6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1106 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-413-3	6,244 Gallons	3020-05 B	1	113.00	113.00	A	6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1107 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-414-3	6,544 Gallons	3020-05 B	1	113.00	113.00	A	6,544 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1108 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-415-3	6,244 Gallons	3020-05 B	1	113.00	113.00	A	6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1109 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-416-3	6,244 Gallons	3020-05 B	1	113.00	113.00	A	6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1110 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-417-3	6,244 Gallons	3020-05 B	1	113.00	113.00	A	6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1111 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

Detailed Facility Report
For Facility=266 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-266-418-3	6,244 Gallons	3020-05 B	1	113.00	113.00	A	6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1121 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-419-3	6,244 Gallons	3020-05 B	1	113.00	113.00	A	6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1122 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-420-3	6,244 Gallons	3020-05 B	1	113.00	113.00	A	6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1123 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-421-3	6,244 Gallons	3020-05 B	1	113.00	113.00	A	6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1124 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-422-3	6,244 Gallons	3020-05 B	1	113.00	113.00	A	6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1125 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-423-3	6,244 Gallons	3020-05 B	1	113.00	113.00	A	6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1126 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-424-3	6,244 Gallons	3020-05 B	1	113.00	113.00	A	6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1127 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-425-3	6,244 Gallons	3020-05 B	1	113.00	113.00	A	6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1128 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-426-3	6,244 Gallons	3020-05 B	1	113.00	113.00	A	6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1129 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-427-3	6,244 Gallons	3020-05 B	1	113.00	113.00	A	6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1130 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-428-3	6,244 Gallons	3020-05 B	1	113.00	113.00	A	6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1131 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-429-3	6,244 Gallons	3020-05 B	1	113.00	113.00	A	6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1141 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-430-3	6,244 Gallons	3020-05 B	1	113.00	113.00	A	6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1142 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-431-3	6,244 Gallons	3020-05 B	1	113.00	113.00	A	6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1143 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

Detailed Facility Report
For Facility=266 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-266-432-3	6,244 Gallons	3020-05 B	1	113.00	113.00	A	6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1144 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-433-3	6,244 Gallons	3020-05 B	1	113.00	113.00	A	6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1145 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-434-3	6,244 Gallons	3020-05 B	1	113.00	113.00	A	6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1146 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-435-3	6,244 Gallons	3020-05 B	1	113.00	113.00	A	6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1147 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-436-3	6,244 Gallons	3020-05 B	1	113.00	113.00	A	6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1148 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-437-3	3,613 Gallons	3020-05 A	1	91.00	91.00	A	3,613 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1149 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-438-3	3,613 Gallons	3020-05 A	1	91.00	91.00	A	3,613 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1150 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-439-3	3,613 Gallons	3020-05 A	1	91.00	91.00	A	3,613 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1151 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-440-3	3,613 Gallons	3020-05 A	1	91.00	91.00	A	3,613 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1152 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-441-3	88,432 Gallons	3020-05 D	1	223.00	223.00	A	88,432 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1201 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-442-3	88,432 Gallons	3020-05 D	1	223.00	223.00	A	88,432 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1202 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-443-3	88,471 Gallons	3020-05 D	1	223.00	223.00	A	88,471 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1203 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-444-3	88,247 Gallons	3020-05 D	1	223.00	223.00	A	88,247 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1204 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-445-3	101,348 Gallons	3020-05 E	1	296.00	296.00	A	101,348 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1205 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

Detailed Facility Report
For Facility=266 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-266-446-3	102,041 Gallons	3020-05 E	1	296.00	296.00	A	102,041 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1206 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-447-3	101,637 Gallons	3020-05 E	1	296.00	296.00	A	101,637 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1207 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-448-3	101,750 Gallons	3020-05 E	1	296.00	296.00	A	101,750 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1208 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-449-3	88,281 Gallons	3020-05 D	1	223.00	223.00	A	88,281 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1211 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-450-3	88,526 Gallons	3020-05 D	1	223.00	223.00	A	88,526 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1212 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-451-3	88,264 Gallons	3020-05 D	1	223.00	223.00	A	88,264 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1213 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-452-3	88,459 Gallons	3020-05 D	1	223.00	223.00	A	88,459 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1214 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-453-3	101,234 Gallons	3020-05 E	1	296.00	296.00	A	101,234 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1215 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-454-3	101,638 Gallons	3020-05 E	1	296.00	296.00	A	101,638 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1216 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-455-3	102,042 Gallons	3020-05 E	1	296.00	296.00	A	102,042 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1217 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-456-3	101,703 Gallons	3020-05 E	1	296.00	296.00	A	101,703 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1218 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-457-3	49,867 Gallons	3020-05 C	1	165.00	165.00	A	49,867 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1221 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-458-3	50,030 Gallons	3020-05 D	1	223.00	223.00	A	50,030 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1222 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-459-3	49,869 Gallons	3020-05 C	1	165.00	165.00	A	49,869 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1223 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

Detailed Facility Report
For Facility=266 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-266-460-3	49,854 Gallons	3020-05 C	1	165.00	165.00	A	49,854 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1224 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-461-3	49,633 Gallons	3020-05 C	1	165.00	165.00	A	49,633 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1225 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-462-3	49,610 Gallons	3020-05 C	1	165.00	165.00	A	49,610 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1226 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-463-3	50,050 Gallons	3020-05 D	1	223.00	223.00	A	50,050 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1227 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-464-3	50,087 Gallons	3020-05 D	1	223.00	223.00	A	50,087 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1228 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-465-3	49,820 Gallons	3020-05 C	1	165.00	165.00	A	49,820 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1231 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-466-3	49,835 Gallons	3020-05 C	1	165.00	165.00	A	49,835 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1232 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-467-3	50,078 Gallons	3020-05 D	1	223.00	223.00	A	50,078 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1233 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-468-3	49,836 Gallons	3020-05 C	1	165.00	165.00	A	49,836 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1234 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-469-3	49,640 Gallons	3020-05 C	1	165.00	165.00	A	49,640 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1235 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-470-3	49,603 Gallons	3020-05 C	1	165.00	165.00	A	49,603 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1236 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-471-3	50,080 Gallons	3020-05 D	1	223.00	223.00	A	50,080 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1237 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-472-3	50,093 Gallons	3020-05 D	1	223.00	223.00	A	50,093 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1238 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-473-3	25,422 Gallons	3020-05 C	1	165.00	165.00	A	25,422 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1241 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

Detailed Facility Report
For Facility=266 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-266-474-3	25,512 Gallons	3020-05 C	1	165.00	165.00	A	25,512 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1242 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-475-3	25,381 Gallons	3020-05 C	1	165.00	165.00	A	25,381 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1243 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-476-3	25,495 Gallons	3020-05 C	1	165.00	165.00	A	25,495 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1244 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-477-3	25,403 Gallons	3020-05 C	1	165.00	165.00	A	25,403 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1245 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-478-3	25,501 Gallons	3020-05 C	1	165.00	165.00	A	25,501 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1246 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-479-3	25,422 Gallons	3020-05 C	1	165.00	165.00	A	25,422 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1247 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-480-3	25,414 Gallons	3020-05 C	1	165.00	165.00	A	25,414 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1248 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-481-3	25,414 Gallons	3020-05 C	1	165.00	165.00	A	25,414 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1249 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-482-3	25,299 Gallons	3020-05 C	1	165.00	165.00	A	25,299 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1250 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-483-3	25,532 Gallons	3020-05 C	1	165.00	165.00	A	25,532 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1251 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-484-3	25,633 Gallons	3020-05 C	1	165.00	165.00	A	25,633 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1252 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-485-3	25,565 Gallons	3020-05 C	1	165.00	165.00	A	25,565 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1253 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-486-3	25,442 Gallons	3020-05 C	1	165.00	165.00	A	25,442 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1254 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-487-3	25,403 Gallons	3020-05 C	1	165.00	165.00	A	25,403 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1255 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

Detailed Facility Report
For Facility=266 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-266-488-3	25,403 Gallons	3020-05 C	1	165.00	165.00	A	25,403 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1256 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-489-3	25,186 Gallons	3020-05 C	1	165.00	165.00	A	25,186 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1257 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-490-3	25,411 Gallons	3020-05 C	1	165.00	165.00	A	25,411 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1258 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-491-3	25,299 Gallons	3020-05 C	1	165.00	165.00	A	25,299 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1259 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-492-3	25,403 Gallons	3020-05 C	1	165.00	165.00	A	25,403 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1260 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-493-3	25,318 Gallons	3020-05 C	1	165.00	165.00	A	25,318 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1261 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-494-3	25,318 Gallons	3020-05 C	1	165.00	165.00	A	25,318 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1262 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-495-3	25,318 Gallons	3020-05 C	1	165.00	165.00	A	25,318 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1263 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-496-3	25,318 Gallons	3020-05 C	1	165.00	165.00	A	25,318 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1264 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-497-3	25,318 Gallons	3020-05 C	1	165.00	165.00	A	25,318 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1265 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-498-3	25,318 Gallons	3020-05 C	1	165.00	165.00	A	25,318 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1266 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-499-3	25,458 Gallons	3020-05 C	1	165.00	165.00	A	25,458 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1267 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-500-3	25,458 Gallons	3020-05 C	1	165.00	165.00	A	25,458 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1268 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-501-3	25,425 Gallons	3020-05 C	1	165.00	165.00	A	25,425 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1269 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

Detailed Facility Report
For Facility=266 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-266-502-3	25,425 Gallons	3020-05 C	1	165.00	165.00	A	25,425 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1270 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-503-5	5.978 MMBtu/hr	3020-02 G	1	980.00	980.00	A	5.978 MMBTU/HR FULTON BOILER EQUIPPED WITH FULTON MODEL 102347 BURNER
N-266-569-1	50,184 Gallons	3020-05 D	1	223.00	223.00	A	50,184 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1229 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-570-1	50,184 Gallons	3020-05 D	1	223.00	223.00	A	50,184 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1230 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-571-1	50,184 Gallons	3020-05 D	1	223.00	223.00	A	50,184 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1239 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-572-1	50,184 Gallons	3020-05 D	1	223.00	223.00	A	50,184 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1240 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-573-1	50,550 Gallons	3020-05 D	1	223.00	223.00	A	50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1271 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-574-1	50,550 Gallons	3020-05 D	1	223.00	223.00	A	50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1272 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-575-1	50,550 Gallons	3020-05 D	1	223.00	223.00	A	50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1273 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-576-1	50,550 Gallons	3020-05 D	1	223.00	223.00	A	50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1274 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-577-1	50,550 Gallons	3020-05 D	1	223.00	223.00	A	50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1401 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-578-1	50,550 Gallons	3020-05 D	1	223.00	223.00	A	50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1402 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-579-1	50,550 Gallons	3020-05 D	1	223.00	223.00	A	50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1403 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-580-1	50,550 Gallons	3020-05 D	1	223.00	223.00	A	50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1404 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

Detailed Facility Report
For Facility=266 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-266-581-1	50,550 Gallons	3020-05 D	1	223.00	223.00	A	50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1405 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-582-1	50,550 Gallons	3020-05 D	1	223.00	223.00	A	50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1406 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-583-1	50,550 Gallons	3020-05 D	1	223.00	223.00	A	50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1407 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-584-1	50,550 Gallons	3020-05 D	1	223.00	223.00	A	50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1408 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-585-1	50,550 Gallons	3020-05 D	1	223.00	223.00	A	50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1409 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-586-1	50,550 Gallons	3020-05 D	1	223.00	223.00	A	50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1410 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-587-1	50,550 Gallons	3020-05 D	1	223.00	223.00	A	50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1411 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-588-1	50,550 Gallons	3020-05 D	1	223.00	223.00	A	50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1412 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-589-1	50,550 Gallons	3020-05 D	1	223.00	223.00	A	50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1413 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-590-1	50,550 Gallons	3020-05 D	1	223.00	223.00	A	50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1414 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-591-1	50,550 Gallons	3020-05 D	1	223.00	223.00	A	50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1415 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-592-1	50,550 Gallons	3020-05 D	1	223.00	223.00	A	50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1416 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-593-1	50,550 Gallons	3020-05 D	1	223.00	223.00	A	50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1417 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-594-1	50,550 Gallons	3020-05 D	1	223.00	223.00	A	50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1418 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

Detailed Facility Report
For Facility=266 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-266-595-1	50,550 Gallons	3020-05 D	1	223.00	223.00	A	50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1419 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-596-1	50,550 Gallons	3020-05 D	1	223.00	223.00	A	50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1420 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-597-1	50,550 Gallons	3020-05 D	1	223.00	223.00	A	50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1421 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-599-1	50,550 Gallons	3020-05 D	1	223.00	223.00	A	50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1422 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-600-1	50,550 Gallons	3020-05 D	1	223.00	223.00	A	50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1423 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-601-1	50,550 Gallons	3020-05 D	1	223.00	223.00	A	50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1424 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-602-1	50,550 Gallons	3020-05 D	1	223.00	223.00	A	50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1425 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-603-1	50,550 Gallons	3020-05 D	1	223.00	223.00	A	50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1426 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-604-1	50,550 Gallons	3020-05 D	1	223.00	223.00	A	50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1427 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-605-1	50,550 Gallons	3020-05 D	1	223.00	223.00	A	50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1428 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-606-1	50,550 Gallons	3020-05 D	1	223.00	223.00	A	50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1431 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-607-1	50,550 Gallons	3020-05 D	1	223.00	223.00	A	50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1432 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-608-1	50,550 Gallons	3020-05 D	1	223.00	223.00	A	50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1433 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-609-1	50,550 Gallons	3020-05 D	1	223.00	223.00	A	50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1434 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

Detailed Facility Report
For Facility=266 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-266-610-1	50,550 Gallons	3020-05 D	1	223.00	223.00	A	50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1435 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-611-1	50,550 Gallons	3020-05 D	1	223.00	223.00	A	50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1436 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-612-1	50,550 Gallons	3020-05 D	1	223.00	223.00	A	50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1437 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-613-1	50,550 Gallons	3020-05 D	1	223.00	223.00	A	50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1438 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-614-1	103,660 Gallons	3020-05 E	1	296.00	296.00	A	103,660 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1441 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-615-1	103,660 Gallons	3020-05 E	1	296.00	296.00	A	103,660 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1442 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-616-1	103,660 Gallons	3020-05 E	1	296.00	296.00	A	103,660 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1443 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-617-1	103,660 Gallons	3020-05 E	1	296.00	296.00	A	103,660 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1444 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-618-1	103,660 Gallons	3020-05 E	1	296.00	296.00	A	103,660 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1451 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-619-1	103,660 Gallons	3020-05 E	1	296.00	296.00	A	103,660 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1452 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-620-1	103,660 Gallons	3020-05 E	1	296.00	296.00	A	103,660 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1453 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-621-1	103,660 Gallons	3020-05 E	1	296.00	296.00	A	103,660 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1454 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-622-1	103,660 Gallons	3020-05 E	1	296.00	296.00	A	103,660 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1461 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-623-1	103,660 Gallons	3020-05 E	1	296.00	296.00	A	103,660 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1462 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

Detailed Facility Report
For Facility=266 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-266-624-1	103,660 Gallons	3020-05 E	1	296.00	296.00	A	103,660 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1463 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-625-1	103,660 Gallons	3020-05 E	1	296.00	296.00	A	103,660 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1464 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-626-1	103,660 Gallons	3020-05 E	1	296.00	296.00	A	103,660 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1465 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-627-1	103,660 Gallons	3020-05 E	1	296.00	296.00	A	103,660 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1466 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-628-1	103,660 Gallons	3020-05 E	1	296.00	296.00	A	103,660 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1471 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-629-1	103,660 Gallons	3020-05 E	1	296.00	296.00	A	103,660 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1472 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-630-1	103,660 Gallons	3020-05 E	1	296.00	296.00	A	103,660 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1473 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-631-1	103,660 Gallons	3020-05 E	1	296.00	296.00	A	103,660 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1474 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-632-1	103,660 Gallons	3020-05 E	1	296.00	296.00	A	103,660 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1475 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-633-1	103,660 Gallons	3020-05 E	1	296.00	296.00	A	103,660 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1476 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-634-1	74,000 Gallons	3020-05 D	1	223.00	223.00	A	74,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 185 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-635-1	74,000 Gallons	3020-05 D	1	223.00	223.00	A	74,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 186 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-636-1	74,000 Gallons	3020-05 D	1	223.00	223.00	A	74,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 193 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-637-1	74,000 Gallons	3020-05 D	1	223.00	223.00	A	74,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 194 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

Detailed Facility Report
For Facility=266 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-266-638-1	74,000 Gallons	3020-05 D	1	223.00	223.00	A	74,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 195 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-639-1	74,000 Gallons	3020-05 D	1	223.00	223.00	A	74,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 196 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-640-3	Miscellaneous	3020-06	1	128.00	128.00	A	ORGANIC WASTE AND FEEDSTOCK MATERIAL RECEIVING, STORAGE, AND MIXING OPERATION.
N-266-641-3	Miscellaneous	3020-06	1	128.00	128.00	A	OPEN WINDROW ACTIVE AND CURING PHASE ORGANIC MATERIAL COMPOSTING OPERATION WITH AN INDEPENDENT WATERING SYSTEM SERVING THE ACTIVE-PHASE COMPOSTING WINDROW PILES.
N-266-642-2	Miscellaneous	3020-06	1	128.00	128.00	A	FINISHED COMPOST LOADOUT OPERATION.
N-266-643-1	25,000 gal	3020-05 C	1	165.00	165.00	A	25,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B22 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-644-1	25,000 gal	3020-05 C	1	165.00	165.00	A	25,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B24 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-645-1	25,000 gal	3020-05 C	1	165.00	165.00	A	25,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B19 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-646-1	25,000 gal	3020-05 C	1	165.00	165.00	A	25,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B20 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-647-1	25,000 gal	3020-05 C	1	165.00	165.00	A	25,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B21 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-648-1	25,000 gal	3020-05 C	1	165.00	165.00	A	25,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B23 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-649-1	14,000 gal	3020-05 B	1	113.00	113.00	A	14,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B08 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-650-1	14,000 gal	3020-05 B	1	113.00	113.00	A	14,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B09 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-651-1	14,000 gal	3020-05 B	1	113.00	113.00	A	14,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B17 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

Detailed Facility Report
For Facility=266 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-266-652-1	14,000 gal	3020-05 B	1	113.00	113.00	A	14,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B18 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-653-1	12,700 gal	3020-05 B	1	113.00	113.00	A	12,700 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B06 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-654-1	12,700 gal	3020-05 B	1	113.00	113.00	A	12,700 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B07 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-655-1	12,700 gal	3020-05 B	1	113.00	113.00	A	12,700 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B15 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-656-1	12,700 gal	3020-05 B	1	113.00	113.00	A	12,700 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B16 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-657-1	8,500 gal	3020-05 B	1	113.00	113.00	A	8,500 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B04 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-658-1	8,500 gal	3020-05 B	1	113.00	113.00	A	8,500 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B05 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-659-1	8,500 gal	3020-05 B	1	113.00	113.00	A	8,500 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B13 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-660-1	8,500 gal	3020-05 B	1	113.00	113.00	A	8,500 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B14 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-661-1	6,200 gal	3020-05 B	1	113.00	113.00	A	6,200 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B01 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-662-1	6,200 gal	3020-05 B	1	113.00	113.00	A	6,200 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B02 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-663-1	6,200 gal	3020-05 B	1	113.00	113.00	A	6,200 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B03 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-664-1	6,200 gal	3020-05 B	1	113.00	113.00	A	6,200 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B10 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-665-1	6,200 gal	3020-05 B	1	113.00	113.00	A	6,200 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B11 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

Detailed Facility Report
For Facility=266 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-266-666-1	6,200 gal	3020-05 B	1	113.00	113.00	A	6,200 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B12 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-667-1	200,000 gallons	3020-05 E	1	296.00	296.00	A	200,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 352 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-668-1	200,000 gallons	3020-05 E	1	296.00	296.00	A	200,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 353 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-669-1	200,000 gallons	3020-05 E	1	296.00	296.00	A	200,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 354 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-670-1	200,000 gallons	3020-05 E	1	296.00	296.00	A	200,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 355 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-671-1	200,000 gallons	3020-05 E	1	296.00	296.00	A	200,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 356 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-672-1	200,000 gallons	3020-05 E	1	296.00	296.00	A	200,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 362 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-673-1	200,000 gallons	3020-05 E	1	296.00	296.00	A	200,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 363 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-674-1	200,000 gallons	3020-05 E	1	296.00	296.00	A	200,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 364 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-675-1	200,000 gallons	3020-05 E	1	296.00	296.00	A	200,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 365 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-676-1	200,000 gallons	3020-05 E	1	296.00	296.00	A	200,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 366 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-678-1	70,000 gallon	3020-05 D	1	223.00	223.00	A	70,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 712 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-679-1	70,000 gallon	3020-05 D	1	223.00	223.00	A	70,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 714 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-680-1	70,000 gallon	3020-05 D	1	223.00	223.00	A	70,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 715 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

Detailed Facility Report
For Facility=266 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-266-681-1	70,000 gallon	3020-05 D	1	223.00	223.00	A	70,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 716 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-682-1	70,000 gallon	3020-05 D	1	223.00	223.00	A	70,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 717 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-683-1	70,000 gallon	3020-05 D	1	223.00	223.00	A	70,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 718 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-684-1	70,000 gallon	3020-05 D	1	223.00	223.00	A	70,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 719 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-685-1	70,000 gallon	3020-05 D	1	223.00	223.00	A	70,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 720 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-686-1	70,000 gallon	3020-05 D	1	223.00	223.00	A	70,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 721 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-687-1	70,000 gallon	3020-05 D	1	223.00	223.00	A	70,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 722 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-688-1	70,000 gallon	3020-05 D	1	223.00	223.00	A	70,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 723 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-689-1	70,000 gallon	3020-05 D	1	223.00	223.00	A	70,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 724 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-690-1	70,000 gallon	3020-05 D	1	223.00	223.00	A	70,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 725 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-691-1	70,000 gallon	3020-05 D	1	223.00	223.00	A	70,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 726 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-692-1	70,000 gallon	3020-05 D	1	223.00	223.00	A	70,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 727 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-693-1	70,000 gallon	3020-05 D	1	223.00	223.00	A	70,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 728 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-694-1	70,000 gallon	3020-05 D	1	223.00	223.00	A	70,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 729 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

Detailed Facility Report
For Facility=266 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-266-695-1	70,000 gallon	3020-05 D	1	223.00	223.00	A	70,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 730 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-696-1	70,000 gallon	3020-05 D	1	223.00	223.00	A	70,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 731 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-697-1	70,000 gallon	3020-05 D	1	223.00	223.00	A	70,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 733 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-698-1	154,000 gallon	3020-05 E	1	296.00	296.00	A	154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1507 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-699-1	154,000 gallon	3020-05 E	1	296.00	296.00	A	154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1508 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-700-1	154,000 gallon	3020-05 E	1	296.00	296.00	A	154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1509 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-701-1	154,000 gallon	3020-05 E	1	296.00	296.00	A	154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1510 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-702-1	154,000 gallon	3020-05 E	1	296.00	296.00	A	154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1517 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-703-1	154,000 gallon	3020-05 E	1	296.00	296.00	A	154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1518 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-704-1	154,000 gallon	3020-05 E	1	296.00	296.00	A	154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1519 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-705-1	154,000 gallon	3020-05 E	1	296.00	296.00	A	154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1520 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-706-1	154,000 gallon	3020-05 E	1	296.00	296.00	A	154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1527 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-707-1	154,000 gallon	3020-05 E	1	296.00	296.00	A	154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1528 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-708-1	154,000 gallon	3020-05 E	1	296.00	296.00	A	154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1529 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

Detailed Facility Report
For Facility=266 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-266-709-1	154,000 gallon	3020-05 E	1	296.00	296.00	A	154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1530 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-710-1	154,000 gallon	3020-05 E	1	296.00	296.00	A	154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1537 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-711-1	154,000 gallon	3020-05 E	1	296.00	296.00	A	154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1538 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-712-1	154,000 gallon	3020-05 E	1	296.00	296.00	A	154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1539 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-713-1	154,000 gallon	3020-05 E	1	296.00	296.00	A	154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1540 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-714-1	154,000 gallon	3020-05 E	1	296.00	296.00	A	154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1547 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-715-1	154,000 gallon	3020-05 E	1	296.00	296.00	A	154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1548 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-716-1	154,000 gallon	3020-05 E	1	296.00	296.00	A	154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1549 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-717-1	154,000 gallon	3020-05 E	1	296.00	296.00	A	154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1550 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-718-1	154,000 gallon	3020-05 E	1	296.00	296.00	A	154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1557 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-719-1	154,000 gallon	3020-05 E	1	296.00	296.00	A	154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1558 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-720-1	154,000 gallon	3020-05 D	1	223.00	223.00	A	154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1559 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-721-1	154,000 gallon	3020-05 E	1	296.00	296.00	A	154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1560 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-722-1	25,000 gallons	3020-05 C	1	165.00	165.00	A	25,000 GALLON, INSULATED, STAINLESS STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 2501 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

Detailed Facility Report
For Facility=266 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-266-723-1	25,000 gallons	3020-05 C	1	165.00	165.00	A	25,000 GALLON, INSULATED, STAINLESS STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 2502 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-724-1	25,000 gallons	3020-05 C	1	165.00	165.00	A	25,000 GALLON, INSULATED, STAINLESS STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 2503 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-725-1	25,000 gallons	3020-05 C	1	165.00	165.00	A	25,000 GALLON, INSULATED, STAINLESS STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 2504 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-726-1	25,000 gallons	3020-05 C	1	165.00	165.00	A	25,000 GALLON, INSULATED, STAINLESS STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 2511 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-727-1	25,000 Gallons	3020-05 C	1	165.00	165.00	A	25,000 GALLON, INSULATED, STAINLESS STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 2512 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-728-1	25,000 gallons	3020-05 C	1	165.00	165.00	A	25,000 GALLON, INSULATED, STAINLESS STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 2513 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-729-1	25,000 gallons	3020-05 C	1	165.00	165.00	A	25,000 GALLON, INSULATED, STAINLESS STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 2514 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-730-1	13,000 gallons	3020-05 B	1	113.00	113.00	A	13,000 GALLON, INSULATED, STAINLESS STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1321 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-731-1	13,000 gallons	3020-05 B	1	113.00	113.00	A	13,000 GALLON, INSULATED, STAINLESS STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1322 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-732-1	13,000 gallons	3020-05 B	1	113.00	113.00	A	13,000 GALLON, INSULATED, STAINLESS STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1323 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-733-1	13,000 gallons	3020-05 B	1	113.00	113.00	A	13,000 GALLON, INSULATED, STAINLESS STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1324 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-734-1	13,000 gallons	3020-05 B	1	113.00	113.00	A	13,000 GALLON, INSULATED, STAINLESS STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1325 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-735-1	13,000 gallons	3020-05 B	1	113.00	113.00	A	13,000 GALLON, INSULATED, STAINLESS STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1326 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-736-1	13,000 gallons	3020-05 B	1	113.00	113.00	A	13,000 GALLON, INSULATED, STAINLESS STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1327 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

Detailed Facility Report
For Facility=266 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-266-737-1	13,000 gallons	3020-05 B	1	113.00	113.00	A	13,000 GALLON, INSULATED, STAINLESS STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1328 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-738-1	7,000 gallons	3020-05 B	1	113.00	113.00	A	7,000 GALLON, INSULATED, STAINLESS STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1314 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-739-1	7,000 gallons	3020-05 B	1	113.00	113.00	A	7,000 GALLON, INSULATED, STAINLESS STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1315 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-740-1	7,000 gallons	3020-05 B	1	113.00	113.00	A	7,000 GALLON, INSULATED, STAINLESS STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1319 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-741-1	7,000 gallon	3020-05 B	1	113.00	113.00	A	7,000 GALLON, INSULATED, STAINLESS STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1320 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE
N-266-742-1	154,000 gallon	3020-05 E	1	296.00	296.00	A	154,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1505 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION
N-266-743-1	154,000 gallon	3020-05 E	1	296.00	296.00	A	154,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1506 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION
N-266-744-1	154,000 gallon	3020-05 E	1	296.00	296.00	A	154,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1515 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION
N-266-745-1	154,000 gallon	3020-05 E	1	296.00	296.00	A	154,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1516 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION
N-266-746-1	154,000 gallon	3020-05 E	1	296.00	296.00	A	154,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1525 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION
N-266-747-1	154,000 gallon	3020-05 E	1	296.00	296.00	A	154,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1526 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION
N-266-748-1	154,000 gallon	3020-05 E	1	296.00	296.00	A	154,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1536 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION
N-266-749-1	154,000 gallon	3020-05 E	1	296.00	296.00	A	154,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1535 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION
N-266-750-1	60,000 gallon	3020-05 D	1	223.00	223.00	A	60,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 230 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

Detailed Facility Report
For Facility=266 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-266-751-1	60,000 gallon	3020-05 D	1	223.00	223.00	A	60,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 231 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION
N-266-752-1	60,000 gallon	3020-05 D	1	223.00	223.00	A	60,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 232 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION
N-266-753-1	60,000 gallon	3020-05 D	1	223.00	223.00	A	60,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 233 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION
N-266-754-1	60,000 gallon	3020-05 D	1	223.00	223.00	A	60,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 234 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION
N-266-755-1	60,000 gallon	3020-05 D	1	223.00	223.00	A	60,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 235 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION
N-266-756-1	60,000 gallon	3020-05 D	1	223.00	223.00	A	60,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 236 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION
N-266-757-1	60,000 gallon	3020-05 D	1	223.00	223.00	A	60,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 237 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION
N-266-758-1	60,000 gallon	3020-05 D	1	223.00	223.00	A	60,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 239 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION
N-266-759-1	60,000 gallon	3020-05 D	1	223.00	223.00	A	60,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 243 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION
N-266-760-1	25,000 gallon	3020-05 C	1	165.00	165.00	A	25,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 2505 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION
N-266-761-1	25,000 gallon	3020-05 C	1	165.00	165.00	A	25,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 2506 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION
N-266-762-1	25,000 gallon	3020-05 C	1	165.00	165.00	A	25,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 2515 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION
N-266-763-1	25,000 gallon	3020-05 C	1	165.00	165.00	A	25,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 2516 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION
N-266-764-1	13,000 gallon	3020-05 B	1	113.00	113.00	A	13,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1329 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

Detailed Facility Report
For Facility=266 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-266-765-1	13,000 gallon	3020-05 B	1	113.00	113.00	A	13,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1330 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION
N-266-766-1	13,000 gallon	3020-05 B	1	113.00	113.00	A	13,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1331 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION
N-266-767-1	13,000 gallon	3020-05 B	1	113.00	113.00	A	13,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1332 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION
N-266-768-1	13,000 gallon	3020-05 B	1	113.00	113.00	A	13,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1333 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION
N-266-769-1	13,000 gallon	3020-05 B	1	113.00	113.00	A	13,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1334 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION
N-266-770-1	13,000 gallon	3020-05 B	1	113.00	113.00	A	13,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1335 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION
N-266-771-1	13,000 gallon	3020-05 B	1	113.00	113.00	A	13,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1336 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION
N-266-772-1	7,000 gallon	3020-05 B	1	113.00	113.00	A	7,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1312 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION
N-266-773-1	7,000 gallon	3020-05 B	1	113.00	113.00	A	7,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1313 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION
N-266-774-1	7,000 gallon	3020-05 B	1	113.00	113.00	A	7,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1317 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION
N-266-775-1	7,000 gallon	3020-05 B	1	113.00	113.00	A	7,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1318 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION
N-266-776-1	154,000 gallons	3020-05 E	1	296.00	296.00	A	154,000 GALLON (OR EQUIVALENT) WINE STORAGE TANK (TANK #1545) WITH PRESSURE/VACUUM VALVE AND INSULATION
N-266-777-1	154,000 gallons	3020-05 E	1	296.00	296.00	A	154,000 GALLON (OR EQUIVALENT) WINE STORAGE TANK (TANK #1546) WITH PRESSURE/VACUUM VALVE AND INSULATION
N-266-778-1	60,000 gallons	3020-05 D	1	223.00	223.00	A	60,000 GALLON (OR EQUIVALENT) WINE STORAGE TANK (TANK #242) WITH PRESSURE/VACUUM VALVE AND INSULATION
N-266-779-1	60,000 gallons	3020-05 D	1	223.00	223.00	A	60,000 GALLON (OR EQUIVALENT) WINE STORAGE TANK (TANK #238) WITH PRESSURE/VACUUM VALVE AND INSULATION

Detailed Facility Report
For Facility=266 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-266-780-1	60,000 gallons	3020-05 D	1	223.00	223.00	A	60,000 GALLON (OR EQUIVALENT) WINE STORAGE TANK (TANK #240) WITH PRESSURE/VACUUM VALVE AND INSULATION
N-266-781-1	60,000 gallons	3020-05 D	1	223.00	223.00	A	60,000 GALLON (OR EQUIVALENT) WINE STORAGE TANK (TANK #241) WITH PRESSURE/VACUUM VALVE AND INSULATION
N-266-782-1	60,000 gallons	3020-05 D	1	223.00	223.00	A	60,000 GALLON (OR EQUIVALENT) WINE STORAGE TANK (TANK #244) WITH PRESSURE/VACUUM VALVE AND INSULATION
N-266-783-1	60,000 gallons	3020-05 D	1	223.00	223.00	A	60,000 GALLON (OR EQUIVALENT) WINE STORAGE TANK (TANK #245) WITH PRESSURE/VACUUM VALVE AND INSULATION
N-266-784-1	154,433 gallon	3020-05 E	1	296.00	296.00	A	154,000 GALLON NOMINAL (154,433 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1502) WITH PRESSURE/VACUUM VALVE AND INSULATION
N-266-785-1	154,443 gallon	3020-05 E	1	296.00	296.00	A	154,000 GALLON NOMINAL (154,443 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1503) WITH PRESSURE/VACUUM VALVE AND INSULATION
N-266-786-1	153,888 gallon	3020-05 E	1	296.00	296.00	A	154,000 GALLON NOMINAL (153,888 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1504) WITH PRESSURE/VACUUM VALVE AND INSULATION
N-266-787-1	153,785 gallon	3020-05 E	1	296.00	296.00	A	154,000 GALLON NOMINAL (153,785 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1511) WITH PRESSURE/VACUUM VALVE AND INSULATION
N-266-788-1	154,308 gallon	3020-05 E	1	296.00	296.00	A	154,000 GALLON NOMINAL (154,308 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1512) WITH PRESSURE/VACUUM VALVE AND INSULATION
N-266-789-1	154,435 gallon	3020-05 E	1	296.00	296.00	A	154,000 GALLON NOMINAL (154,435 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1513) WITH PRESSURE/VACUUM VALVE AND INSULATION
N-266-790-1	153,842 gallon	3020-05 E	1	296.00	296.00	A	154,000 GALLON NOMINAL (153,842 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1514) WITH PRESSURE/VACUUM VALVE AND INSULATION
N-266-791-1	153,537 gallon	3020-05 E	1	296.00	296.00	A	154,000 GALLON NOMINAL (153,537 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1521) WITH PRESSURE/VACUUM VALVE AND INSULATION
N-266-792-1	153,932 gallon	3020-05 E	1	296.00	296.00	A	154,000 GALLON NOMINAL (153,932 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1522) WITH PRESSURE/VACUUM VALVE AND INSULATION
N-266-793-1	153,842 gallon	3020-05 E	1	296.00	296.00	A	154,000 GALLON NOMINAL (153,842 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1523) WITH PRESSURE/VACUUM VALVE AND INSULATION
N-266-794-1	153,986 gallon	3020-05 E	1	296.00	296.00	A	154,000 GALLON NOMINAL (153,986 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1524) WITH PRESSURE/VACUUM VALVE AND INSULATION

Detailed Facility Report
For Facility=266 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-266-795-1	153,365 gallon	3020-05 E	1	296.00	296.00	A	154,000 GALLON NOMINAL (153,365 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK #(1531) WITH PRESSURE/VACUUM VALVE AND INSULATION
N-266-796-1	154,523 gallon	3020-05 E	1	296.00	296.00	A	154,000 GALLON NOMINAL (154,523 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1532) WITH PRESSURE/VACUUM VALVE AND INSULATION
N-266-797-1	154,208 gallon	3020-05 E	1	296.00	296.00	A	154,000 GALLON NOMINAL (154,208 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1533) WITH PRESSURE/VACUUM VALVE AND INSULATION
N-266-798-1	154,066 gallon	3020-05 E	1	296.00	296.00	A	154,000 GALLON NOMINAL (154,066 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1534) WITH PRESSURE/VACUUM VALVE AND INSULATION
N-266-799-1	153,935 gallon	3020-05 E	1	296.00	296.00	A	154,000 GALLON NOMINAL (153,935 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1541) WITH PRESSURE/VACUUM VALVE AND INSULATION
N-266-800-1	154,107 gallon	3020-05 E	1	296.00	296.00	A	154,000 GALLON NOMINAL (154,107 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1542) WITH PRESSURE/VACUUM VALVE AND INSULATION
N-266-801-1	153,458 gallon	3020-05 E	1	296.00	296.00	A	154,000 GALLON NOMINAL (153,458 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1543) WITH PRESSURE/VACUUM VALVE AND INSULATION
N-266-802-1	153,940 gallon	3020-05 E	1	296.00	296.00	A	154,000 GALLON NOMINAL (153,940 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1544) WITH PRESSURE/VACUUM VALVE AND INSULATION
N-266-803-1	154,170 gallon	3020-05 E	1	296.00	296.00	A	154,000 GALLON NOMINAL (154,170 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1551) WITH PRESSURE/VACUUM VALVE AND INSULATION
N-266-804-1	154,342 gallon	3020-05 E	1	296.00	296.00	A	154,000 GALLON NOMINAL (154,342 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1552) WITH PRESSURE/VACUUM VALVE AND INSULATION
N-266-805-1	153,842 gallon	3020-05 E	1	296.00	296.00	A	154,000 GALLON NOMINAL (153,842 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1553) WITH PRESSURE/VACUUM VALVE AND INSULATION
N-266-806-1	103,315 gallon	3020-05 E	1	296.00	296.00	A	103,000 GALLON NOMINAL (103,315 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1161) WITH PRESSURE/VACUUM VALVE AND INSULATION
N-266-807-1	103,315 gallon	3020-05 E	1	296.00	296.00	A	103,000 GALLON NOMINAL (103,315 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1162) WITH PRESSURE/VACUUM VALVE AND INSULATION
N-266-808-1	103,826 gallon	3020-05 E	1	296.00	296.00	A	103,000 GALLON NOMINAL (103,826 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1163) WITH PRESSURE/VACUUM VALVE AND INSULATION

Detailed Facility Report
For Facility=266 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-266-809-1	103,705 gallon	3020-05 E	1	296.00	296.00	A	103,000 GALLON NOMINAL (103,705 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1164) WITH PRESSURE/VACUUM VALVE AND INSULATION
N-266-810-1	103,477 gallon	3020-05 E	1	296.00	296.00	A	103,000 GALLON NOMINAL (103,477 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1171) WITH PRESSURE/VACUUM VALVE AND INSULATION
N-266-811-1	103,712 gallon	3020-05 E	1	296.00	296.00	A	103,000 GALLON NOMINAL (103,712 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1172) WITH PRESSURE/VACUUM VALVE AND INSULATION
N-266-812-1	103,351 gallon	3020-05 E	1	296.00	296.00	A	103,000 GALLON NOMINAL (103,351 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1173) WITH PRESSURE/VACUUM VALVE AND INSULATION
N-266-813-1	103,302 gallon	3020-05 E	1	296.00	296.00	A	103,000 GALLON NOMINAL (103,302 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1174) WITH PRESSURE/VACUUM VALVE AND INSULATION
N-266-814-1	103,603 gallon	3020-05 E	1	296.00	296.00	A	103,000 GALLON NOMINAL (103,603 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1181) WITH PRESSURE/VACUUM VALVE AND INSULATION
N-266-815-1	103,480 gallon	3020-05 E	1	296.00	296.00	A	103,000 GALLON NOMINAL (103,480 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1182) WITH PRESSURE/VACUUM VALVE AND INSULATION
N-266-816-1	103,508 gallon	3020-05 E	1	296.00	296.00	A	103,000 GALLON NOMINAL (103,508 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1183) WITH PRESSURE/VACUUM VALVE AND INSULATION
N-266-817-1	102,777 gallon	3020-05 E	1	296.00	296.00	A	103,000 GALLON NOMINAL (102,777 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1184) WITH PRESSURE/VACUUM VALVE AND INSULATION
N-266-818-1	103,408 gallon	3020-05 E	1	296.00	296.00	A	103,000 GALLON NOMINAL (103,408 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1191) WITH PRESSURE/VACUUM VALVE AND INSULATION
N-266-819-1	103,088 gallon	3020-05 E	1	296.00	296.00	A	103,000 GALLON NOMINAL (103,088 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1192) WITH PRESSURE/VACUUM VALVE AND INSULATION
N-266-820-1	102,901 gallon	3020-05 E	1	296.00	296.00	A	103,000 GALLON NOMINAL (102,901 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1193) WITH PRESSURE/VACUUM VALVE AND INSULATION
N-266-821-1	103,826 gallon	3020-05 E	1	296.00	296.00	A	103,000 GALLON NOMINAL (103,826 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1194) WITH PRESSURE/VACUUM VALVE AND INSULATION

Detailed Facility Report
For Facility=266 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-266-950-0	61,330 gallon	3020-05 D	1	223.00	223.00	A	DIATOMACEOUS EARTH (DE) MATERIAL RECEIVING, STORAGE, AND TRANSFER OPERATION CONSISTING OF ONE 8,200 CUBIC FOOT STORAGE SILO SERVED BY FOUR DYNAMIC AIR MODEL MODU-KLEEN SERIES 343/200 BIN VENT FILTERS, AND THREE ENCLOSED HOPPERS EACH SERVED BY A DYNAMIC AIR MODEL MODU-KLEEN SERIES 343/200 BIN VENT FILTER
N-266-952-0	250 bhp IC Engine	3020-10 C	1	290.00	290.00	A	250 BHP (INTERMITTENT) JOHN DEERE MODEL 6068HF485T TIER 3 CERTIFIED DIESEL-FIRED EMERGENCY STANDBY IC ENGINE POWERING A FIRE PUMP
N-266-953-0	302 bhp IC engine	3020-10 C	1	290.00	290.00	A	302 BHP (INTERMITTENT) DOOSAN MODEL D111L RICH-BURN NATURAL GAS-FIRED EMERGENCY STANDBY IC ENGINE WITH NON-SELECTIVE CATALYTIC REDUCTION (NSCR) POWERING AN ELECTRICAL GENERATOR

Number of Facilities Reported: 1